SQL ASSIGNMENT – 2

1. Create a database named MovieBooking.

   Query:
   create database Movie_Booking;

2. Create a table named Movies with the following columns: Movie_ID, Movie_Name, Genre, Language, Duration, Release_Year.

   Query:
   create table Movies(
   Movie_ID int,
   Movie_Name varchar(30),
   Genre varchar(30),
   Language varchar(30),
   Duration int,
   Release_Year year);

3. Create a table named Customers with: Customer_ID, Customer_Name, Email, Phone, Age.

   Query:
   create table Customer(
   Customer_ID int,
   Customer_Name varchar(30),
   Email varchar(30),
   Phone varchar(15),
   Age int);

4. Create a table named Bookings with: Booking_ID, Customer_ID, Movie_ID, Theatre_ID, Booking_Date, Tickets, Total_Amount.

Query:

```
create table booking(
Booking_ID int,
Customer_ID int,
Movie_ID int,
Theatre_ID int,
Booking_date date,
Tickets int,
Total_amount int);
```

5. Create a theatre table with : theatre_ID, theatre_name, location, Phone.

   Query:

   ```
   Theatre_ID int,
   Theatre_name varchar(30),
   location varchar(30),
   Phone varchar(15));
   ```

6. Add a new column Rating to the Movies table.

   Query:

   ```
   alter table Movies
   add column Ratings int;
   ```

7. Add a new column Seat_Type to the Bookings table

   Query:

   ```
   alter table Booking
   add column Seat_type varchar(30);
   ```

8. Change the size of the Movie_Name column to VARCHAR(150).

Query:

```
alter table Movies
modify column Movie_Name varchar(150);
```

9. Rename the column Phone to Mobile_Number in the Customers table.

Query:

```
alter table Customer
rename column Phone to Mobile_Number;
```

10. Rename the table Theatres to Cinema_Halls

Query:

```
rename table theatres to Cinema_halls;
```

11. Remove the Rating column from the Movies table

Query:

```
alter table Movies
drop column ratings;
```

12. Create a backup table named Movies_Backup using the structure and data of the Movies table.

Query:

```
create table Movies_backup
like Movies;
```

13. Display the structure of all four tables.

Query:

describe Booking;

Field	Type	Null	Key	Default	Extra
Booking_ID	int	YES		NULL	
Customer_ID	int	YES		NULL	
Movie_ID	int	YES		NULL	
Theatre_ID	int	YES		NULL	
Booking_date	date	YES		NULL	
Tickets	int	YES		NULL	
Total_amount	int	YES		NULL	

Result 3

describe Cinema_halls;

Field	Type	Null	Key	Default	Extra
Theatre_ID	int	YES		NULL	
Theatre_name	varchar(30)	YES		NULL	
location	varchar(30)	YES		NULL	
Phone	varchar(15)	YES		NULL	

describe Customer;

Field	Type	Null	Key	Default	Extra
Customer_ID	int	YES		NULL	
Customer_Name	varchar(30)	YES		NULL	
Email	varchar(30)	YES		NULL	
Mobile_Number	varchar(15)	YES		NULL	
Age	int	YES		NULL	

describe Movies;


Field	Type	Null	Key	Default	Extra
Movie_ID	int	YES		NULL	
Movie_Name	varchar(150)	YES		NULL	
Genre	varchar(30)	YES		NULL	
Language	varchar(30)	YES		NULL	
Duration	int	YES		NULL	
Release_Year	year	YES		NULL	

14. Display all databases available in MySQL

Query:

```
show databases;
```

Output:



15. Delete the entire Movies_Backup table from the database.

Query:

```
drop table movies_backup;
```

16. Delete all bookings where the number of tickets is 0.

Query:

```
delete from booking
where tickets = 0;
```

17. A particular customer permanently deleted their account. Delete the customer whose Customer_ID is 105.

Query:

```
delete from customer
where Customer_ID = 105;
```

18. A theatre has stopped operating. Delete the theatre record with Theatre_ID = 4.

Query:

```
delete from cinema_halls
where theatre_ID = 0004;
```

19. Remove all booking records made before 2025-01-01.

Query:

```
delete from booking
where Booking_date < '2025-01-01';
```

20. Delete all movies belonging to the Horror genre.

Query:

```
delete from movies
where genre = 'horror';
```

21. A movie is no longer available in the application. Delete the movie with Movie_ID = 110.

Query:

```
delete from movies
where Movie_ID = 110;
```

22. Delete all customers whose age is below 18.

Query:

```
delete from Customer
where Age < 18;
```

23. The management wants to clear all booking records while keeping the Bookings table structure. Write a query for this requirement.

Query:

```
truncate table booking;
```