

Filter

URL API

URL

Constructor

URL()

Instance properties

hash

host

hostname

href

origin

password

pathname

port

protocol

search

searchParams

username

Static methods

canParse()

createObjectURL()

parse()

revokeObjectURL()

Instance methods

toJSON()

toString()

Related pages for URL API

URLSearchParams

Guides

Resolving relative references to a URL

URL: URL() constructor

Baseline Widely available

Note: This feature is available in [Web Workers](#).

The `URL()` constructor returns a newly created `URL` object representing the URL defined by the parameters.

If the given base URL or the resulting URL are not valid URLs, the JavaScript `TypeError` exception is thrown.

Syntax

JS

```
new URL(url)
new URL(url, base)
```

Copy

Parameters

`url`

A string or any other object with a [stringifier](#) that represents an absolute URL or a relative reference to a base URL. If `url` is a relative reference, `base` is required, and is used to resolve the final URL. If `url` is an absolute URL, a given `base` will not be used to create the resulting URL.

`base`

Optional

A string representing the base URL to use in cases where `url` is a relative reference. If not specified, it defaults to `undefined`.

When a `base` is specified, the resolved URL is not simply a concatenation of `url` and `base`. Relative references to the parent and current directory are resolved relative to the current directory of the `base` URL, which includes path segments up until the last forward-slash, but not any after. Relative references to the root are resolved relative to the base origin. For more information see [Resolving relative references to a URL](#).

Note: The `url` and `base` arguments will each be stringified from whatever value you pass, such as an `HTMLAnchorElement` or `HTMLAreaElement` element, just like with other Web APIs that accept a string. In particular, you can use an existing `URL` object for either argument, and it will be stringified from the object's `href` property.

In this article

- Syntax
- Examples
- Specifications
- Browser compatibility
- See also

Mozilla Data Collective

Get open datasets
The language datasets you've been missing

Join Now

Exceptions

TypeError

`url` (in the case of absolute URLs) or `base` + `url` (in the case of relative references) is not a valid URL.

Examples

Here are some examples of using the constructor.

 **Note:** [Resolving relative references to a URL](#) provides additional examples demonstrating how different `url` and `base` values are resolved to a final absolute URL.

JS

Copy

```
// Base URLs:

let baseUrl = "https://developer.mozilla.org";

let a = new URL("/", baseUrl);
// => 'https://developer.mozilla.org/'

let b = new URL(baseUrl);
// => 'https://developer.mozilla.org/'

new URL("en-US/docs", b);
// => 'https://developer.mozilla.org/en-US/docs'

let d = new URL("/en-US/docs", b);
// => 'https://developer.mozilla.org/en-US/docs'

new URL("/en-US/docs", d);
// => 'https://developer.mozilla.org/en-US/docs'

new URL("/en-US/docs", a);
// => 'https://developer.mozilla.org/en-US/docs'

new URL("/en-US/docs", "https://developer.mozilla.org/fr-FR/toto");
// => 'https://developer.mozilla.org/en-US/docs'
```

Here are some examples of invalid URLs:

JS

Copy

```
new URL("/en-US/docs", "");
// Raises a TypeError exception as '' is not a valid URL

new URL("/en-US/docs");
// Raises a TypeError exception as '/en-US/docs' is not a valid URL

// Other cases:

new URL("http://www.example.com");
// => 'http://www.example.com/'

new URL("http://www.example.com", B);
// => 'http://www.example.com/'

new URL("", "https://example.com/?query=1");
// => 'https://example.com/?query=1' (Edge before 79 removes query arguments)

new URL("/a", "https://example.com/?query=1");
// => 'https://example.com/a' (see relative URLs)
```

```
// => "https://example.com/a" (see relative URLs)

new URL("//foo.example", "https://example.com");
// => 'https://foo.example/' (see relative URLs)
```

Specifications

Specification
URL # dom-url-url 

Browser compatibility

[Report problems with this compatibility data](#)  • [View data on GitHub](#) 

	
	
	
	Chrome 
	Edge 
	Firefox 
	Opera 
	Safari 
	Chrome Android 
	Firefox for Android 
	Opera Android 
	Safari on iOS 
	Samsung Internet 
	WebView Android 
	WebView on iOS 

	 Bun
	 Deno
	 Node.js
URL () constructor	
✓ Chrome 19	
✓ Edge 12 *	
✓ Firefox 26 *	
✓ Opera 15	
✓ Safari 14.1 ...	
✓ Chrome Android 25	
✓ Firefox for Android 26 *	
✓ Opera Android 14	
✓ Safari on iOS 14.5 ...	
✓ Samsung Internet 1.5	
✓ WebView Android 4.4	
✓ WebView on iOS 14.5 ...	
✓ Bun 1	
✓ Deno 1	
✓ Node.js 6.13	

Tip: you can click/tap on a cell for more information.

✓ Full support ⌚ Partial support * See implementation notes. ... Has more compatibility info.

See also

- `URL.parse()` , a non-throwing alternative to this constructor
- [Polyfill of URL in core-js](#) ↗
- The interface it belongs to: `URL` .

Help improve MDN

Was this page helpful to you?

 Yes

 No

[Learn how to contribute](#)

This page was last modified on Nov 9, 2025 by [MDN contributors](#).

[View this page on GitHub](#) ↗ • [Report a problem with this content](#) ↗



Your blueprint for a better internet.



MDN

[About](#)

[Blog](#)

[Mozilla careers](#) ↗


[Advertise with us](#)

[MDN Plus](#)

[Product help](#) ↗

Contribute

MDN Community



The best way to build AI apps.



AD

[Community resources](#)

[Writing guidelines](#)

[MDN Discord](#) 

[MDN on GitHub](#) 

Developers

[Web technologies](#)

[Learn web development](#)

[Guides](#)

[Tutorials](#)

[Glossary](#)

[Hacks blog](#) 



[Website Privacy Notice](#)  [Telemetry Settings](#)  [Legal](#)  [Community Participation Guidelines](#) 

Visit [Mozilla Corporation's](#) not-for-profit parent, the [Mozilla Foundation](#).

Portions of this content are ©1998–2026 by individual mozilla.org contributors. Content available under [a Creative Commons license](#).