

Update Documents

```
>db.collectionname.updateOne(<filter>,<update>,<options>);  
>db.collectionname.updateMany(<filter>,<update>,<options>);  
>db.collectionname.replaceOne(<filter>,<update>,<options>);
```

```
> db.emp.updateOne({"EID" : 1025},  
                    {$set: {"ADDRESS" : "B302 PRAGYA  
APARTMENTS, DWARKA, DELHI", "PHONE" : 9899245970} }  
                    );
```

```
> db.salary.updateMany({$and: [{"DEPT" : "HR"}, {"DESI" :  
"ASSOCIATE"}]}}, {$set: {"DESI" : "SR. ASSOCIATE"}});
```



Update Documents

```
>db.collectionname.updateMany(<filter>,<update>,<options>);
```

```
> db.salary.updateMany(  
    {$and: [{"DEPT" : "HR"},  
            {"DESI" : "ASSOCIATE"}]},  
    {$set: {"DESI" : "SR. ASSOCIATE"}}  
);  
  
> db.stu2.updateMany(  
    {},  
    {"$set" : {"class" : "8th"}});
```



Update Documents

```
>db.collectionname.replaceOne(<filter>,<update>,<options>);
```

```
> db.stu.replaceOne(  
    {"rno" : 2},  
    {"rno" : 3 ,"name" : "ajay kumar",  
    "age" : 16}  
    );
```

Note: _id remains same the document has been replaced



ASSIGNMENT



- Create a database demo
- Create a EMP collection.
- Insert 8 documents containing in EMP collection containing eid, name, city, doj, dept, desi
- Display the documents in formatted manner.
- Show the documents containing “HR” dept.
- Show the documents for “OPS” managers.
- Promote all the associates as Sr.Associates

MongoDb CRUD Operations

CRUD operations create, read, update, and delete operations on documents

Create Operations – to create a new document

```
db.collection.insertOne()
```

```
db.collection.insertMany()
```

Read Operations – to retrieve the document from collection

```
db.collection.find()
```

```
db.collection.findOne()
```



MongoDb CRUD Operations

Update Operations – to modify existing documents in a collection.

```
db.collection.updateOne()
```

```
db.collection.updateMany()
```

```
db.collection.replaceOne()
```

Delete Operations – to remove documents from a collection.

```
db.collection.deleteOne()
```

```
db.collection.deleteMany()
```



Inserting Documents

`db.collection.save()` can also be used to insert document into a collection.

If you don't specify `_id` in the document then **`save()`** method will work same as **`insert()`** method. If you specify `_id` then it will replace whole data of document containing `_id` as specified in `save()` method.

```
> db.stu2.save({"rno" : 7, "name" : "inderjeet singh", "age" : 15});
```

```
> db.stu2.save({"_id" :
```

```
    ObjectId("608fb168ea90e1f913d52714"),  
    "rno" : 8,  
    "name" : "Inder kumar singh",  
    "age" : 16}
```

```
);
```



Logical Operator in MongoDB

To query documents based on the AND condition, we need to use \$and keyword.

```
>db.collection.find({ $and: [ {<key1>:<value1>}, { <key2>:<value2>} ] })
```

```
> db.sal.find({  
    $and:[  
        {"DEPT" : "HR"},  
        {"DESI" : "ASSOCIATE"}  
    ]  
});
```

Note: and is the default logical operator when working with multiple conditions.

```
> db.sal.find({"DEPT" : "HR", "DESI" : "ASSOCIATE"});
```



Logical Operator in MongoDB

To query documents based on the OR condition, we need to use \$or keyword.

```
>db.collection.find({ $or: [ {<key1>:<value1>}, { <key2>:<value2>} ] })
```

```
> db.sal.find(  
    {$or:[  
        {"DEPT" : "HR"},  
        {"DESI" : "ASSOCIATE"}  
    ]  
});
```



Logical Operator in MongoDB

To query documents based on the NOT condition, we need to use \$not keyword.

```
> db.salary.find(  
    {"DEPT" :  
      {$not:  
        {$eq : "HR"}}  
    }  
  );
```



Logical Operator in MongoDB

NOR is the combination of NOT and OR, we need to use \$nor keyword.

```
> db.salary.find({$nor:  
  [  
    { "DESI" : "ASSOCIATE"},  
    {"DEPT" : "HR"}  
  ]  
});
```



Comparison Operator in MongoDB

\$eq: Equality Operator same as where dept = 'hr' in SQL

Syntax : {<key>:{**\$eq**;<value>}}

Eg1: > db.sal.find({"DEPT" :{\$eq : "HR"}});

Eg2: > db.sal.find({"DEPT" : "HR"});

\$ne: Not equal to Operator same as where dept <> 'hr' in SQL

Syntax : {<key>:{**\$ne**;<value>}}

Eg: > db.sal.find({"DEPT" :{\$ne : "HR"}});



Comparison Operator in MongoDB

\$lt: less than Operator same as where salary < 100000 in SQL

Syntax: {<key>:{\$lt:<value>}}

Eg: > db.sal.find({"SALARY" :{\$lt : 50000}});

\$lte: less than or equal to Operator same as where salary <= 50000 in SQL

Syntax: {<key>:{\$lte:<value>}}

Eg: > db.sal.find({"SALARY" :{\$lte : 50000}});



Comparison Operator in MongoDB

\$gt: greater than or equal to Operator same as where salary >= 50000 in SQL

Syntax: {<key>:{\$gt:<value>}}

Eg: > db.sal.find({"SALARY" :{\$gt : 50000}});

\$gte: greater than or equal to Operator same as where salary >= 50000 in SQL

Syntax: {<key>:{\$gte:<value>}}

Eg: > db.sal.find({"SALARY" :{\$gte : 50000}});



Comparison Operator in MongoDB

\$in: represents values in an array same as where dept in ('hr', 'it', 'admin')

Syntax: {<key>:{\$in:[<value1>, <value2>,.....<valueN>]}}

```
Eg: > db.sal.find({"DEPT" :  
                    {$in :  
                      ["HR", "IT", "TEMP"]  
                    }  
                });
```

\$nin: represents values not in an array same as where NOT dept in ('hr', 'it', 'admin')

Syntax: {<key>:{\$nin:[<value1>, <value2>,.....<valueN>]}}

```
Eg: > db.sal.find({"DEPT" :{$nin : ["HR", "IT", "TEMP","ADMIN"]}});
```



Operators Examples

```
> db.orders.find({"Category" : {"$eq" : "Technology"},"Sub-Category" : {"$eq" : "Phones"}}).count()
> db.salary.find({"$and" : [{"DEPT" : {"$eq" : "HR"}}, {"DESI" : {"$eq" : "ASSOCIATE"}}]})
> db.salary.find({"$and" : [{"DEPT" : "HR"}, {"DESI" : "ASSOCIATE"}]})
> db.salary.find({"$and" : [{"$or" : [{"DEPT" : "HR"}, {"DEPT" : "MIS"}]}, {"$or" : [{"DESI" : "MANAGER"}, {"DESI" : "SR. ASSOCIATE"}]}]})
> db.salary.find({"SALARY" : {"$not" : {"$gt" : 100000}}})
```



Importing Data

For importing the data we need to download MongoDB Database Tools.

<https://www.mongodb.com/try/download/database-tools>

Download the Zip file

Unzip the downloaded file – Browse to the bin folder – Copy mongoimport application - paste it under the bin folder of MongoDB

C:\Program Files\MongoDB\Server\4.4\bin

Go to the command prompt and run mongoimport application



Importing Data

Flags used with mongoimport command.

-d: Specifies what database to use. We used the demo database.

-c: Specifies what collection to use. We used a sal collection.

--type: Specifies the type of file to import. json, csv, or tsv. We are using csv

--headerline: Specifies that the first row in our csv file should be the field names.

--drop: Specifies that we want to drop the collection before importing documents to avoid duplicate documents.

```
>mongoimport -d demo -c sal --type csv --file Salary.csv --headerline --drop
```

```
>mongoimport -d demo2 -c sal --type csv --file C:\Users\Raj\Desktop\Salary.csv --headerline --drop
```



Delete Documents

- >`db.collectionname.deleteOne({})` – delete one document even though specified criteria returns multiple documents.
- >`db.collectionname.deleteMany({})` – delete all documents returned by the specified criteria.
- >`db.collectionname.remove({},Just One)` – delete a single or all documents returned by the specified criteria.

Note: `db.collectionname.deleteMany({})` –this will delete all the documents.



Delete Documents

```
>db.collectionname.deleteOne()
```

```
>db.temp.insertMany([
```

```
  {"id" : 1, "name" : "a" , "age" : 15},
```

```
  {"id" : 2, "name" : "b" , "age" : 15},
```

```
  {"id" : 3, "name" : "c" , "age" : 16},
```

```
  {"id" : 4, "name" : "d" , "age" : 14},
```

```
  {"id" : 5, "name" : "e" , "age" : 13},
```

```
  {"id" : 6, "name" : "f" , "age" : 15},
```

```
  {"id" : 7, "name" : "g" , "age" : 16},
```

```
  {"id" : 8, "name" : "h" , "age" : 14},
```

```
  {"id" : 9, "name" : "i" , "age" : 13},
```

```
  {"id" : 10, "name" : "j" , "age" : 15}]])
```

```
> db.temp.deleteOne({"id" : 10});
```



Delete Documents

```
>db.collectionname.deleteMany()
```

```
> db.temp.deleteMany({"age" : 14});
```

```
> db.temp.deleteMany({});
```



Delete Documents

>db.collectionname.remove() – delete a single or all documents returned by the specified criteria.

> db.temp.remove({"age" : 15}); - remove all documents with the matching criteria

> db.temp.remove({"age" : 15},true); - remove first document with the matching criteria

> db.temp.remove({"age" : 15},1); - remove first document with the matching criteria



Projections

Projections means selecting the required data rather than selecting the entire data of document. If a document has 5 fields and you need to show only 3, then select only 3 fields from them.

The second optional parameter of the find() method is the list of fields we need to retrieve.

```
>db.collectionname.find({}, {key : 1})
```

1 is used to display a field & 0 is used to hide a field

```
> db.emp.find({}, {"EID" :1, "NAME" :1 ,"DOJ" : 1});
```

```
> db.emp.find({}, {"DOJ" : 0, "DOB" : 0, "ADDRESS" :0});
```



Limiting Documents

limit() method is used to restrict the no of documents to be retrieved. The method accepts one number type argument, which is the number of documents that you want to be displayed

```
>db.COLLECTION_NAME.find().limit(NUMBER)
```

```
> db.salary.find({}).limit(10);
```

The **skip()** method along with the **limit()** method is used to skip the number of documents.

```
>db.COLLECTION_NAME.find().limit(NUMBER).skip(NUMBER)
```

```
> db.salary.find({}).limit(2).skip(1);
```



ASSIGNMENT



- Import the emp & salary csv files and perform the below actions on the data:
- List the documents of Managers having salary more than 100000.
- List the documents of employees from either IT or ADMIN team.
- Remove the documents of TEMP employees