

ForgeCore Industries

B2B Manufacturer of Industrial Crucibles & Foundry Consumables

Founded 1987 — Pittsburgh, Pennsylvania, USA

Product Catalogue — 2025 Edition

ForgeCore Industries has been a trusted supplier of high-performance crucibles and foundry consumables for over 35 years. Our product line serves foundries, smelters, and research laboratories across 40+ countries. Each product is engineered for durability, thermal stability, and consistent performance in demanding industrial environments.

Product Family Overview

SKU	Material	Max Temp (°C)	Primary Use
FC-45	Silicon Carbide	1,500	Ferrous metal melting
FC-50	High-purity Graphite	1,800	Non-ferrous metals, copper alloys
FC-72	Clay-Graphite Composite	1,300	Aluminum and zinc casting
FC-90	Zircon (ZrSiO ₄)	2,000	Precious metals, specialty alloys
FC-AX	Alumina Ceramic	1,750	High-purity laboratory melting
FC-MX	Magnesia Refractory	1,600	Slag-line protection

Detailed Product Descriptions

FC-45 — Silicon Carbide Crucible

Our flagship product. FC-45 is engineered for high-temperature ferrous metal melting applications including iron and steel production. The silicon carbide composition offers exceptional thermal conductivity and resistance to thermal shock.

Specification	Value
Operating Temperature	Up to 1,500°C
Standard Sizes	S, M, L, XL
Wall Thickness	12-25 mm
Typical Lifespan	300-500 heats

FC-50 — High-Purity Graphite Crucible

Designed for non-ferrous metal melting, particularly copper alloys, brass, and bronze. The high-purity graphite construction provides excellent thermal conductivity and minimal contamination risk for sensitive alloys.

Specification	Value
Operating Temperature	Up to 1,800°C
Standard Sizes	S, M, L, XL, XXL
Carbon Content	99.5% min
Typical Lifespan	200-400 heats

FC-72 — Clay-Graphite Composite Crucible

An economical choice for aluminum and zinc casting operations. The clay-graphite blend balances cost and performance for high-volume production foundries.

Specification	Value
Operating Temperature	Up to 1,300°C
Standard Sizes	S, M, L
Density	2.1 g/cm ³
Typical Lifespan	150-250 heats

FC-90 — Zircon Crucible

A premium crucible for precious metals and specialty alloys. Zircon (zirconium silicate) offers outstanding chemical inertness and the highest temperature rating in our lineup.

Specification	Value
Operating Temperature	Up to 2,000°C
Standard Sizes	S, M, L
ZrO ₂ Content	65% min
Typical Lifespan	100-200 heats

Ordering Information

Orders can be placed via your regional ForgeCore sales representative or through our customer portal at orders.forgecore.example.com. Standard sizes ship within 5 business days; custom dimensions require a

4-6 week lead time. All crucibles ship in protective foam-lined wooden crates with full handling documentation.

Minimum order quantities apply for custom sizes: 25 units for FC-45 and FC-50, 50 units for FC-72, and 10 units for FC-90. Volume discounts are available for orders exceeding 100 units.

Technical Support and Warranty

All ForgeCore products are backed by a 12-month limited warranty against manufacturing defects. Our applications engineering team provides complimentary sizing and material selection consultations. Contact support@forgecore.example.com or call +1-412-555-0142.