ASSIGNMENT 2

GIT COMMANDS Commands used for local Git repository setup and GitHub connection

1. git --version: This command checks whether Git is installed on the computer and displays the version of Git currently installed. It is useful for verifying the Git installation before starting Git operations.

2. git init: This command initializes a new Git repository in the current project folder. It creates the hidden .git directory, which allows Git to track changes and maintain the project's version history.

3. git status: This command displays the current state of the Git repository. It shows the active branch and indicates which files are untracked, modified, staged, or ready to be committed.

4. git add . : This command adds all new and modified files from the current folder to the Git staging area. Staging prepares the selected files to be included in the next commit.

5. git commit -m "Initial commit": This command permanently records the staged changes in the local Git repository. The message "Initial commit" describes this first saved version of the project.

6. git branch -M main: This command changes the name of the current branch to main. The main branch is commonly used as the primary branch for a project.

7. git remote -v: This command displays the remote repositories connected to the local Git repository. It helps verify the fetch and push URLs used to communicate with GitHub.

8. git remote add origin <GitHub-URL>: This command connects the local Git repository to a GitHub repository. The name origin is used as the standard short name for the remote GitHub repository.

9. git push -u origin main: This command uploads the local main branch and its committed files to the GitHub repository. The -u option establishes a tracking relationship between the local main branch and origin/main, making future pushes easier.

```
C:\Users\dell\Desktop\PRACHI102>git --version
git version 2.55.0.windows.5
```

```
C:\Users\dell\Desktop\PRACHI102>git push -u origin main --force
Enumerating objects: 18, done.
Counting objects: 100% (18/18), done.
Delta compression using up to 8 threads
Compressing objects: 100% (18/18), done.
Writing objects: 100% (18/18), 232.68 KiB | 9.31 MiB/s, done.
Total 18 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/PrachiMohite2507/fullstack-practice
 + 07e1ab7...a06d392 main -> main (forced update)
branch 'main' set up to track 'origin/main'.
```

```
C:\Users\dell\Desktop\PRACHI102>git init
Initialized empty Git repository in C:/Users/dell/Desktop/PRACHI102/.git/

C:\Users\dell\Desktop\PRACHI102>git add .

C:\Users\dell\Desktop\PRACHI102>git commit -m "Initial commit"
[master (root-commit) a06d392] Initial commit
 13 files changed, 503 insertions(+)
 create mode 100644 Assignment 1/Contact.html
 create mode 100644 Assignment 1/Foundation.jpg
 create mode 100644 Assignment 1/Lipstick.jpg
 create mode 100644 Assignment 1/background.jpg
 create mode 100644 Assignment 1/eyeshdow.jfif
 create mode 100644 Assignment 1/index.html
 create mode 100644 Assignment 1/powder.jpg
 create mode 100644 Assignment 1/product.html
 create mode 100644 Assignment 1/styles1.css
 create mode 100644 Assignment 3/index.html
 create mode 100644 Assignment 3/style.css
 create mode 100644 Assignment 4/index.html
 create mode 100644 Assignment 4/style4.css

C:\Users\dell\Desktop\PRACHI102>git branch -M main

C:\Users\dell\Desktop\PRACHI102>git remote add origin https://github.com/PrachiMohite2507/fullstack-practice
```