CS G525 ADVANCED COMPUTER NETWORKS · BITS PILANI

Progress Review II

Project SA7 · Reactive vs. Proactive Flow Installation in OpenFlow SDN

Project: Empirical Evaluation of Reactive vs. Proactive Flow Installation in OpenFlow SDN
Group: 2
Members: N. NISARG VAGH, D. DHADUK MRUDUL HITESHBHAI, PRACHIT SURESH DESHINGE, Mukul Saini
Review date: 30 October 2026 (Progress Review II: working implementation, full experiments, preliminary analysis)
Code and raw data: https://github.com/PrachitDeshinge-324/Openflow_SDN
Version: 15 October 2026, with the Step 4 results (budgeted hybrid, long timeouts, oracle)

---

0. At a glance

The question. In OpenFlow SDN, a switch needs a rule before it can forward a packet. There are two ways to get one:

- **reactive:** ask the controller when the first packet of a flow arrives;
- **proactive:** install every rule in advance.

Which is better, by how much, and when?

Everything below is measured on Mininet 2.3.0 + Open vSwitch 3.7.1 (kernel datapath) + POX 0.7.0. It ran on our laptops (Windows 11, WSL2) with our own instrumented controllers.

Since Review I we added	Headline result (reactive vs proactive)
Networks with many paths: a data-centre **fat-tree** and the real **Abilene** ISP backbone	Reactive's paths are up to **4.5× longer in delay**. Real pings are **51% slower** (40.5 vs 26.9 ms). Proactive always uses a best path.
Load balancing (ECMP) as a third controller	In the fat-tree, ECMP carries **50% more traffic** than reactive (95 vs 64 Mbit/s) and leaves only 16% of links idle (reactive leaves 59%).
University traffic (Benson et al., IMC 2010)	Small flows: **median 55.7 ms reactive vs 1.3 ms proactive (44×)**. The controller ran at **86% CPU** with 2,379 requests/s.
Data-centre traffic (DCTCP web search, VL2 data mining)	Small flows are **8–10× faster with proactive ECMP**, and large flows **3–3.6× faster**.
Real ISP traffic (Abilene traffic matrices, 2004)	Small flows: **median 120 vs 48 ms (2.5×)**. Measured split (Section 6): **44 ms from the spanning tree's detours, 26 ms from asking the controller**.
Budgeted hybrid (new controller): a weighted counter keeps the busiest host pairs pre-installed, within a rule budget	With 25% of pairs pre-installed: **52–68% of new connections skip the controller**, 2.3–2.9× fewer controller requests and 2.0–2.5× fewer rules than reactive. The simple counter gets **within 6–12% of an oracle** that knows the future traffic (25–50% budgets).
Long timeouts (60 s / 300 s; the SmartTime idea in its simplest form)	**No gain in 4 of 4 scenarios**, and 2.3–2.9× more rules.
Review I **reproduced on a second laptop**	Same patterns, identical rule counts.

Every flow finished in every run (0 failures), and every controller got exactly the same traffic. Step 4 numbers are from one run per configuration; repeats with 95% confidence intervals are the next step (Section 9).

---

1. Response to the Review I feedback

Review I score: 7.5 / 10. The feedback, and what we did:

Feedback	What we did	Where
"Previous eval done and improvements done"	This report: Review I recap (Section 2), all new work (Sections 4–7), reproduced on a second laptop	Sections 2, 4–7
"Increase the traffic like uni traffic, data centre, ISP"	Four realistic workloads, each from a published measurement: university, data-centre web search, data-centre data mining, and real Abilene ISP traffic matrices	Section 5
"Parameters for evaluation: optimal path vs haphazard path"	New networks with many paths. We measured path stretch, delay, throughput and link balance for reactive (haphazard), proactive (optimal) and proactive ECMP	Section 4
"Cmp with previous works / papers which already has predictor, traffic gen, emulator, etc."	Literature review of 14 papers (11 checked in full text), plus a survey of 28 prediction/ML rule papers and what they compare against. Our numbers are set next to theirs, and every network and traffic choice is traced to a paper. **Two published ideas now run as baselines on our testbed**: long timeouts (SmartTime / AH-IHTA) and a budgeted cache of popular rules (CacheFlow / PARD), plus an **oracle** that bounds what any predictor, ML included, could gain.	Sections 6, 7, `docs/literature/`, `docs/Evaluation_Plan.md`
"Run on multiple comps using distributed switches in lab"	**Tool ready, run pending.** POX can now run on a second PC (`controller_agent.py` + `--controller-host`), with the WSL2 networking steps documented. It is tested end to end on one machine; the two-PC run needs a second laptop.	Section 9, `docs/Controller_On_Second_PC.md`

---

2. Recap: Review I results, now reproduced

Setup. Tree networks with 4, 8 and 16 computers. Two instrumented POX controllers:


- `reactive_eval`: the same logic as POX's `l2_learning`, with exact-match rules (idle 10 s, hard 30 s);
- `proactive_eval`: one rule per host pair on its shortest path, installed when the switch connects.

Measurement (laptop 1, 27 Sep)	4 computers	8 computers	16 computers
First packet, reactive (ms)	3.81	6.60	5.44
First packet, proactive (ms)	0.67	0.86	0.77
Later packets, both (ms)	0.06–0.09	0.07–0.09	0.09
Rules, proactive / reactive with all pairs active	28 / 28	216 / 216	624 / 624
Rules after 5 s of 200 new flows/s: reactive vs proactive	2,321 vs 28	3,857 vs 216	2,631 vs 624
Controller at 200 new flows/s, reactive: PACKET_IN/s, CPU	465, 20.8%	786, 36.4%	544, 31.6%

Reproduced on laptop 2 (9 Oct). Same software, a different machine:

- First packet, reactive: 7.2 / 11.4 / 8.7 ms; proactive: 1.0 / 1.5 / 1.0 ms.
- Rule counts were **identical**.

- At 200 new flows/s: 477 / 782 / 535 PACKET_IN/s.
- The 8-computer tree was again the slowest. It has the longest paths (4 switches), and reactive sets rules up switch by switch.



Review I latency

Review I findings in short.

1. Reactive's first packet is 5–8× slower, and the cost grows with the number of switches on the path.
2. Later packets are equal.
3. When every pair talks, proactive uses no more rules than reactive. Under churn, reactive's exact-match rules pile up to 4–83× more.

3. Testbed and method (common to all experiments)

Item	Value
Emulator / switch / controller	Mininet 2.3.0, Open vSwitch 3.7.1 (kernel datapath), POX 0.7.0 (`gar`), OpenFlow 1.0
Machine	Laptops with Windows 11 + WSL2 (Ubuntu, kernel 6.18), Python 3.14
Controllers	**Reactive:** learning switch, exact-match rules, idle 10 s / hard 30 s. In networks with loops it runs over POX `openflow.discovery` + `openflow.spanning_tree`. **Proactive:** one rule per host pair on the lowest-cost path, plus a table-miss drop rule. **Proactive ECMP:** host pairs hashed (CRC32 of the MACs) across equal-cost paths. **Budgeted hybrid** (Section 6): reactive on shortest paths, plus pre-installed rules for the busiest host pairs within a budget.
Same conditions	Static ARP, IPv6 off, fixed random seed. **Every controller gets exactly the same pairs, traffic permutations and flow schedules.**
Measured, not modelled	Paths are read from the switches' flow tables (`ovs-ofctl dump-flows`); latency with ping / TCP flow completion times; controller load from counters inside our controllers; link loads from interface byte counters
Realism	Every network, traffic pattern and parameter is traced to a paper in `docs/Realism_Sources.md` (18 references)

4. Experiment A: optimal path vs haphazard path

Why. A tree has one path between two hosts, so all controllers used the same path in Review I. Real networks have many paths.

Networks.

- **fat-tree, k = 4** (data centre; Al-Fares, SIGCOMM 2008): 20 switches, 16 hosts, up to 4 equal paths between pods.
- **Abilene** (real US research backbone; Internet Topology Zoo): 11 cities, 14 links. Each link delay is the city distance ÷ 200 km/ms (light in fibre), emulated with netem.
- **Link speed:** 10 Mbit/s on every link, so only the path choice matters.

Controllers.

- Reactive = learning switch over a spanning tree. Floods follow the tree, so paths are whatever the tree gives: **haphazard**.
- Proactive = lowest-delay path: **optimal**.
- Proactive ECMP = optimal paths, spread over the equal-cost ones.

Traffic.

- **A (paths):** 40 host pairs, 6 pings each. The real path is traced switch by switch.


- **B (throughput):** every host sends one TCP flow to another at the same time (permutation traffic, as in Al-Fares 2008 / Hedera 2010), 3 permutations × 10 s.

Results (laptop, 15 Oct; `results/measured/paths-20261015-094800/`)


Network	Controller	Hop stretch mean / max	Delay stretch mean / max	Pairs on a longer path	Ping RTT (ms)
fat-tree	Reactive	**1.11 / 1.50**	-	**22%**	0.14
fat-tree	Proactive	1.00 / 1.00	-	0%	0.13
fat-tree	Proactive ECMP	1.00 / 1.00	-	0%	0.13
Abilene	Reactive	**1.40 / 3.00**	**1.58 / 4.47**	**70%**	**40.51**
Abilene	Proactive	1.02 / 1.33	1.00 / 1.00	0%	26.90
Abilene	Proactive ECMP	1.02 / 1.33	1.00 / 1.00	0%	26.24

Network	Controller	Total throughput, Mbit/s (ideal)	Jain index over links	Links unused
fat-tree	Reactive	63.6 ± 10.7 (160)	0.36	59%
fat-tree	Proactive	61.7 ± 9.8 (160)	0.33	63%
fat-tree	Proactive ECMP	**95.3 ± 3.3** (160)	**0.58**	**16%**
Abilene	Reactive	42.1 ± 2.6 (110)	0.56	29%
Abilene	Proactive	**60.7 ± 17.4** (110)	0.52	20%
Abilene	Proactive ECMP	**60.6 ± 16.3** (110)	0.52	20%


The busiest link was at 100% in every run, so the links (not the laptop) were the bottleneck. 0 packets were lost.



Path stretch



Throughput



Link balance

Findings

1. **ISP: reactive takes slow paths.**
    - 70% of pairs are on a slower path than necessary: +58% delay on average, up to 4.5× in the worst case.
    - Real pings are **40.5 ms against 26.9 ms**, and they match the map's prediction (39.3 vs 25.7 ms), which confirms the path tracing.
    - The cause is the spanning tree, which switches off 4 of Abilene's 14 links. Example: Atlanta → Washington has a direct 4.4 ms link, but reactive goes through Houston, Kansas City, Indianapolis, Chicago and New York (~23 ms).
2. **Data centre: one shortest path is not enough.**
    - One fixed shortest path gives no more throughput than reactive (62 vs 64 Mbit/s): both push traffic through the same core switch and leave ~60% of links idle.
    - **ECMP spreads the load: +50% throughput (95 Mbit/s), only 16% of links idle**, and the steadiest results.
3. **Nobody reaches the ideal.** ECMP on host pairs sometimes hashes two flows onto one link: the known ECMP collision problem (Al-Fares 2008, Hedera 2010).
4. **Reproducible.** A separate cloud-VM run produced exactly the same paths.

---

5. Experiment B: realistic traffic (university, data centre, ISP)

Why. Real traffic is mostly tiny flows, plus a few huge ones, arriving all the time. With reactive, every new flow costs a trip to the controller.

Scenarios. Each network carries the traffic measured in that kind of network:

Scenario	Network	Flow sizes	Flow arrivals	Source
University	campus tree, 16 hosts	87% < 10 KB, largest 10% carry 96% of bytes	Weibull gaps, 80% between 4 and 40 ms per edge switch (~200 flows/s)	Benson et al., IMC 2010 (Fig. 4a, Sec. 5, Table 4)
Data centre, web search	fat-tree k = 4	published table, mean 1.67 MB	Poisson, 30% load (~39 flows/s)	DCTCP (SIGCOMM 2010), as pFabric / PIAS `CDF_dctcp.tcl`
Data centre, data mining	fat-tree k = 4	published table: 80% < 10 KB, but 95% of bytes in flows > 35 MB	Poisson, 30% load (~57 flows/s)	VL2 (SIGCOMM 2009), as pFabric / PIAS `CDF_vl2.tcl`
ISP	Abilene: real link speeds (Atlanta–Indianapolis at ¼), city delays (netem)	SURGE web sizes: median 12 KB, mean 65 KB	**Real Abilene traffic matrices** for Mon 1 Mar 2004, 24 hours replayed in 30 s, scaled so each link is as busy as in 2004 (~57 flows/s)	Zhang et al., IMC 2005; SURGE (Barford & Crovella 1998)


Measurement setup.

- **What a flow is:** a TCP connection that sends N bytes and waits for a 1-byte reply. Flow completion time (FCT) runs from connect to reply.
- **Links:** 100 Mbit/s. Flows over 20 MB are capped to 20 MB, which affects 0–4% of flows.
- **Same flows for everyone:** the flow schedule is computed in advance, so every controller gets exactly the same flows.


Results (laptop, 15 Oct; `results/measured/traffic-20261015-113417/` and `traffic-20261015-122618/`)

Scenario	Controller	Small flows < 100 KB, FCT median / p99 (ms)	Large flows > 10 MB, mean FCT (s)	PACKET_IN/s	Controller CPU	Peak rules: all switches / one switch
University	Reactive	**55.7** / 126.0	-	**2,379**	**86.4%**	**10,928 / 3,377**
University	Proactive	**1.3** / 37.9	-	0	0.1%	624 / 192
DC web search	Reactive	155.3 / 343.5	12.2	514	44.3%	4,623 / 779
DC web search	Proactive	62.6 / 242.0	12.8	0	0.3%	1,072 / 192
DC web search	Proactive ECMP	**19.2** / 170.8	**3.5**	0	0.3%	1,072 / **58**
DC data mining	Reactive	113.0 / 244.2	10.9	738	56.3%	6,083 / 1,003
DC data mining	Proactive	24.9 / 111.0	10.7	0	0.3%	1,072 / 192
DC data mining	Proactive ECMP	**11.5** / 67.7	**3.6**	0	0.3%	1,072 / **58**
ISP (Abilene)	Reactive	**120.0** / 405.7	-	624	44.0%	7,176 / 1,051
ISP (Abilene)	Proactive	**48.1** / 198.4	-	0	0.2%	386 / 62


Flows completed: 6,102 university, 1,159 web search, 1,707 data mining and 1,761 ISP, for every controller, with **0 failures**.



Small-flow FCT, data-centre and university



Controller load and rules



Small-flow FCT, ISP

Findings

1. **University traffic: small flows are 44× slower with reactive** (median 55.7 vs 1.3 ms). The network is only 6% loaded, so this is purely the cost of asking the controller about every new flow.
2. **The controller nears saturation, and a busy controller causes even more work.**
   - **Load:** 203 new flows/s caused 2,379 PACKET_INs/s at 86% CPU (POX is single-threaded).
   - **More requests than needed:** each flow caused ~12 PACKET_INs, although it needs at most ~6. While the controller is slow, more packets of the same flow reach the switch before its rule does, and each one asks again.
   - **Lighter load, fewer requests:** a 10-s run at a similar rate had a less-loaded controller (54% CPU) and only 7.4 requests per flow. Requests per flow grow with controller load: a feedback loop towards overload.

3. **Reactive fills the switches:** 17× more rules on the campus tree (10,928 vs 624), and up to 3,377 in one switch. For scale, the HP 5406zl hardware switch studied in DevoFlow holds 16K exact-match rules, and our network has only 16 hosts.
4. **Data centre: the path matters as much as the controller.**
    - Small flows are **8–10× faster with proactive ECMP than with reactive** (web search 19 vs 155 ms; data mining 11.5 vs 113 ms).
    - Large flows depend on load balance, not on the controller: ~11–13 s with reactive or one shortest path, **3.5 s with ECMP**.
5. **ISP: reactive pays twice.**
    - Small flows are 2.5× slower (120 vs 48 ms).
    - Both reactive's longer paths and waiting for the controller add time. Our first estimate from the ping round trips of Experiment A was ~27 ms for the paths and ~40 ms for the controller.
    - **Section 6 measures the split directly** by running reactive on shortest paths: **44 ms from the paths, 26 ms from the controller**. The estimate had the two the wrong way round, so we use the measured split from now on.

---

6. Experiment C: how much does a rule budget buy? (Step 4)

Why. Sections 4 and 5 compare the two extremes: no rules in advance (reactive) and every rule in advance (proactive). Published work proposes things in between:

- keeping rules longer (SmartTime, AH-IHTA);
- caching only the popular rules (CacheFlow);
- hybrids that pre-install some flows (PARD);
- predictors that guess which flows will come (Batista 2024, mostly on IoT traffic).

We ran the simplest version of each idea on our testbed, with the same traffic as Section 5. All details are in `docs/Budgeted_Hybrid_Experiment.md`.

Controllers added.

Mode	What it does	What it tests
Reactive, long timeouts	Reactive, idle 60 s / hard 300 s instead of 10 s / 30 s	"Keep rules longer" (SmartTime, AH-IHTA)
Reactive on shortest paths	Our new `hybrid_eval` with budget 0: reactive, but it knows the map, so it uses shortest paths instead of the spanning tree	Separates the **setup cost** from the **path cost**
Hybrid, counter, 10 / 25 / 50%	Reactive on shortest paths, **plus** pair rules (source MAC + destination MAC) for the busiest host pairs, at most 10 / 25 / 50% of all pairs	A budget of popular rules (CacheFlow, PARD)
Oracle, 10 / 25 / 50%	Pre-installs the pairs that **really** carry the most flows in the run (read from the flow schedule), before the first flow	The best that **any** predictor (counter, ML, anything) can do with that budget

The counter. Every second, for each host pair: `score = 0.97 × score + (1 if the pair was used this second, else 0)`.


- **How "used" is seen:** pre-installed pairs no longer reach the controller, so their use is read from the switch's packet counters.
- **What is kept:** the top-K scores keep pair rules.
- **Hysteresis:** a newcomer must score 1.5× the weakest kept pair to replace it, so pairs near the cut-off do not swap every second.

Hit rate = the share of new TCP connections whose first packet found a rule (no trip to the controller).

Traffic. Each scenario uses Section 5's traffic:

- **university, fat-tree:** host pairs get Zipf popularity (exponent 1), as CacheFlow assumes ("traffic tends to follow a Zipf distribution");
- **Abilene:** the real traffic matrices give the popularity;
- **a control run** uses uniform pairs.


Results (laptop, 15 Oct; one run each; `results/measured/traffic-20261015-204208/`, `-210056/`, `-211130/`, `-213728/`, `-215331/`)



Hit rate against rule budget, four scenarios

Scenario	Controller	Hit rate	Small flows: median FCT (ms)	PACKET_IN/s	Controller CPU	Peak rules
University tree	Reactive	-	53.4	2,371	83.6%	11,170
	Reactive, long timeouts	-	59.1	2,327	83.6%	**32,644**
	Reactive, shortest paths	0%	53.7	2,329	82.7%	11,159
	Hybrid counter, 25%	62.3%	12.8	861	48.2%	5,010
	Hybrid counter, 50%	80.5%	4.1	365	28.3%	2,340
	Oracle, 25% / 50%	70.6 / 85.7%	7.4 / 3.0	572 / 274	39.7 / 22.0%	3,287 / 1,987
	Proactive	100%	1.7	0	0.1%	624
Fat-tree, web search	Reactive	-	142.7	509	44.2%	4,398
	Reactive, long timeouts	-	141.5	468	41.2%	**10,912**
	Reactive, shortest paths	0%	103.9	514	42.4%	3,843
	Hybrid counter, 25%	67.6%	55.4	180	21.4%	1,525
	Hybrid counter, 50%	78.5%	46.6	127	17.2%	1,624
	Oracle, 25% / 50%	74.7 / 88.8%	50.3 / 37.4	132 / 60	15.5 / 7.7%	1,214 / 972
	Proactive ECMP	100%	26.3	0	0.4%	1,072
Abilene ISP	Reactive	-	117.5	619	44.3%	7,167
	Reactive, long timeouts	-	116.6	603	43.4%	**16,440**
	Reactive, shortest paths	0%	73.4	484	37.1%	5,331
	Hybrid counter, 25%	52.2%	62.7	207	20.8%	2,628
	Hybrid counter, 50%	78.1%	52.3	84	10.1%	1,147
	Oracle, 25% / 50%	59.1 / 83.2%	60.5 / 50.1	172 / 64	16.1 / 6.4%	2,386 / 1,115
	Proactive	100%	47.8	0	0.2%	386

All runs: 6,088 university, 1,156 web search and 1,761 ISP flows, **0 failures**. The 10% budgets are in the figure and in the detailed document.



Where reactive's extra time goes

Two extra runs.

- **Control, uniform pairs** (university): the counter's hit rate is 9.7 / 24.5 / 47.7% at 10 / 25 / 50%, about the budget share itself. With no popular pairs there is nothing to learn.
- **Warm-up, 120 s instead of 30 s** (university, 10%): the counter's hit rate rises from 24.5% to **38.1%**; the oracle stays at 51.5%. Half of the counter's gap at 10% was learning time; the other half is how it ranks pairs (below).

Findings

1. **Long timeouts never help.**
    - In all 4 scenarios: the same delay and the same controller load, with 2.3–2.9× the rules.
    - Why: reactive rules are exact matches, and every new TCP connection has a new source port. A rule kept longer is never matched again.
    - So "keep rules longer" does not help short-flow traffic unless the rules are coarser.
2. **Part of reactive's cost is the spanning tree, not the controller.** Running reactive on shortest paths separates the two (figure above):
    - **University tree:** all 52 ms of the gap is setup. A tree has one path, so the spanning tree costs nothing.
    - **Fat-tree:** 39 ms is the spanning tree's path, 78 ms is setup plus ECMP's better load balance.
    - **Abilene: 44 ms is path and only 26 ms is setup.** Section 5's "reactive vs proactive" gap mixed two effects; the larger one in the ISP is the path.
3. **A small budget removes most of the setup cost when traffic is skewed.** With 25% of pairs pre-installed, compared with reactive on shortest paths:
    - 52–68% of new connections skip the controller;

- 2.3–2.9× fewer PACKET_INs;
- 2.0–2.5× **fewer** rules, because one pair rule replaces the many per-connection rules.

On the university tree, the small-flow median drops 4.2× (53.7 → 12.8 ms) and controller CPU drops from 83% to 48%.

4. **The value of the budget comes from skew.**
   - **Uniform pairs:** a budget of B% buys about B% hit rate, the same as picking pairs at random.
   - **Zipf pairs, or real Abilene traffic:** 25% of pairs buys 52–68%.
   - **Real ISP traffic is skewed on its own:** the busiest 10% of city pairs carry a third of the flows. That is measured, not assumed.
5. **The simple counter is close to a perfect predictor.**
   - At 25–50% budgets it reaches **0.88–0.94 of the oracle's hit rate** in every skewed scenario. So ML could add at most 5–10 points of hit rate there.
   - **Weak spot:** a small budget (10%) with many flows per pair (university): 0.47 of the oracle in 30 s, 0.74 in 120 s.
   - **The cause is our design:** the counter scores a pair 0 or 1 per second, so pairs with 1.4 and 0.8 flows/s look alike. Counting flows instead is the obvious fix.
6. **On our small networks, proactive is still the best choice.** It is the fastest, has no controller load, and uses the fewest rules (or nearly). A rule budget only matters when all pairs do not fit in the switches, which happens in large networks, not in 11–16-host ones. **We do not claim the hybrid beats proactive here.**

7. Comparison with previous work

7.1 Our measurements next to published numbers

What	Published	Ours
Reactive first-packet delay	10 ms (NOX, in DIFANE); < 1.5 ms worst case (Ethane)	3.8–6.6 ms (laptop 1), 7.2–11.4 ms (laptop 2)
Proactive / data-plane first packet	0.4 ms (DIFANE)	0.67–1.5 ms (includes Open vSwitch's cache fill)
Controller capacity	NOX ≈ 30k flows/s, NOX-MT 1.6M/s (Tootoonchian 2012)	POX: 2,379 PACKET_IN/s at 86% CPU, near its limit
Flow sizes in campus / enterprise data centres	80% of flows < 10 KB (Benson 2010)	Our generator: 87% < 10 KB (uses Benson's curve)
ECMP leaves throughput on the table	Hash collisions limit ECMP (Al-Fares 2008, Hedera 2010)	ECMP reached 95 of 160 Mbit/s (60%), with the busiest links at 100%
Small rule budget serves most traffic	90% hits with < 5% of rules (CacheFlow 2016)	Same direction, smaller effect: 52–68% hits with 25% of host pairs, 24–52% with 10% (Section 6). Our networks have only 110–240 pairs, and our hit rate counts connections, not packets
Timeouts cut controller load	−58% cost (SmartTime 2014); −28% setups (AH-IHTA 2020)	**Not for short-flow traffic with exact-match rules:** 60 s / 300 s timeouts gave no fewer controller requests and 2.3–2.9× more rules (Section 6)
ML predictors beat reactive	LSTM pre-install: −51% response time vs reactive (Batista 2024, IoT)	Beating reactive is easy: a plain counter cut controller requests 2.3–2.9×. The useful bound is the oracle: at 25–50% budgets the counter is within 6–12% of it, so ML could add at most 5–10 points of hit rate

Numbers from different papers are not directly comparable (different hardware, controllers and years). **The ranges and trends agree.**

7.2 Realism: the paper behind every choice

`docs/Realism_Sources.md` lists the source of every network, traffic pattern and parameter: 18 references, each marked "checked in PDF", "checked online", "data file" or "to check".

- **Networks:** Al-Fares 2008 (fat-tree); Topology Zoo and the Abilene dataset's own topology file (Abilene).
- **Traffic:** Benson 2010 (university); DCTCP / VL2 through the exact pFabric/PIAS tables (data centre); the real Abilene traffic matrices of Zhang et al. 2005 (ISP).

7.3 Previous methods run on our testbed

Published idea	Our version	Status
Longer timeouts (SmartTime, AH-IHTA)	Reactive with idle 60 s / hard 300 s	**Done** (Section 6). Adaptive timeouts are not implemented; fixed long ones already show the limit.
Cache of popular rules within a budget (CacheFlow); hybrid installation (PARD)	Budgeted hybrid with a weighted counter, 10 / 25 / 50% of pairs	**Done** (Section 6)
A predictor that knows which flows will come (Batista's LSTM, any ML)	The **oracle**: the best possible choice for a budget, used as the upper bound	**Done** (Section 6). A real ML model is optional (Section 9): the oracle already shows how little it could add at 25–50% budgets.

The full list of comparisons, each next to the closest paper and what that paper does not measure, is in `docs/Evaluation_Plan.md`.

---

8. What we learned so far

Situation	What decides performance	Winner
Many small flows, light load (university)	The cost of setting up each new flow	**Proactive**: 44× faster small flows; the controller idles
Heavy load (data centre)	Path choice and load balance	**Proactive ECMP**: 8–10× faster small flows, 3× faster large flows
Wide-area network (ISP)	Both: longer paths **and** controller set-up	**Proactive**: 2.5× faster small flows
Every pair active, no churn (Review I)	Nothing: same number of rules	Tie
Skewed traffic, limited rule space (Section 6)	Which pairs get the scarce rules	**Budgeted hybrid**: 25% of pairs removes 52–68% of controller trips with fewer rules than reactive; a simple counter is close to the best possible choice
Uniform traffic (Section 6, control)	Nothing to learn	A budget buys only its own share

Reactive loses on both counts. It pays a set-up cost for every new flow, and on networks with loops its paths are chosen by flooding, not by quality. Section 6 shows how much of each: on the ISP map the path costs more than the setup. Proactive's weak point is that it installs a rule for **every** pair, whether used or not; on larger networks this grows as N^2.

What changed in our plan since Review I. At Review I we planned an "idle-time hybrid": pre-install popular pairs only while the controller is quiet. Reading the literature

(`docs/literature/`) showed that each in-between idea has been tested only on its own traffic and setup, and never side by side. So our contribution is the **measured comparison** (`docs/Evaluation_Plan.md`), not a new algorithm:

- **Built:** the budgeted hybrid, which is the popularity part of the plan.
- **Not built:** the idle-time scheduling. The counter's work (one statistics request per pre-installed pair per second) is small next to the PACKET_INs it saves.

What we do not claim. The budgeted hybrid is close to CacheFlow and PARD, and it does not beat proactive on our small networks.

---

9. Plan to the final submission (20 Nov)

When	Work
By 2 Nov	**Repeats:** every Step 4 scenario 5× with different seeds, reported as mean ± 95% confidence interval (`--repeats 5`, already implemented; overnight runs)
By 5 Nov	**Two PCs (feedback point "multiple computers"):** POX on one laptop, Mininet on another; same runs, to measure real control-channel delay and a controller with its own CPU (tool ready: `docs/Controller_On_Second_PC.md`)
5–12 Nov	**The counter's weak spot:** a counter that counts flows instead of busy seconds, and a shorter memory (decay 0.9), at the 10% budget. **Optional:** an ML predictor (e.g. logistic regression) against the counter and the oracle at the same budget
5–12 Nov	**A larger network** (fat-tree k = 6: 54 hosts, 2,862 pairs, if the laptop can run it), where proactive's N^2 rules start to matter
12–20 Nov	Read the remaining full texts (PARD, the ML papers), check SURGE's parameters; final runs, final report and demo

Risks.

- **POX near saturation:** POX is single-threaded and was at 86% CPU under university traffic, which also tells us where reactive breaks.
- **WSL2 timing noise:** repeats and a second laptop are used to control it. The counter is the noisiest result: its 10% hit rate was 24.5% on the laptop and 35.7% on a cloud test with the same traffic.
- **Small networks:** with 11–16 hosts proactive's rules always fit, so the rule budget is never forced. A larger network is planned; it may not fit on a laptop.
- **One unverified parameter:** SURGE's numbers (ISP flow sizes) are still to be checked against the paper. The ISP traffic *volumes* are real data.
- **Second PC:** depends on borrowing a laptop and on WSL2 mirrored networking (Windows 11).

10. How to reproduce

```
git clone https://github.com/PrachitDeshinge-324/Openflow_SDN.git && cd Openflow_SDN
bash setup.sh                                                  # first time only (see INSTALL
sudo python3 experiments/run_experiments.py                    # Review I: latency, rules, ch
sudo python3 experiments/run_path_experiments.py               # Section 4: path quality (~15
sudo python3 experiments/run_traffic_experiments.py            # Section 5: realistic traffic
sudo python3 experiments/run_traffic_experiments.py --scenarios tree-d2-f4:university --budge
sudo python3 experiments/run_traffic_experiments.py --scenarios fattree-k4:websearch --budget
sudo python3 experiments/run_traffic_experiments.py --scenarios abilene:isp --budget-sweep
python3 docs/figures/make_step4_figures.py                     # Section 6 summary figures
sudo python3 demo/run_demo.py                                  # live demo (reactive vs proac
```

Detailed documents:

- `docs/Path_Quality_Experiment.md`
- `docs/Realistic_Traffic_Experiment.md`
- `docs/Budgeted_Hybrid_Experiment.md` (Step 4)
- `docs/Controller_On_Second_PC.md`
- `docs/Evaluation_Plan.md`: every comparison next to the closest paper
- `docs/Realism_Sources.md`
- `docs/literature/Literature_Review_IdleHybrid.md` and `docs/literature/ML_Rule_Prediction_Survey.md`
- `docs/Progress_Review_1.md`

Raw data: every run's raw data (each flow, each path, POX logs) is in `results/measured/`.