

FHS

Fixomech Center Hollow Plain Ram Spring Return – Single Acting

APPLICATION

These jacks are designed to provide oil force in both the advance and retraction of ram, in vertical & horizontal position, where cycle time is crucial. These are mainly used for hydraulic testing machine and for lifting, lowering, spreading of structures, bridges, heavy machinery, etc.

ADVANTAGES / FEATURES

- Removal & Assembly of pins, bushes, bearings, Sprockets, Gears & General Maintenance.
- Speed Nuts, Speed Nut Handles, Threaded Saddle, Plain Saddle Centre Screw, Etc.
- Alloy steel body for better life.
- Hard chrome-plated ram to resist scoring & corrosion.
- Ideal for heavy duty application.
- Provides force in advance & return cycles.
- High-pressure long-life seals. Ram wiper protects inner cylinder from dirt which extends cylinder life.
- Fast & Complete ram retraction.
- Bottom mounting holes, collar threading is provided on request.
- Connection Port size 3/8-inch NPT.

FHS Series – F: Fixomech, H: Hollow Rod, S: Single Acting Spring Return

Model	Cap. in (ton)	Cap. in (kN)	Stroke in (mm)	"A" Close Height	Effective area in (cm ²)	Oil Cap in (cc)	"B" Cylinder OD	"C" Cyl Bore ID	"S" Hole dia.	"D" Ram dia.	"E" Saddle dia.	wt. Approx. in kg
FHS 10 - 100	10	110	100	215	15.7	157	75	60	21	50	50	6
FHS 20 - 100	20	231	100	220	33.0	330	105	85	28	75	73	13.5
FHS 30 - 100	30	298	100	245	42.6	426	115	95	34	80	78	16
FHS 50 - 100	50	550	100	255	78.5	785	150	125	42	100	97	27
FHS 60 - 100	60	605	100	270	86.4	864	165	135	54	110	107	35
FHS 100 - 100	100	990	100	295	141.4	1414	215	180	77	150	146	62

Model	Ram Internal Threading	Thread Depth	Collar Threads	Length	PCD x No. of Holes	Bottom Thread Size	Thread Depth
FHS - 10	M42X2P	22	M75X2P	30	60X2	M8	15
FHS - 20	M56X2P	23	M105X2P	36	85X2	M10	17
FHS - 30	M64X2P	30	M115X2P	40	90X2	M10	17
FHS - 50	M80X2P	30	M150X3P	40	125X2	M12	18
FHS - 60	M90X2P	33	M165X3P	45	135X2	M12	20
FHS - 100	M120X2P	40	M215X3P	50	180X2	M16	24