

# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_MCQ\_Updated

Attempt : 1  
Total Mark : 20  
Marks Obtained : 18

#### Section 1 : MCQ

1. What will be the output of the following program?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};
```

```
int main() {
    struct Node* head = NULL;
    struct Node* tail = NULL;
    for (int i = 0; i < 5; i++) {
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
```

```
temp->data = i + 1;
temp->prev = tail;
temp->next = NULL;
if (tail != NULL) {
    tail->next = temp;
} else {
    head = temp;
}
tail = temp;
}
struct Node* current = head;
while (current != NULL) {
    printf("%d ", current->data);
    current = current->next;
}
return 0;
}
```

**Answer**

1 2 3 4 5

**Status : Correct**

**Marks : 1/1**

2. What happens if we insert a node at the beginning of a doubly linked list?

**Answer**

The previous pointer of the new node is NULL

**Status : Correct**

**Marks : 1/1**

3. Which of the following information is stored in a doubly-linked list's nodes?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

4. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
newNode->data = value;  
newNode->next = NULL;  
newNode->prev = NULL;
```

**Answer**

Creates a new node and initializes its data to 'value'

**Status :** Correct

**Marks :** 1/1

5. Which pointer helps in traversing a doubly linked list in reverse order?

**Answer**

prev

**Status :** Correct

**Marks :** 1/1

6. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head\_ref: Pointer to Pointer of node)

temp = NULL

current = \*head\_ref

While current is not NULL

temp = current->prev

current->prev = current->next

current->next = temp

current = current->prev

End While

```
If temp is not NULL
    *head_ref = temp->prev
End If
End Procedure
```

**Answer**

6 &lt;--&gt; 5 &lt;--&gt; 4 &lt;--&gt; 3 &lt;--&gt; 2 &lt;--&gt; 1.

**Status :** Correct

**Marks :** 1/1

7. Which of the following statements correctly creates a new node for a doubly linked list?

**Answer**

```
struct Node* newNode = (struct Node*) malloc(sizeof(struct Node));
```

**Status :** Correct

**Marks :** 1/1

8. How do you delete a node from the middle of a doubly linked list?

**Answer**

All of the mentioned options

**Status :** Correct

**Marks :** 1/1

9. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

```
Define Structure Node
    data: Integer
    prev: Pointer to Node
    next: Pointer to Node
End Define
```

```
Define Structure TwoWayLinkedList
    head: Pointer to Node
    tail: Pointer to Node
End Define
```

**Answer**

```
struct TwoWayLinkedList* list = malloc(sizeof(struct TwoWayLinkedList)); list->head = NULL; list->tail = NULL;
```

**Status :** Correct

**Marks :** 1/1

10. How many pointers does a node in a doubly linked list have?

**Answer**

2

**Status :** Correct

**Marks :** 1/1

11. Which code snippet correctly deletes a node with a given value from a doubly linked list?

```
void deleteNode(Node** head_ref, Node* del_node) {  
    if (*head_ref == NULL || del_node == NULL) {  
        return;  
    }  
    if (*head_ref == del_node) {  
        *head_ref = del_node->next;  
    }  
    if (del_node->next != NULL) {  
        del_node->next->prev = del_node->prev;  
    }  
    if (del_node->prev != NULL) {  
        del_node->prev->next = del_node->next;  
    }  
    free(del_node);  
}
```

**Answer**

Deletes the node at a given position in a doubly linked list.

**Status :** Wrong

**Marks :** 0/1

12. What will be the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};
```

```
int main() {
    struct Node* head = NULL;
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
    temp->data = 2;
    temp->next = NULL;
    temp->prev = NULL;
    head = temp;
    printf("%d\n", head->data);
    free(temp);
    return 0;
}
```

**Answer**

2

**Status :** Correct

**Marks :** 1/1

13. What is the correct way to add a node at the beginning of a doubly linked list?

**Answer**

```
void addFirst(int data){ Node* newNode = new Node(data);  newNode->
    &gt;next = head;      if (head != NULL) {      head-&gt;prev =
    newNode;  }  head = newNode;      }
```

**Status :** Correct

**Marks :** 1/1

14. What is a memory-efficient double-linked list?

**Answer**

Each node has only one pointer to traverse the list back and forth

**Status : Wrong**

**Marks : 0/1**

15. What is the main advantage of a two-way linked list over a one-way linked list?

**Answer**

Two-way linked lists allow for traversal in both directions.

**Status : Correct**

**Marks : 1/1**

16. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;  
    struct Node *Fwd;  
    struct Node *Bwd;  
};
```

**Answer**

X->Bwd->Fwd = X->Fwd; X->Fwd->Bwd = X->Bwd;

**Status : Correct**

**Marks : 1/1**

17. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

**Answer**

The node will become the new head

**Status : Correct**

**Marks : 1/1**

18. How do you reverse a doubly linked list?

**Answer**

By swapping the next and previous pointers of each node

**Status : Correct**

**Marks : 1/1**

19. Which of the following is true about the last node in a doubly linked list?

**Answer**

Its next pointer is NULL

**Status : Correct**

**Marks : 1/1**

20. Which of the following is false about a doubly linked list?

**Answer**

Implementing a doubly linked list is easier than singly linked list

**Status : Correct**

**Marks : 1/1**



# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Your task is to create a program to manage a playlist of items. Each item is represented as a character, and you need to implement the following operations on the playlist.

Here are the main functionalities of the program:

Insert Item: The program should allow users to add items to the front and end of the playlist. Items are represented as characters. Display Playlist: The program should display the playlist containing the items that were added.

To implement this program, a doubly linked list data structure should be used, where each node contains an item character.

**Input Format**

The input consists of a sequence of space-separated characters, representing the items to be inserted into the doubly linked list.

The input is terminated by entering - (hyphen).

### **Output Format**

The first line of output prints "Forward Playlist: " followed by the linked list after inserting the items at the end.

The second line prints "Backward Playlist: " followed by the linked list after inserting the items at the front.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: a b c -

Output: Forward Playlist: a b c

Backward Playlist: c b a

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    char item;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
void insertAtEnd(struct Node** head, char item) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->item = item;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
    if(*head == NULL)  
    {  
        *head = newNode;  
        return;  
    }  
}
```

```

    struct Node* temp = *head;
    while(temp -> next != NULL)
    {
        temp = temp -> next;
    }
    temp -> next = newNode;
    newNode -> prev = temp;
}

void displayForward(struct Node* head) {
    struct Node* temp = head;
    while(temp != NULL)
    {
        printf("%c ",temp -> item);
        temp = temp -> next;
    }
    printf("\n");
}

void displayBackward(struct Node* tail) {
    struct Node* temp = tail;
    while(temp != NULL)
    {
        printf("%c ",temp -> item);
        temp = temp -> prev;
    }
    printf("\n");
}

void freePlaylist(struct Node* head) {
    struct Node* temp = head;
    while(temp != NULL)
    {
        struct Node* nextNode = temp -> next;
        free(temp);
        temp = nextNode;
    }
    head = NULL;
}

int main() {
    struct Node* playlist = NULL;
    char item;

```

```
while (1) {
    scanf(" %c", &item);
    if (item == '-') {
        break;
    }
    insertAtEnd(&playlist, item);
}

struct Node* tail = playlist;
while (tail->next != NULL) {
    tail = tail->next;
}

printf("Forward Playlist: ");
displayForward(playlist);

printf("Backward Playlist: ");
displayBackward(tail);

freePlaylist(playlist);

return 0;
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

##### ***Input Format***

The first line consists of an integer  $n$ , representing the number of participant IDs to be added.

The second line consists of  $n$  space-separated integers representing the participant IDs.

### **Output Format**

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!"

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

163 137 155

Output: 163

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
typedef struct Node
{
    int data;
    struct Node* next;
    struct Node* prev;
}Node;
void insertAtend(Node** head,int e)
{
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode -> data = e;
    newNode -> next = NULL;
    newNode -> prev = NULL;
    if(*head == NULL)
    {
        *head = newNode;
        return;
    }
    Node* temp = *head;
    while(temp -> next != NULL)
    {
        temp = temp -> next;
    }
    temp -> next = newNode;
```

```

        newNode -> prev = temp;
    }
    void find_big(Node* head)
    {
        if(head == NULL)
        {
            printf("Empty list!");
            return;
        }
        int max = head -> data;
        Node* temp = head;
        while(temp != NULL)
        {
            if(temp -> data > max)
            {
                max = temp -> data;
            }
            temp = temp -> next;
        }
        printf("%d",max);
    }
    int main()
    {
        Node* head = NULL;
        int n,e;
        scanf("%d",&n);
        for(int i =0 ;i< n;i++)
        {
            scanf("%d",&e);
            insertAtend(&head,e);
        }
        find_big(head);
    }

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bob is tasked with developing a company's employee record management system. The system needs to maintain a list of employee records using a doubly linked list. Each employee is represented by a unique integer ID.

Help Bob to complete a program that adds employee records at the front, traverses the list, and prints the same for each addition of employees to the list.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of employees.

The second line consists of N space-separated integers, representing the employee IDs.



### **Output Format**

For each employee ID, the program prints "Node Inserted" followed by the current state of the doubly linked list in the next line, with the data values of each node separated by spaces.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4  
101 102 103 104  
Output: Node Inserted  
101  
Node Inserted  
102 101  
Node Inserted  
103 102 101  
Node Inserted  
104 103 102 101

### **Answer**

```
#include <iostream>
using namespace std;

struct node {
    int info;
    struct node* prev, * next;
};

struct node* start = NULL;
struct node* head = NULL;
void traverse() {
    struct node* temp = head;
    while(temp != NULL)
    {
        printf("%d ",temp -> info);
        temp = temp -> next;
    }
    printf("\n");
}
```

```

}
void insertAtFront(int data) {
    struct node* newNode = (struct node*)malloc(sizeof(struct node));
    newNode -> info = data;
    newNode -> next = NULL;
    newNode -> prev = NULL;
    if(head == NULL)
    {
        head = newNode;
        printf("Node Inserted\n");
        return;
    }
    newNode -> next = head;
    head -> prev = newNode;
    printf("Node Inserted\n");
    head = newNode;
}

int main() {
    int n, data;
    cin >> n;
    for (int i = 0; i < n; ++i) {
        cin >> data;
        insertAtFront(data);
        traverse();
    }
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

##### ***Input Format***

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

### **Output Format**

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
typedef struct node
{
    int data;
    struct node* next;
    struct node* prev;
}Node;
void insertAtend(Node** head,int data)
{
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->data = data;
    newNode->next = NULL;
    newNode->prev = NULL;
    if(*head == NULL)
    {
        *head = newNode;
        return;
    }
    Node* temp = *head;
    while(temp->next != NULL)
    {
        temp = temp->next;
    }
```

```
temp -> next = newNode;
newNode -> prev = temp;
}
void Traverse(Node* head)
{
    Node* temp = head;
    while(temp != NULL)
    {
        printf("%d ",temp -> data);
        temp = temp -> next;
    }
}
int main()
{
    int n,e;
    Node* head = NULL;
    scanf("%d",&n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&e);
        insertAtend(&head,e);
    }
    Traverse(head);
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: pradeepa .p  
Email: 240801243@rajalakshmi.edu.in  
Roll no: 2116240801243  
Phone: 8270260637  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 5

Attempt : 2  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

### ***Input Format***

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

### ***Output Format***

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 4

1 2 3 4

5

Output: Data entered in the list:

node 1 : 1

node 2 : 2

node 3 : 3

node 4 : 4

Invalid position. Try again.

### ***Answer***

```
void DListcreation(int n) {  
    int i, num;  
    struct node *fnNode;
```

```

if (n >= 1) {
    stnode = (struct node *)malloc(sizeof(struct node));
    scanf("%d", &num);
    stnode->num = num;
    stnode->preptr = NULL;
    stnode->nextptr = NULL;
    ennode = stnode;

    for (i = 2; i <= n; i++) {
        fnNode = (struct node *)malloc(sizeof(struct node));
        scanf("%d", &num);
        fnNode->num = num;
        fnNode->preptr = ennode;
        fnNode->nextptr = NULL;
        ennode->nextptr = fnNode;
        ennode = fnNode;
    }
}
}

```

```

void DListDeleteFirstNode() {
    struct node *toDel;
    if (stnode == NULL) {
        return;
    }
    toDel = stnode;
    stnode = stnode->nextptr;
    if (stnode != NULL)
        stnode->preptr = NULL;
    free(toDel);
}

```

```

void DListDeleteLastNode() {
    struct node *toDel;
    if (ennode == NULL) {
        return;
    }
    toDel = ennode;
    ennode = ennode->preptr;
    if (ennode != NULL)
        ennode->nextptr = NULL;
}

```



```
    else  
        stnode = NULL;  
    free(toDel);  
}
```

```
void DListDeleteAnyNode(int pos) {  
    struct node *curNode;  
    int i;  
    if (pos == 1) {  
        DListDeleteFirstNode();  
        return;  
    }  
  
    curNode = stnode;  
    for (i = 1; i < pos && curNode != NULL; i++) {  
        curNode = curNode->nextptr;  
    }  
  
    if (curNode == NULL || curNode == stnode) {  
        printf("Invalid position. Try again.");  
        return;  
    }  
  
    if (curNode->nextptr == NULL) {  
        DListDeleteLastNode();  
        return;  
    }  
  
    curNode->preptr->nextptr = curNode->nextptr;  
    curNode->nextptr->preptr = curNode->preptr;  
  
    free(curNode);  
}
```

```
void displayDList(int a) {  
    struct node *tmp;  
    int n = 1;  
  
    if (stnode == NULL) {  
        printf("List is empty.\n");  
        return;  
    }  
}
```

```
if (a == 1)
    printf("Data entered in the list:\n");
else
    printf("\nAfter deletion the new list:\n");

tmp = stnode;
while (tmp != NULL) {
    printf(" node %d : %d\n", n, tmp->num);
    n++;
    tmp = tmp->nextptr;
}
}
```

**Status :** Correct

**Marks :** 10/10