

## Q. Assertion – 1

```
import java.util.Scanner;
public class Assertion1 {
    public static void main(String[] args)
    {
        Scanner scanner = new Scanner(System.in);
        System.out.print("Enter your age : ");
        int value = scanner.nextInt();
        assert value >= 18 : "Eligible : ";
        System.out.println("Your entered age is " + value);
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Assertion1.java

Enter your age : 21

Your entered age is 21

## Q. Assertion – 2

```
public class Assertion2 {  
    public static void main(String args[]) throws java.io.IOException  
    {  
        int value=10;  
  
        assert value>=20 : "Eligible";  
        System.out.println("Value : " + value);  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Assertion2.java

Value : 10

### Q. Example of Scanner

```
import java.util.Scanner;
public class Scan {
    public static void main(String args[]) throws java.io.IOException {
        Scanner scanner = new Scanner(System.in);
        System.out.print("Enter Your Name : ");
        String name = scanner.nextLine();
        System.out.print("Enter Your age : ");
        int age = scanner.nextInt();
        System.out.print("Enter Your salary : ");
        double salary = scanner.nextDouble();
        System.out.println("Name is:" + name);
        System.out.println("Age is:" + age);
        System.out.println("Salary is:" + salary);
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Scan.java

Enter Your Name : Pradip

Enter Your age : 21

Enter Your salary : 25000

Name is:Pradip

Age is:21

Salary is:25000.0

## Q. System Properties

```
import java.util.*;
public class GetProperties{
    public static void main(String[] args)
    {
        Properties properties = System.getProperties();
        properties.list(System.out);
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\GetProperties.java

-- listing properties --

java.specification.version=13

sun.cpu.isalist=amd64

sun.jnu.encoding=Cp1252

java.class.path=.

java.vm.vendor=Oracle Corporation

sun.arch.data.model=64

user.variant=

java.vendor.url=https://java.oracle.com/

java.vm.specification.version=13

os.name=Windows 10

sun.java.launcher=SUN\_STANDARD

user.country=IN

sun.boot.library.path=C:\Program Files\Java\jdk-13.0.1\bin

sun.java.command=jdk.compiler/com.sun.tools.javac.laun...

jdk.debug=release

sun.cpu.endian=little

user.home=C:\Users\Xtrem

user.language=en

sun.stderr.encoding=cp850

java.specification.vendor=Oracle Corporation

java.version.date=2019-10-15

java.home=C:\Program Files\Java\jdk-13.0.1

file.separator=\

java.vm.compressedOopsMode=32-bit

line.separator=

sun.stdout.encoding=cp850

java.vm.specification.vendor=Oracle Corporation

java.specification.name=Java Platform API Specification

jdk.module.main.class=com.sun.tools.javac.launcher.Main

user.script=

sun.management.compiler=HotSpot 64-Bit Tiered Compilers

java.runtime.version=13.0.1+9

user.name=Xtrem

jdk.launcher.sourcefile=D:\MCA\MCA SEM 3\JAVA\Practice\.\GetP...

path.separator=;

os.version=10.0

java.runtime.name=Java(TM) SE Runtime Environment

file.encoding=Cp1252

java.vm.name=Java HotSpot(TM) 64-Bit Server VM

java.vendor.url.bug=<https://bugreport.java.com/bugreport/>

java.io.tmpdir=C:\Users\Xtrem\AppData\Local\Temp\

java.version=13.0.1

user.dir=D:\MCA\MCA SEM 3\JAVA\Practice

os.arch=amd64

java.vm.specification.name=Java Virtual Machine Specification

sun.os.patch.level=

java.library.path=C:\Program Files\Java\jdk-13.0.1\bin;...

java.vm.info=mixed mode, sharing

java.vendor=Oracle Corporation

java.vm.version=13.0.1+9

sun.io.unicode.encoding=UnicodeLittle

java.class.version=57.0

## Q. 2D Array

```
public class TwoDeminsionArray {  
    public static void main(String args[]){  
        int arr[][] = { {2,7,9},{3,6,1},{7,4,2} };  
        for(int i = 0; i < 3; i++)  
        {  
            for(int j = 0; j < 3; j++)  
            {  
                System.out.print(arr[i][j] + " ");  
            }  
            System.out.println();  
        }  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\TwoDeminsionArray.java

2 7 9

3 6 1

7 4 2

### Q. 3D Array

```
public class ThreeDeminsion {
    public static void main(String args[]){
        int arr[][][] = { { {2,7,9},{3,6,1},{7,4,2} }, { {3,6,1},{2,7,9},{7,4,2} }, { {2,7,9},{7,4,2},{3,6,1} } };
        for(int i = 0; i < 3; i++)
        {
            for(int j = 0; j < 3; j++)
            {
                for(int k = 0; k < 3; k++)
                {
                    System.out.print(arr[i][j][k] + " ");
                }
                System.out.println();
            }
            System.out.println();
        }
    }
}
```

**Output :**

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\ThreeDeminsion.java

2 7 9

3 6 1

7 4 2

3 6 1

2 7 9

7 4 2

2 7 9

7 4 2

3 6 1



### Q. Jagged Array

```
public class JaggedArray {  
    public static void main(String[] args){  
        int ja[][] = {{1,2,3},{1,2,3,4}};  
        for(int i = 0; i < 2; i++)  
        {  
            for(int j = 0; j < 3 + i; j++)  
            {  
                System.out.print(ja[i][j] + " ");  
            }  
            System.out.println("\n");  
        }  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\JaggedArray.java

1 2 3

1 2 3

## Q. Array 1 Example

```
import java.util.Arrays;
public class ArrayExample{
    public static void main(String[] args) {
        int arr[]=new int [5];

        for(int i=5;i>0;i--)
            arr[5-i] = i;

        Arrays.sort(arr);

        for(int i=0;i<5;++i)
            System.out.print(arr[i]);
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\ArrayExample.java

12345

## Q. String Collection

```
public class StringCollection {  
    public static void main(String[] args){  
        String Phrase = "The Quick Brown fox Jumped over the lazy dog";  
        int vowels = 0;  
        for(char ch : Phrase.toCharArray()){  
            ch = Character.toLowerCase(ch);  
            if(ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u')  
                ++vowels;  
        }  
        System.out.println("The Phrase contains " + vowels + " Vowels");  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\StringCollection.java

The Phrase contains 12 Vowels

## Q. Count Vowels

```
public class StringCollection {  
    public static void main(String[] args){  
        String Phrase = "The Quick Brown fox Jumped over the lazy dog";  
        int vowels = 0;  
        for(char ch : Phrase.toCharArray()){  
            ch = Character.toLowerCase(ch);  
            if(ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch == 'u')  
                ++vowels;  
        }  
        System.out.println("The Phrase contains " + vowels + " Vowels");  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\StringCollection.java

The Phrase contains 12 Vowels

## Q. Test String

```
public class TestString {  
    public static void main(String[] args){  
        String s1 = "Test";  
        String s2 = "Test";  
        String s3 = new String("Test");  
        final String s4 = s3.intern();  
        System.out.println(s1 == s2);  
        System.out.println(s2 == s3);  
        System.out.println(s3 == s4);  
        System.out.println(s1 == s3);  
        System.out.println(s1 == s4);  
  
        System.out.println(s1.equals(s2));  
        System.out.println(s2.equals(s3));  
        System.out.println(s3.equals(s4));  
        System.out.println(s1.equals(s4));  
        System.out.println(s1.equals(s3));  
    }  
}
```

## Output:

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\TestString.java

true

false

false

false

true

true

true

true

true

true

### Q. Lucky Star

```
public class LuckyStar {  
    public static void main(String[] args) {  
        String[] stars = {  
            "Robert Redford" , "Marilyn Monroe",  
            "Boris Karloff" , "Lassie",  
            "Hopalong Cassidy", "Trigger"  
        };  
        System.out.println("Your lucky star for today is " + stars[(int)(stars.length*Math.random())]);  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\LuckyStar.java

Your lucky star for today is Boris Karloff

## Q. Join String

```
public class JoinString {  
    public static void main(String[] args) {  
        String firstString = "Many ";  
        String secondString = "hands ";  
        String thirdString = "make light work";  
        String myString;  
  
        myString = firstString + secondString + thirdString;  
        System.out.println(myString);  
  
        int numHands = 99;  
        myString = numHands + " " + secondString + thirdString;  
        System.out.println(myString);  
  
        myString = "fifty five is " + 5 + 5;  
        System.out.println(myString);  
  
        myString = 5 + 5 + " is ten ";  
        System.out.println(myString);  
    }  
}
```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\JoinString.java

Many hands make light work

99 hands make light work

fifty five is 55

10 is ten

## Q. Match String

```
public class MatchStrings {
    public static void main(String[] args) {
        String string1 = "Too many ";
        String string2 = "cooks";
        String string3 = "Too many cooks";

        string1 += string2;

        System.out.println("Test 1");
        System.out.println("string3 is now: " + string3);
        System.out.println("string1 is now: " + string1);
        if(string1 == string3)
            System.out.println("string1 == string3 is true." + " string1 and string3 point to the same string");
        else
            System.out.println("string1 == string3 is false." + " string1 and string3 do not point to the same string");

        string3 = string1;

        System.out.println("\n\nTest 2");
        System.out.println("string3 is now: " + string3);
        System.out.println("string1 is now: " + string1);
        if(string1 == string3)
            System.out.println("string1 == string3 is true." + " string1 and string3 point to the same string");
        else
            System.out.println("string1 == string3 is false." + " string1 and string3 do not point to the same string");
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\MatchStrings.java

Test 1

string3 is now: Too many cooks



string1 is now: Too many cooks

string1 == string3 is false. string1 and string3 do not point to the same string

Test 2

string3 is now: Too many cooks

string1 is now: Too many cooks

string1 == string3 is true. string1 and string3 point to the same string

### Q. Match String (immutable string)

```
class Immutablestr{  
    public static void main(String args[]){  
        String s = "MCA 3 ";  
        s = s.concat("Placement");  
        System.out.println(s);  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Immutablestr.java

MCA 3 Placement

## Q. All Method of String

```
public class AllStringOperation {
    public static void main(String args[]){
        String str1 = "when it comes to web programming, java is #1.";
        String str2 = new String(str1);
        String str3 = "java strings are powerful.";
        int result,idx;
        char ch;

        System.out.println("length of str1 : "+str1.length());

        //display str1,one char at a time.
        for(int i=0;i<str1.length();i++)
            System.out.print(str1.charAt(i));

        System.out.println();

        if(str1.equals(str2))
            System.out.println("str1 equals str2");
        else
            System.out.println("str1 does not equal str2");

        if(str1.equals(str3))
            System.out.println("str1 equals str3");
        else
            System.out.println("str1 does not equal str3");

        result = str1.compareTo(str3);
        if(result == 0)
            System.out.println("str1 and str3 are equal");
        else if(result<0)
            System.out.println("str1 is less than str3");
        else
            System.out.println("str1 is greater than str3");

        idx = str2.indexOf("one");
        System.out.println("index of first occurence of one : "+idx);
        idx = str2.lastIndexOf("one");
        System.out.println("index of last occurence of one : "+idx);
    }
}
```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\AllStringOperation.java
```

length of str1 : 45

when it comes to web programming, java is #1.

str1 equals str2

str1 does not equal str3

str1 is greater than str3

index of first occurrence of one : -1

index of last occurrence of one : -1

## Q. Array of String

```
public class ArrayString {  
    public static void main(String args[]){  
        String str[] = { "this","is","a","test."};  
        System.out.print("original array : ");  
        for(String s : str)  
            System.out.print(s+" ");  
  
        System.out.println("\n");  
  
        str[1] = "was";  
        str[3] = "test , tool";  
        System.out.print("Modified array : ");  
        for(String s : str)  
            System.out.print(s+" ");  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\ArrayString.java

original array : this is a test.

Modified array : this was a test , tool

### Q. Sub-String

```
public class SubString {  
    public static void main(String args[]){  
        String orgstr = "java makes the web move.";  
  
        String substr = orgstr.substring(5,18);  
  
        System.out.println("orgstr : "+orgstr);  
        System.out.println("substr : "+substr);  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\SubString.java

orgstr : java makes the web move.

substr : makes the web

## Q. String Switch

```
public class StringSwitch {  
    public static void main(String args[]){  
        String command = "connect";  
  
        switch(command){  
            case "connect" :  
                System.out.println("connecting");  
                break;  
            case "cancel" :  
                System.out.println("canceling");  
                break;  
            case "disconnect" :  
                System.out.println("disconnecting");  
                break;  
            default :  
                System.out.println("command error");  
                break;  
        }  
    }  
}
```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\StringSwitch.java

Connecting

## Q. Using a StringBuffer Object to Assemble a String

```
public class UseStringBuffer {
    public static void main(String[] args) {
        StringBuffer sentence = new StringBuffer(20);
        System.out.println("\nStringBuffer object capacity is "+ sentence.capacity()+" and string length is "+sentence.length());

        String[] words = {"Too" , "many", "cooks", "spoi", "the" , "broth"};
        sentence.append(words[0]);
        for(int i = 1 ; i<words.length ; i++)
            sentence.append(' ').append(words[i]);

        System.out.println("\nString in StringBuffer object is:\n"+sentence.toString());
        System.out.println("StringBuffer object capacity is now "+ sentence.capacity()+" and string length is "+sentence.length());

        sentence.insert(sentence.lastIndexOf("cooks")+4,"ie");
        sentence.insert(sentence.lastIndexOf("broth")+5, "er");
        System.out.println("\nString in StringBuffer object is:\n "+ sentence);
        System.out.println("StringBuffer object capacity is now "+ sentence.capacity()+" and string length is "+sentence.length());
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\UseStringBuffer.java

StringBuffer object capacity is 20 and string length is 0

String in StringBuffer object is:



Too many cooks spoils the broth

StringBuffer object capacity is now 42 and string length is 29

String in StringBuffer object is:

Too many cookies spoils the broth

StringBuffer object capacity is now 42 and string length is 33

## Q. Exciting Concordance Entries

```
public class FindCharacter {
    public static void main(String[] args) {

        String text = "To be or not to be, that is the question;" + " Whether 'tis nobler in the mind to suffer" + " the slings and arrows of outrageous fortune," + " or to take arms against a sea of troubles," + " and by opposing end them?";

        int andCount = 0;
        int theCount = 0;
        int index = -1;
        String andStr = "and";
        String theStr = "the";

        index = text.indexOf(andStr);
        while(index >= 0) {
            ++andCount;
            index += andStr.length();
            index = text.indexOf(andStr, index);
        }

        index = text.lastIndexOf(theStr);
        while(index >= 0) {
            ++theCount;
            index -= theStr.length();
            index = text.lastIndexOf(theStr, index);
        }
        System.out.println("The text contains " + andCount + " ands\n" + "The text contains " + theCount + " thes");
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\FindCharacter.java

The text contains 2 ands

The text contains 5 thes

## Q. String Tokenizing

```
public class StringToken {  
    public static void main(String[] args) {  
        String text = "To be or not to be, that is the question.";  
        String delimiters = "[, .]";  
        int[] limits = {0, -1};  
  
        for(int limit : limits) {  
            System.out.println("\nAnalysis with limit = " + limit);  
            String[] tokens = text.split(delimiters, limit);  
            System.out.println("Number of tokens: " + tokens.length);  
            for(String token : tokens) {  
                System.out.println(token);  
            }  
        }  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\StringToken.java

Analysis with limit = 0

Number of tokens: 11

To

be

or

not

to

be

that

is

the

question

Analysis with limit = -1

Number of tokens: 12

To

be

or

not

to

be

that

is

the

question

# Exercise - 2

---

## Q. Exercise

- Month And Average

```
public class MonthAndAverage {
    public static void main(String args[]) {
        String[] monthNames = {
            "January" , "February", "March" , "April",
            "May"      , "June"    , "July"   , "August",
            "September", "October" , "November", "December"
        };

        double average = 0.0;
        double[] numbers = new double[12];

        for(int i = 0 ; i<numbers.length ; i++) {
            numbers[i] = Math.random()*100.0;
            System.out.println(monthNames[i] + " Generated " + numbers[i]);
            average += numbers[i];
        }
        average /= numbers.length;

        System.out.println("\nAverage of Random Generated numbers is " + average);
    }
}
```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice\23> java .\MonthAndAverage.java

January Generated 14.796351800091923

February Generated 39.711269832223785

March Generated 58.32386495973172

April Generated 19.083891467683557

May Generated 78.52264624324705

June Generated 72.46307769949362

July Generated 64.2760130349091

August Generated 51.97756817789709

September Generated 17.767136593640963

October Generated 71.2641366807655

November Generated 82.89356693449919

December Generated 49.55683721304006

Average of Random Generated numbers is 51.71969671976862

- **Tables**

```
public class Tables {
    final static int TABLESIZE = 12;
    public static void main(String[]args) {
        int[][] table = new int[TABLESIZE][TABLESIZE];

        for(int i = 0 ; i<table.length ; i++) {
            for(int j = 0 ; j<table[i].length ; j++)
                table[i][j] = (i+1)*(j+1);
        }

        System.out.print("      ");

        for(int j = 1 ; j<=table[0].length ; j++) {
            System.out.print((j<10 ? "   " : " ") + j);
        }

        System.out.println("\n.....
--");

        for(int i=0; i<table.length; i++) {
            System.out.print("Row" + (i<9 ? "   " : " ") + (i+1) + ":");

            for(int j=0; j<table[i].length; j++) {
```

```

        System.out.print((table[i][j]<10 ? " " : table[i][j]<100 ? " " :
" ") + table[i][j]);
    }

    System.out.println();
}
}
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice\23> java .\Tables.java

1 2 3 4 5 6 7 8 9 10 11 12

-----

Row 1: 1 2 3 4 5 6 7 8 9 10 11 12

Row 2: 2 4 6 8 10 12 14 16 18 20 22 24

Row 3: 3 6 9 12 15 18 21 24 27 30 33 36

Row 4: 4 8 12 16 20 24 28 32 36 40 44 48

Row 5: 5 10 15 20 25 30 35 40 45 50 55 60

Row 6: 6 12 18 24 30 36 42 48 54 60 66 72

Row 7: 7 14 21 28 35 42 49 56 63 70 77 84

Row 8: 8 16 24 32 40 48 56 64 72 80 88 96

Row 9: 9 18 27 36 45 54 63 72 81 90 99 108

Row 10: 10 20 30 40 50 60 70 80 90 100 110 120

Row 11: 11 22 33 44 55 66 77 88 99 110 121 132

Row 12: 12 24 36 48 60 72 84 96 108 120 132 144

- Sort

```
public class Sort {
    public static void main(String args[]) {

        String text = "Lorem Ipsum is simply dummy text of the printing and typesetting industry " +
            "It is a long established fact that a reader will be distracted by the readable content of a page when looking at its layout ";

        int count = 0;
        boolean isWord = false;
        for (int i = 0 ; i<text.length() ; i++) {
            if(isWord) {
                if(Character.isLetter(text.charAt(i)) || text.charAt(i) == '\\')
                    continue;
                else
                    isWord = false;
            }
            else if(Character.isLetter(text.charAt(i))) {

                count++;
                isWord = true;
            }
        }

        String[] words = new String[count];

        int start = 0;
        int wordIndex = 0;

        isWord = false;
        for (int i = 0 ; i<text.length() ; i++) {
            if(!isWord) {
                if(Character.isLetter(text.charAt(i))) {
                    start = i;
                    isWord = true;
                }
            }
            else {
                if(Character.isLetter(text.charAt(i)) || text.charAt(i) == '\\')
                    continue;
            }
        }
    }
}
```



```

        else {
            isWord = false;
            words[wordIndex++] = text.substring(start,i);
        }
    }
}

if(wordIndex < words.length)
    words[wordIndex] = text.substring(start);

String temp = null;
boolean exchange = true;
while(exchange) {
    exchange = false;
    for(int i = 1 ; i<words.length ; i++) {
        if(words[i-1].compareTo(words[i])>0) {
            temp = words[i];
            words[i] = words[i-1];
            words[i-1] = temp;
            exchange = true;
        }
    }
}

for(String word : words) {
    System.out.println(word);
}

}
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice\23> java .\Sort.java

Ipsum

It

Lorem

a

a

a

and

at

be

by

content

distracted

dummy

established

fact

industry

is

is

its

layout

long

looking

of

of

page

printing

readable

reader

simply

text

that

the

the

typesetting

when

will

- **Dates**

```
public class Date {  
    public static void main(String args[]) {  
        String[] dates = new String[10];  
        String[] monthNames = {  
            "January", "February", "March", "April",  
            "May", "June", "July", "August", "September",  
            "October", "November", "December"  
        };  
  
        int[] daysInMonth = {31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31};  
        String ending = "th";  
        String dayStr = null;  
        String monthStr = null;  
        String yearStr = null;  
        char separator = '/';  
        int day = 0;  
        int month = 0;
```

```

int year = 0;
int daysIncrement = 0;

for(int i=0 ; i<dates.length ; i++) {
    year = (int)(100.0*Math.random());
    month = (int)(12.0*Math.random()) + 1;

    daysIncrement = (((year % 4 == 0) && !(year % 100 == 0)) || (year % 4
00 == 0)) && (month == 2) ? 1 : 0;

    day = (int)(Math.random()*(daysInMonth[month-1]+daysIncrement))+1;
    dates[i] = "" + day + separator + month + separator + (year<10 ? "0"
:"") + year;
    System.out.println(dates[i]);
}

int start = 0;
int end = 0;

System.out.println();
for(String date : dates){
    start = 0;
    end = date.indexOf(separator,start);
    dayStr = date.substring(start, end);
    start = end+1;
    end = date.indexOf(separator,start);
    monthStr = date.substring(start, end);
    start = end+1;
    yearStr = date.substring(start);

    if(dayStr.length() == 1)
        switch(dayStr.charAt(0)) {
            case '1':
                ending = "st";
                break;
            case '2':
                ending = "nd";
                break;
            case '3':
                ending = "rd";
                break;
            default:
                ending = "th";
        }
}

```

```

        else if(dayStr.charAt(0) == '1')
            ending = "th";
        else
            switch(dayStr.charAt(1)) {
                case '1':
                    ending = "st";
                    break;
                case '2':
                    ending = "nd";
                    break;
                case '3':
                    ending = "rd";
                    break;
                default:
                    ending = "th";
            }

        System.out.println(dayStr + ending + " " +
            monthNames[monthStr.length() == 1 ? monthStr.charAt(0) -
'1': 9 + monthStr.charAt(1) - '0'] + " " + "19" + yearStr);
    }
}
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice\23> java .\Date.java

14/11/55

9/2/85

6/1/93

28/12/07

21/2/78

12/2/04

3/11/13

31/1/31

1/6/85

6/1/61

14th November 1955

9th February 1985

6th January 1993

28th December 1907

21st February 1978

12th February 1904

3rd November 1913

31st January 1931

1st June 1985

6th January 1961

- **Reverse**

```
public class Reverse {  
  
    public static void main(String args[]) {  
        String text = "Lorem Ipsum is simply dummy text of the printing and typeset  
ting industry " +  
            "\nIt is a long established fact that a reader will be distracted by the re  
adable content of a page when looking at its layout ";  
  
        boolean isWord = false;  
        int start = 0;  
        StringBuffer reversedText = new StringBuffer();
```

```

StringBuffer word = new StringBuffer();
for(int i = 0 ; i<text.length() ; i++) {
    if(!isWord) {
        if(Character.isLetter(text.charAt(i))) {
            word.append(text.charAt(i));
            isWord = true;
        } else {
            reversedText.append(text.charAt(i));
        }
    } else {
        if(Character.isLetter(text.charAt(i)) || text.charAt(i) == '\\') {
            word.append(text.charAt(i));
            continue;
        }
        else {
            reversedText.append(word.reverse());
            reversedText.append(text.charAt(i));
            word.delete(0,word.length());
            isWord = false;
        }
    }
}
if(word.length()>0)
    reversedText.append(word.reverse());

System.out.println(reversedText);
}
}

```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice\23> java .\Reverse.java

merol muspl si ylpmis ymmud txet fo eht gnitnirp dna gnittesepyt yrtsudni

tl si a gnol dehsilbatse tcaf taht a redaer lliw eb detcartsid yb eht elbadaer

tnetnoc fo a egap nehwn gnikool ta sti tuoyal

# Class Work - 3

---

## Q. Reference Assignment

```
public class AssignRef {  
    public static void main(String args[]){  
        int i;  
        int num1[] = new int[10];  
        int num2[] = new int[10];  
  
        for(i=0;i<10;i++)  
            num1[i] = i;  
  
        for(i=0;i<10;i++)  
            num2[i] = -i;  
  
        System.out.println("here is num1 : ");  
  
        for(i=0;i<10;i++)  
            System.out.print(num1[i]+" ");  
  
        System.out.println();  
        System.out.println("here is num2 : ");  
  
        for(i=0;i<10;i++)  
            System.out.print(num2[i]+" ");  
  
        System.out.println();  
  
        num2 = num1;  
  
        System.out.println("here is num2 after assignment : ");  
  
        for(i=0;i<10;i++)  
            System.out.print(num2[i]+" ");  
  
        System.out.println();  
  
        num2[3] = 99;  
  
        System.out.println("here is num1 after change through num1 : ");  
  
        for(i=0;i<10;i++)  
            System.out.print(num1[i]+" ");  
  
        System.out.println();  
    }  
}
```



**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\AssignRef.java
```

here is num1 :

0 1 2 3 4 5 6 7 8 9

here is num2 :

0 -1 -2 -3 -4 -5 -6 -7 -8 -9

here is num2 after assignment :

0 1 2 3 4 5 6 7 8 9

here is num1 after change through num1 :

0 1 2 99 4 5 6 7 8 9

## Q. Queue Demo

```
public class QueueDemo {
    public static void main(String args[]){
        Queue bigQ = new Queue(100);
        Queue smallQ = new Queue(4);
        char ch;

        System.out.println("Using bigQ to store the alphabet");

        for (int i = 0; i < 26; i++)
            bigQ.put((char) ('A' + i));

        System.out.println("Contents of bigQ: ");
        for (int i = 0; i < 26; i++) {
            ch = bigQ.get();
            if(ch != (char) 0)
                System.out.println(ch);
        }
        System.out.println("\n");

        System.out.println("Using smallQ to generate errors");
        for (int i = 0; i < 5; i++) {
            System.out.println("Attempting to store " + (char) ('Z' - i));
            smallQ.put((char) ('Z' - i));
            System.out.println();
        }
        System.out.println();

        System.out.println("Contents of smallQ : ");
        for (int i = 0; i < 5; i++) {
            ch = smallQ.get();
            if(ch != (char) 0)
                System.out.println(ch);
        }
    }
}

class Queue {
    char q[];
    int putloc;
    int getloc;

    Queue(int size) {
        q = new char[size];
        putloc = getloc = 0;
    }

    void put(char ch) {
        if(putloc == q.length) {
```

```

        System.out.println(" - Queue is Full.");
        return;
    }

    q[putloc++] = ch;
}

char get() {
    if(getloc == putloc) {
        System.out.println(" - Queue is Empty.");
        return (char) 0;
    }

    return q[getloc++];
}
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\QueueDemo.java

Using bigQ to store the alphabet

Contents of bigQ:

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

Q

R

S

T

U

V

W

X

Y

Z

Using smallQ to generate errors

Attempting to store Z

Attempting to store Y

Attempting to store X

Attempting to store W

Attempting to store V

- Queue is Full.

Contents of smallQ :

Z

Y

X

W

- Queue is Empty.

## Q. TryGeometry

```
import static java.lang.Math.sqrt;

public class TryGeometry {
    public static void main(String[] args) {
        Point start = new Point(0.0, 1.0);
        Point end = new Point(5.0, 6.0);
        System.out.println("Points created are " + start + " and " + end);

        Line line1 = new Line(start, end);
        Line line2 = new Line(0.0, 3.0, 3.0, 0.0);
        System.out.println("Lines created are " + line1 + " and " + line2);

        System.out.println("Intersection is " + line2.intersects(line1));

        end.move(1.0, -5.0);
        System.out.println("Intersection is " + line1.intersects(line2));
    }
}

class Point {
    // Coordinates of the point
    double x;
    double y;

    Point(double xVal, double yVal) {
        x = xVal;
        y = yVal;
    }

    Point(final Point oldPoint) {
        x = oldPoint.x;
        y = oldPoint.y;
    }

    void move(double xDelta, double yDelta) {
        x += xDelta;
        y += yDelta;
    }

    double distance(final Point aPoint) {
        return sqrt((x - aPoint.x)*(x - aPoint.x) + (y - aPoint.y)*(y -
aPoint.y));
    }

    public String toString() {
```

```

        return Double.toString(x) + ", " + y;
    }
}

class Line {
    Point start;
    Point end;

    Line(final Point start, final Point end) {
        this.start = new Point(start);
        this.end = new Point(end);
    }

    Line(double xStart, double yStart, double xEnd, double yEnd) {
        start = new Point(xStart, yStart);
        end = new Point(xEnd, yEnd);
    }

    double length() {
        return start.distance(end);
    }

    public String toString() {
        return "(" + start + "):(" + end + ")";
    }

    Point intersects(final Line line1) {
        Point localPoint = new Point(0, 0);
        double num = (this.end.y - this.start.y)*(this.start.x -
line1.start.x) -
        (this.end.x - this.start.x)*(this.start.y - line1.start.y);
        double denom = (this.end.y - this.start.y)*(line1.end.x -
line1.start.x) -
        (this.end.x - this.start.x)*(line1.end.y - line1.start.y);
        localPoint.x = line1.start.x + (line1.end.x -
line1.start.x)*num/denom;
        localPoint.y = line1.start.y + (line1.end.y -
line1.start.y)*num/denom;
        return localPoint;
    }
}

```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice\trygeometry> java .\TryGeometry.java
```

Points created are 0.0, 1.0 and 5.0, 6.0

Lines created are (0.0, 1.0):(5.0, 6.0) and (0.0, 3.0):(3.0, 0.0)

Intersection is 1.0, 2.0

Intersection is 1.0, 2.0



## Q. Rabbit Out of Hats

```
import java.util.Random;
public class MagicHat {
    static int maxRabbits = 5;
    static Random select = new Random();

    public MagicHat(String hatName) {
        this.hatName = hatName;
        rabbits = new Rabbit[1+select.nextInt(maxRabbits)];
        for(int i = 0; i < rabbits.length; i++) {
            rabbits[i] = new Rabbit();
        }
    }

    public String toString() {

        String hatString = "\n" + hatName + " contains:\n";
        for(Rabbit rabbit : rabbits) {
            hatString += " " + rabbit;
        }
        return hatString;
    }
    private String hatName;
    private Rabbit rabbits[];

    static class Rabbit {

    }

    static public void main(String[] args) {
        System.out.println(new MagicHat("Gray Topper"));
        System.out.println(new MagicHat("Black Topper"));
        System.out.println(new MagicHat("Baseball Cap"));
        MagicHat oldHat = new MagicHat("Old hat");
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\MagicHat.java

Gray Topper contains:

MagicHat\$Rabbit@275710fc MagicHat\$Rabbit@525f1e4e  
MagicHat\$Rabbit@75f9eccc MagicHat\$Rabbit@52aa2946

Black Topper contains:

MagicHat\$Rabbit@4de5031f MagicHat\$Rabbit@67e2d983  
MagicHat\$Rabbit@5d47c63f

Baseball Cap contains:

MagicHat\$Rabbit@5ea434c8 MagicHat\$Rabbit@3bbc39f8  
MagicHat\$Rabbit@4ae3c1cd MagicHat\$Rabbit@29f69090  
MagicHat\$Rabbit@568bf312

## Q. Nested Class Demo

```
public class NestedClassDemo {
    public static void main(String args[]){
        int x[] = {3,2,1,5,6,9,7,8};
        Outer outob = new Outer(x);
        outob.analyze();
    }
}
class Outer{
    int nums[];
    Outer(int n[]){
        nums=n;
    }
    void analyze(){
        Inner inob = new Inner();
        System.out.println("Minimum : "+inob.min());
        System.out.println("Maximum: "+inob.max());
        System.out.println("Average : "+inob.avg());
    }
    class Inner{
        int min(){
            int m = nums[0];
            for(int i =1; i<nums.length; i++)
                if(nums[i] < m) m = nums[i];
            return m;
        }
        int max(){
            int m = nums[0];
            for(int i =1; i<nums.length; i++)
                if(nums[i] > m) m = nums[i];
            return m;
        }
        int avg(){
            int a = 0;
            for(int i =1; i<nums.length; i++)
                a += nums[i];

            return a/nums.length;
        }
    }
}
```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\NestedClassDemo.java
```

Minimum : 1

Maximum: 9

Average : 4

## Q. Interface

### → Conversion.java

```
package conversions;
public interface Conversion {
    double inchesToMillimeters (double inches);
    double ouncesToGrams(double ounces);
    double poundsToGrams(double pounds);
    double hpToWatts(double hp);
    double wattsToHP(double watts);
}
```

### → ConversionFactors.java

```
package conversions;
public interface ConversionFactors {
    double INCH_TO_MM = 25.4;
    double OUNCE_TO_GRAM = 28.349523125;
    double POUND_TO_GRAM = 453.5924;
    double HP_TO_WATT = 745.7;
    double WATT_TO_HP = 1.0/HP_TO_WATT;
}
```

### → TryConversion.java

```
package conversions;
import static conversions.ConversionFactors.*; // Import static members
public class TryConversion implements Conversion {
    public double wattsToHP (double watts) {
        return watts*WATT_TO_HP;
    }
    public double hpToWatts (double hp) {
        return hp*HP_TO_WATT;
    }
    public double ouncesToGrams(double ounces) {
        return ounces*OUNCE_TO_GRAM;
    }
    public double poundsToGrams(double pounds) {
        return pounds*POUND_TO_GRAM;
    }
    public double inchesToMillimeters(double inches) {
        return inches*INCH_TO_MM;
    }
}
```

```

    }
    public static void main(String args[]) {
        int myWeightInPounds = 180;
        int myHeightInInches = 75;
        TryConversion converter = new TryConversion();
        System.out.println("My weight in pounds: " + myWeightInPounds + " \t -in grams: " + (int)converter.poundsToGrams(myWeightInPounds));
        System.out.println("My height in inches: " + myHeightInInches + " \t -in millimeters: " + (int)converter.inchesToMillimeters(myHeightInInches));
    }
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\Conversion.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\ConversionFactors.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\TryConversion.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> java conversions.TryConversion

My weight in pounds: 180      -in grams: 81646

My height in inches: 75      -in millimeters: 1905

## Q. Defining Interface

### → RemoteControl.java

```
package remote;

public interface RemoteControl {

    boolean powerOnOff(); // Returns new state, on = true
    int volumeUp(int increment); // Returns new volume level
    int volumeDown(int decrement); // Returns new volume level
    void mute(); // Mutes sound output
    int setChannel(int channel); // Set the channel number and return it
    int channelUp(); // Returns new channel number
    int channelDown(); // Returns new channel number
}
```

### → TV.java

```
package remote;

import static java.lang.Math.max;
import static java.lang.Math.min;

public class TV implements RemoteControl {

    public TV(String make, int screensize) {
        this.make = make;
        this.screensize = screensize;
    }

    public boolean powerOnOff() {
        power = !power;
        System.out.println(make + " " + screensize + " inch TV power " + (power ? "on." : "off. "));
        return power;
    }

    public int volumeUp(int increment) {
        if(!power)
            return 0;

        volume += increment;
        volume = min(volume, MAX_VOLUME);
    }
}
```

```

        System.out.println(make + " " + screensize + " inch TV volume level: " + volume);
        return volume;
    }

    public int volumeDown(int decrement) {
        if(!power)
            return 0;

        volume -= decrement;
        volume = max(volume, MIN_VOLUME);
        System.out.println(make + " " + screensize + " inch TV volume level: " + volume);
        return volume;
    }

    public void mute() {
        if(!power)
            return;

        volume = MIN_VOLUME;
        System.out.println(make + " " + screensize + " inch TV volume level: " + volume);
    }

    public int setChannel(int newChannel) {
        if(!power)
            return 0;

        if(newChannel >= MIN_CHANNEL && newChannel <= MAX_CHANNEL)
            channel = newChannel;

        System.out.println(make + " " + screensize + " inch TV tuned to channel: " + channel);
        return channel;
    }

    public int channelUp(){
        if(!power)
            return 0;

        channel = channel < MAX_CHANNEL ? ++channel : MIN_CHANNEL;
        System.out.println(make + " " + screensize + " inch TV tuned to channel: " + channel);
        return channel;
    }

```



```

    }

    public int channelDown(){
        if(!power)
            return 0;

        channel = channel > MIN_CHANNEL ? --channel : MAX_CHANNEL;
        System.out.println(make + " " + screensize + " inch TV tuned to channel: "
+ channel);
        return channel;
    }
    private String make = null;
    private int screensize = 0;
    private boolean power = false;
    private int MIN_VOLUME = 0;
    private int MAX_VOLUME = 100;
    private int volume = MIN_VOLUME;
    private int MIN_CHANNEL = 0;
    private int MAX_CHANNEL = 999;
    private int channel = 0;
}

```

## ➔ VCR.java

```

package remote;
import static java.lang.Math.max;
import static java.lang.Math.min;
public class VCR implements RemoteControl {
    public VCR(String make) {
        this.make = make;
    }

    public boolean powerOnOff() {
        power = !power;
        System.out.println(make + " VCR power " + (power ? "on.":"off."));
        return power;
    }

    public int volumeUp(int increment) {
        if(!power)
            return 0;
    }
}

```

```

        volume += increment;
        volume = min(volume, MAX_VOLUME);
        System.out.println(make + " VCR volume level: " + volume);
        return volume;
    }

    public int volumeDown(int decrement) {
        if(!power)
            return 0;

        volume -= decrement;
        volume = max(volume, MIN_VOLUME);
        System.out.println(make + " VCR volume level: " + volume);
        return volume;
    }

    public void mute() {
        if(!power)
            return;

        volume = MIN_VOLUME;
        System.out.println(make + " VCR volume level: " + volume);
    }

    public int setChannel(int newChannel) {
        if(!power)
            return 0;

        if(newChannel >= MIN_CHANNEL && newChannel <= MAX_CHANNEL)
            channel = newChannel;

        System.out.println(make + " VCR tuned to channel: " + channel);
        return channel;
    }

    public int channelUp(){
        if(!power)
            return 0;

        channel = channel < MAX_CHANNEL ? ++channel : MIN_CHANNEL;
        System.out.println(make + " VCR tuned to channel: " + channel);
        return channel;
    }

```

```

public int channelDown(){
    if(!power)
        return 0;

    channel = channel > MIN_CHANNEL ? --channel : MAX_CHANNEL;
    System.out.println(make + " VCR tuned to channel: " + channel);
    return channel;
}
private String make = null;
private boolean power = false;
private int MIN_VOLUME = 0;
private int MAX_VOLUME = 100;
private int volume = MIN_VOLUME;
private int MIN_CHANNEL = 0;
private int MAX_CHANNEL = 99;
private int channel = 0;
}

```

## → TryRemoteControl.java

```

package remote;
import static java.lang.Math.random;
public class TryRemoteControl {
    public static void main(String args[]) {
        RemoteControl remote = null;
        for(int i = 0 ; i<5 ; i++) {
            if(random()<0.5)
                remote = new TV(random()<0.5 ? "Sony" : "Hitachi",random()<0.5 ?
32 : 28);
            else
                remote = new VCR(random()<0.5 ? "Panasonic": "JVC");
            remote.powerOnOff();
            remote.channelUp();
            remote.volumeUp(10);
        }
    }
}

```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\RemoteControl.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\TV.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\VCR.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\TryRemoteControl.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> java remote.TryRemoteControl
```

Panasonic VCR power on.

Panasonic VCR tuned to channel: 1

Panasonic VCR volume level: 10

JVC VCR power on.

JVC VCR tuned to channel: 1

JVC VCR volume level: 10

Hitachi 32 inch TV power on.

Hitachi 32 inch TV tuned to channel: 1

Hitachi 32 inch TV volume level: 10

JVC VCR power on.

JVC VCR tuned to channel: 1

JVC VCR volume level: 10

Hitachi 32 inch TV power on.

Hitachi 32 inch TV tuned to channel: 1

Hitachi 32 inch TV volume level: 10

## Q. Queue Interface

→ ICharQ.java

```
public interface ICharQ
{
    //Put a character into the queue
    void put(char ch);
    //Get a character from the queue
    char get();
}
```

→ IQDemo.java

```
class FixedQueue implements ICharQ{
    private char q[];
    private int putloc,getloc;

    public FixedQueue(int size)
    {
        q = new char[size];
        putloc = getloc = 0;
    }

    public void put(char ch)
    {
        if(putloc == q.length)
        {
            System.out.println("Alert : Queue is full");
            return;
        }
        q[putloc++] = ch;
    }

    public char get()
    {
        if(getloc == putloc)
        {
            System.out.println("Alert : Queue is empty");
            return (char) 0;
        }
    }
}
```

```

        return q[getloc++];
    }
}

class CircularQueue implements ICharQ
{
    private char q[];
    private int putloc, getloc;

    public CircularQueue(int size)
    {
        q = new char[size+1];
        putloc = getloc = 0;
    }

    public void put(char ch)
    {
        if(putloc+1 == getloc | ((putloc == q.length-1) & (getloc == 0)))
        {
            System.out.println("Alert : Queue is full");
            return;
        }
        q[putloc++] = ch;
        if(putloc == q.length)
        {
            putloc = 0;
        }
    }

    public char get()
    {
        if(getloc == putloc)
        {
            System.out.println("Alert : Queue is empty");
            return (char) 0;
        }
        char ch = q[getloc++];
        if(getloc == q.length) getloc = 0;
        return ch;
    }
}

class DynQueue implements ICharQ
{

```

```

private char q[];
private int putloc, getloc;

public DynQueue(int size)
{
    q = new char[size];
    putloc = getloc = 0;
}

public void put(char ch)
{
    if(putloc == q.length)
    {
        char t[] = new char[q.length * 2];

        for(int i=0; i < q.length; i++)
            t[i] = q[i];
        q = t;
    }
    q[putloc++] = ch;
}

public char get()
{
    if(getloc == putloc)
    {
        System.out.println("Alert : Queue is empty");
        return (char) 0;
    }
    return q[getloc++];
}
}

class IQDemo
{
    public static void main(String[] args)
    {
        FixedQueue fixedQueue = new FixedQueue(10);
        DynQueue dynQueue = new DynQueue(5);
        CircularQueue circularQueue = new CircularQueue(10);

        ICharQ iQ;
        char ch;
    }
}

```

```
int i;
iQ = fixedQueue;

for(i=0; i < 10;i++)
{
    iQ.put((char) ('A' + i));
}

System.out.println("Contents of FixedQueue: ");
for(i = 0; i < 10; i++)
{
    ch = iQ.get();
    System.out.print(ch);
}
System.out.println();

iQ = dynQueue;

for(i=0; i < 10;i++)
{
    iQ.put((char) ('Z' - i));
}

System.out.println("Contents of DynQueue: ");
for(i = 0; i < 10; i++)
{
    ch = iQ.get();
    System.out.print(ch);
}
System.out.println();

iQ = circularQueue;

for(i=0; i < 10;i++)
{
    iQ.put((char) ('A' + i));
}

System.out.println("Contents of CircularQueue: ");
for(i = 0; i < 10; i++)
{
```



```

        ch = iQ.get();
        System.out.print(ch);
    }
    System.out.println();

    for(i=10; i < 20;i++)
    {
        iQ.put((char) ('A' + i));
    }

    System.out.println("Contents of CircularQueue: ");
    for(i = 0; i < 10; i++)
    {
        ch = iQ.get();
        System.out.print(ch);
    }
    System.out.println("\nStore and consume from circularqueue");

    for(i = 0; i < 20; i++)
    {
        iQ.put((char) ('A' + i));
        ch = iQ.get();
        System.out.print(ch);
    }
}
}

```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac .\ICharQ.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac .\IQDemo.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> java IQDemo

Contents of FixedQueue:

ABCDEFGHIJ

Contents of DynQueue:

ZYXWVUTSRQ

Contents of CircularQueue:

ABCDEFGHIJ

Contents of CircularQueue:

KLMNOPQRST

Store and consume from circular queue

ABCDEFGHIJKLMNOPQRST

## Q. Generic Functional Interface

```
class GenericFunctionalInterface
{
    public static void main(String[] args)
    {
        SomeTest<Integer> isFactor = (n,d) -> (n%d) == 0;

        if(isFactor.test(10,2))
            System.out.println("2 is factor of 10");
        System.out.println();

        SomeTest<Double> isFactorD = (n,d) -> (n%d) == 0;

        if(isFactorD.test(212.0,4.0))
            System.out.println("4 is factor of 212");

        System.out.println();

        SomeTest<String> isIn = (a, b) -> a.indexOf(b) != -1;
        String str = "Generic Functional Interface";
        if(isIn.test(str, "face"))
            System.out.println("face is found");
        else
            System.out.println("face is no found");
    }
}

interface SomeTest<T>
{
    boolean test(T n, T m);
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\GenericFunctionalInterface.java

2 is factor of 10

4 is factor of 212

face is found

## Q. Lambda Argument Demo

```
public class LambdaArgumentDemo {
    static String changeStr(StringFunc sf, String s) {
        return sf.func(s);
    }

    public static void main(String args[]) {
        String inStr = "Lambda Expression Expand Java";
        String outStr;

        System.out.println("Here is input string : " + inStr);

        StringFunc reverse = (str) -> {
            String result = "";
            for (int i = str.length()-1; i >= 0; i--)
                result += str.charAt(i);

            return result;
        };

        outStr = changeStr(reverse, inStr);
        System.out.println("The string reversed : " + outStr);

        outStr = changeStr((str) -> str.replace(' ', '-'), inStr);
        System.out.println("The string with spaces replaced : " + outStr);

        outStr = changeStr((str) -> {
            String result = "";
            char ch;

            for (int i = 0; i < str.length(); i++) {
                ch = str.charAt(i);
                if(Character.isUpperCase(ch))
                    result += Character.toLowerCase(ch);
                else
                    result += Character.toUpperCase(ch);
            }
            return result;
        }, inStr);
        System.out.println("The string in reversed case : " + outStr);
    }
}
```

```
interface StringFunc {  
    String func(String str);  
}
```

### **Output :**

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\LambdaArgumentDemo.java

Here is input string : Lambda Expression Expand Java

The string reversed : avaJ dnapxE noisserpxE adbmaL

The string with spaces replaced : Lambda-Expression-Expand-Java

The string in reversed case : lAMBDA eXPRESSION eXPAND jAVA

## Q. Lambda Exception Demo

```
import java.io.*;

class LambdaExceptionDemo{
    public static void main(String args[])
    {
        double[] values = {1.0,2.0,3.0,4.0};
        MyIOAction myIO = (rdr) -> {
            int ch = rdr.read();
            return true;
        };
    }
}

interface MyIOAction{
    boolean ioAction(Reader rdr) throws IOException;
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\LambdaExceptionDemo.java

PS D:\MCA\MCA SEM 3\JAVA\Practice>

## Q. Package ExtInterface

### → ExtInterface.java

```
package extInterface;  
public interface ExtInterface {  
    public void method1();  
    public void method2();  
}
```

### → TestExtInterface.java

```
package extInterface;  
  
import java.util.Scanner;  
  
class TestExtInterface implements ExtInterface{  
    public void method1() {  
        System.out.println("Implementation of Method1");  
        Scanner sc = new Scanner(System.in);  
        System.out.println("Enter number to find the Square root in java:");  
        double square = sc.nextDouble();  
        double squareRoot = Math.sqrt(square);  
        System.out.printf("Square root of number: %f is -  
> %f", square, squareRoot);  
    }  
    public void method2() {  
        System.out.println("Implementation of method2");  
    }  
    public static void main(String[] args) {  
        ExtInterface obj = new TestExtInterface();  
        obj.method1();  
    }  
}
```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice\35> javac -d . .\ExtInterface.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice\35> javac -d . .\TestExtInterface.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice\35> java extInterface.TestExtInterface
```

Implementation of Method1

Enter number to find the Square root in java:

9

Square root of number: 9.000000 is -> 3.000000



## Q. Package BasicOperation

### → Math.java

```
package basicoperation;
public interface Math{
    public void add();
    public void sub();
    public void mul();
    public void div();
}
```

### → Student.java

```
package basicoperation;
import java.util.Scanner;
public class Student implements math{
    @Override
    public void add() {
        Scanner kb = new Scanner(System.in);
        System.out.println("Enter any two integer values to perform addition : ");
;
        int a = kb.nextInt();
        int b = kb.nextInt();
        int s = a + b;
        System.out.println("Difference of "+a+" and "+b+" is "+s);
    }

    @Override
    public void sub() {
        Scanner kb = new Scanner(System.in);
        System.out.println("Enter any two integer values to perform subtraction : ");
;
        int a = kb.nextInt();
        int b = kb.nextInt();
        int s = a - b;
        System.out.println("Difference of "+a+" and "+b+" is "+s);
    }
}
```

```

@Override
public void mul() {
    Scanner kb = new Scanner(System.in);
    System.out.println("Enter any two integer values to perform multiplication : ");
    int a = kb.nextInt();
    int b = kb.nextInt();
    int s = a * b;
    System.out.println("Difference of "+a+" and "+b+" is "+s);
}

@Override
public void div() {
    Scanner kb = new Scanner(System.in);
    System.out.println("Enter any two integer values to perform division : ");
    int a = kb.nextInt();
    int b = kb.nextInt();
    int s = a / b;
    System.out.println("Difference of "+a+" and "+b+" is "+s);
}

public static void main(String[] args){
    Student stu = new Student();
    stu.add();
    stu.sub();
    stu.mul();
    stu.div();
}
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java basicoperation.Student

Enter any two integer values to perform addition :

10 20

Difference of 10 and 20 is 30

Enter any two integer values to perform subtraction :

30 20

Difference of 30 and 20 is 10

Enter any two integer values to perform multiplication :

2

30

Difference of 2 and 30 is 60

Enter any two integer values to perform division :

40 2

Difference of 40 and 2 is 20

## Q. Package mca

### → Solution.java

```
package mca;  
public interface Solution{  
    public void Hello();  
    public void Welcome();  
}
```

### → classA.java

```
package mca;  
public class classA implements Solution {  
    public void Hello(){  
        System.out.println("Hello World");  
    }  
    public void Welcome(){  
        System.out.println("Welcome MCAIII");  
    }  
  
    public static void main(String[] args) {  
        classA test = new classA();  
        test.Hello();  
        test.Welcome();  
    }  
}
```

## Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java mca.classA

Hello World

Welcome MCAIII

## Q. Package book

### ➔ Books.java

```
package backpack;

public class Books{
    //these are protected members
    protected String title;
    protected String author;
    protected int pubDate;

    public Books(String t, String a, int d)
    {
        title = t;
        author = a;
        pubDate = d;
    }

    public void show()
    {
        System.out.println(title);
        System.out.println(author);
        System.out.println(pubDate);
        System.out.println();
    }
}
```

### ➔ UseBook.java

```
package bookpackext;
import backpack.*;

class UseBook {
    public static void main(String args[])
    {
        Books book[] = new Books[5];
        book[0] = new Books("Java: A Beginner's Guide","Schildt",2014);

        book[1] = new Books("Java: The Complete Reference","Schildt",2014);

        book[2] = new Books("The Art of Java","Schildt and Holmes",2003);
    }
}
```

```

        book[3] = new Books("Red Storm Rising","Clancy",1986);

        book[4] = new Books("On The Road","Kerouac",1955);

        for(int index = 0; index < book.length;index++) book[index].show();
    }
}

```

## → ProtectDemo.java

```

package backpackext;

class ExtBook extends backpack.Books{
    private String publisher;
    public ExtBook(String t,String a, int d,String p)
    {
        super(t,a,d);
        publisher = p;
    }

    public void show()
    {
        super.show();
        System.out.println(publisher);
        System.out.println();
    }

    public String getPublisher() { return publisher; }
    public void setPublisher(String p) { publisher = p; }

    public String getTitle() { return title; }
    public void setTitle(String t) { title = t; }

    public String getAuthor() { return author; }
    public void setAuthor(String a) { author = a; }

    public int getPubDate() { return pubDate; }
    public void setTitle(int d) { pubDate = d; }
}

```

```

class ProtectDemo
{
    public static void main(String[] args)
    {
        ExtBook books[] = new ExtBook[5];
        books[0] = new ExtBook("Java: A Beginner's Guide","Schildt",2014,"McGrew-
Hill Professional");

        books[1] = new ExtBook("Java: The Complete Reference","Schildt",2014,"McG
rew-Hill Professional");

        books[2] = new ExtBook("The Art of Java","Schildt and Holmes",2003,"McGre
w-Hill Professional");

        books[3] = new ExtBook("Red Storm Raising","Clancy",1986,"Putham");

        books[4] = new ExtBook("On The Road","Kerouac",1955,"Viking");

        for(int index = 0; index < books.length; index++)
        {
            books[index].show();
        }

        System.out.println("Showing all books by schildt.");
        for(int index=0;index<books.length;index++)
        {
            if(books[index].getAuthor() == "Schildt")
            {
                System.out.println(books[index].getTitle());
            }
            //books[index].title = "test title"; error by accessing protected
        }
    }
}

```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\Books.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\UseBook.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\ProtectDemo.java

PS D:\MCA\MCA SEM 3\JAVA\Practice> java bookpackext.ProtectDemo

Java: A Beginner's Guide

Schildt

2014

McGraw-Hill Professional

Java: The Complete Reference

Schildt

2014

McGraw-Hill Professional

The Art of Java

Schildt and Holmes

2003

McGraw-Hill Professional

Red Storm Raising

Clancy

1986



Putham

On The Road

Kerouac

1955

Viking

Showing all books by schildt.

Java: A Beginner's Guide

Java: The Complete Reference

## Q. Series Program

➔ Series.java

```
public interface Series
{
    int getNext();
    void reset();
    void setStart(int x);
}
```

➔ SeriesDemo.java

```
class ByTwos implements Series
{
    int start;
    int val;

    ByTwos() {
        start = 0;
        val = 0;
    }

    public int getNext() {
        val += 2;
        return val;
    }

    public void reset()
    {
        val = start;
    }

    public void setStart(int x)
    {
        start = x;
        val = x;
    }
}

class ByThrees implements Series
{
    int start;
```

```

    int val;

    ByThrees() {
        start = 0;
        val = 0;
    }

    public int getNext(){
        val += 3;
        return val;
    }

    public void reset()
    {
        val = start;
    }

    public void setStart(int x)
    {
        start = x;
        val = x;
    }
}

class SeriesDemo{
    public static void main(String args[])
    {
        ByTwos twoOb = new ByTwos();
        ByThrees threeOb = new ByThrees();
        Series ob;

        for(int i=0; i < 5; i++)
        {
            ob = twoOb;
            System.out.println("Next ByTwos value is " + ob.getNext());

            ob = threeOb;
            System.out.println("Next ByThrees value is " + ob.getNext());
        }
    }
}

```

**Output :**

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\Series.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> javac -d . .\SeriesDemo.java
```

```
PS D:\MCA\MCA SEM 3\JAVA\Practice> java SeriesDemo
```

Next ByTwos value is 2

Next ByThrees value is 3

Next ByTwos value is 4

Next ByThrees value is 6

Next ByTwos value is 6

Next ByThrees value is 9

Next ByTwos value is 8

Next ByThrees value is 12

Next ByTwos value is 10

Next ByThrees value is 15

## Q. Lambda Displayable

```
public class LambdaDisplayable implements displayble {
    public void display(String msg){
        System.out.println(msg);
    }
    public static void main(String[] args) {
        LambdaDisplayable dis = new LambdaDisplayable();
        dis.display("Welcome to the World.");
    }
}
interface displayble {
    void display(String msg);
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\LambdaDisplayable.java

Welcome to the World.

### Q. Lambda with functional Interface

```
public class LambdaFuntionalInterface {  
    public static void main(String[] args)  
    {  
        FuncInterface fobj = (int x) -> System.out.println(2*x);  
        fobj.abstractFun(12);  
    }  
}  
  
interface FuncInterface{  
    void abstractFun(int x);  
  
    default void normalFun()  
    {  
        System.out.println("Hello");  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\LambdaFuntionalInterface.java

## Q. Calculator Using Lambda

```
public class Functionallambda {
    interface IntegerMath {
        int operation(int a, int b);
    }

    public int operateBinary(int a, int b, IntegerMath op) {
        return op.operation(a, b);
    }

    public static void main(String[] args) {
        Functionallambda myApp = new Functionallambda();

        IntegerMath addition = (a, b) -> a + b;
        IntegerMath subtraction = (a, b) -> a - b;
        IntegerMath multiplication = (a, b) -> a * b;
        IntegerMath division = (a, b) -> a / b;

        int a = 10, b = 5;

        System.out.println(a + " + " + b + " = " + myApp.operateBinary(a, b, addition));
        System.out.println(a + " - "
            + b + " = " + myApp.operateBinary(a, b, subtraction));
        System.out.println(a + " * " + b + " = " + myApp.operateBinary(a, b, multiplication));
        System.out.println(a + " / " + b + " = " + myApp.operateBinary(a, b, division));
    }
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Functionallambda.java

10 + 5 = 15

10 - 5 = 5

10 \* 5 = 50

10 / 5 = 2

## Q. Implement Uber using interface, Anonymous class and Lambda Expression

### ➔ Uber1.java

```
public class Uber1 {  
    public static void main(String[] args) {  
        Cab cab = new UberX1();  
        cab.bookCab();  
    }  
}  
  
@FunctionalInterface  
interface Cab {  
    void bookCab();  
}  
  
class UberX1 implements Cab {  
    public void bookCab() {  
        System.out.println("UberX Booked!! Arriving Soon !!");  
    }  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Uber1.java

UberX Booked!! Arriving Soon !!

### ➔ Uber2.java

```
public class Uber2 {  
    public static void main(String[] args) {  
        Cab cab = new Cab() {  
  
            @Override  
            public void bookCab() {  
                System.out.println("UberX Booked!! Arriving Soon !!");  
            }  
        };  
  
        cab.bookCab();  
    }  
}
```



```
    }  
}  
  
@FunctionalInterface  
interface Cab {  
    void bookCab();  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Uber2.java

UberX Booked!! Arriving Soon !!

### ➔ Uber3.java

```
public class Uber3 {  
    public static void main(String[] args) {  
        Cab cab = () -> System.out.println("UberX Booked!! Arriving Soon !!");  
        cab.bookCab();  
    }  
}  
  
@FunctionalInterface  
interface Cab {  
    void bookCab();  
}
```

### Output :

PS D:\MCA\MCA SEM 3\JAVA\Practice> java .\Uber3.java

UberX Booked!! Arriving Soon !!