

PRIMING

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

Priming: fill casing with water before start. Never run dry beyond 30 seconds.

CAVITATION SHUTDOWN

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

Cavitation shutdown: stop pump if vibration exceeds 7 mm/s. Torque flange bolts to 40 Nm.

SEAL CHECK

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

Seal check: inspect mechanical seal faces every 500 hours. Replace if leakage exceeds 5 drops per minute

BEARING LUBE

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

Bearing lube: grease bearings with lithium EP2 every 2000 hours. Quantity 30 grams per bearing.

LOG ENTRY

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.

Log entry: record suction pressure, discharge pressure and amps in shift log sheet 7B.