



HTML Marquee Tag

[HTML Tutorial Index](#)

[HTML Overview](#)

[HTML Basics](#)

[HTML Tags](#)

[HTML Comment Tag](#)

[HTML Head Tag](#)

[HTML Meta Tag](#)

[HTML Body Tag](#)

[HTML Heading Tag](#)

[HTML Anchor](#)

[HTML Div Tag](#)

[HTML Fonts](#)

[HTML Images](#)

Marquee is one of the important tags introduced in HTML to support such scrollable texts and images within a web page. In this tutorial, you will be learning about the Marquee tag and its different attributes for developing a well-groomed static website.

The Marquee Tag

The `<marquee>` tag is a container tag of HTML is implemented for creating scrollable text or images within a web page from either left to right or vice versa, or top to bottom or vice versa. But this tag has been **deprecated in the new version of HTML, i.e., HTML 5**.

The different attributes of `<marquee>` tag are:

HTML Phrase Tags

HTML Lists

HTML Tables

HTML Frames

HTML Marquee Tag

HTML Blink Tag

HTML Video Tag

HTML Abbr Tag

HTML Blockquote Tag

HTML Button tag

HTML Attributes

HTML Colors

HTML Forms

[report this ad](#)

Attribute	Description
width	provides the width or breadth of a marquee. For example <code>width="10"</code> or <code>width="20%"</code>
height	provides the height or length of a marquee. For example <code>height="20"</code> or <code>height="30%"</code>
direction	provides the direction or way in which your marquee will allow you to scroll. The value of this attribute can be: left, right, up or down
scrollDelay	provides a feature whose value will be used for delaying among each jump.
scrollAmount	provides value for speeding the marquee feature
behavior	provides the scrolling type in a marquee. That scrolling can be like sliding, scrolling or alternate
loop	provides how many times the marquee will loop
bgcolor	provides a background color where the value will be either the name of the color or the hexadecimal color-code.
vspace	provides a vertical space and its value can be like: <code>vspace="20"</code> or <code>vspace="30%"</code>

hspace	provides a horizontal space and its value can be like: <code>hspace="20"</code> or <code>hspace="30%"</code>
--------	--

[report this ad](#)


Here's are some example of how to use `<marquee>` tag in HTML:

Scroll Up

Example:

```
<marquee width="60%" direction="up" height="100px">  
This is a sample scrolling text that has scrolls in the upper direction.  
</marquee>
```


Output:



Scroll Down

Example:

```
<marquee width="60%" direction="down" height="100px">  
This is a sample scrolling text that has scrolls texts to down.  
</marquee>
```

Output:**Scroll Left to Right**

Example:

```
<marquee width="60%" direction="right" height="100px">  
This is a sample scrolling text that has scrolls texts to right.  
</marquee>
```

Output:

ig text that has scrolls texts to right.

Scroll Right to Left

Example:

```
<marquee width="60%" direction="left" height="100px">  
This is a sample scrolling text that has scrolls texts to left.  
</marquee>
```

Output:

This is a sample scrolling text that has s

Scrolling Speed

Marquee speed can be changed using the "scrollmount" attribute. For example, if you are using `scrollmount="1"` then it sets the marquee to scroll very slowly, and as you increase the "scrollmount," the scrolling speed will also increase.

Example:

```
<marquee behavior="scroll" direction="up" scrollamount="1">Slow  
Scrolling</marquee>
```

```
<marquee behavior="scroll" direction="right" scrollamount="12">Little Fast Scrolling</marquee>  
<marquee behavior="scroll" direction="left" scrollamount="20">Fast Scrolling</marquee>  
<marquee behavior="scroll" direction="right" scrollamount="50">Very Fast Scrolling</marquee>
```

Output:

Slow Scrolling

Little Fast Scrolling

Marquee can also be implemented using CSS. Read the [CSS Marquee](#) chapter to learn more about it.

Blinking Text Within Marquee

```
<html>  
  
  <head>  
    <title>Example of a blinking text using CSS within a
```

```
        animation: blinker 1.5s linear infinite;
        color: red;
        font-family: sans-serif;
    }
    @keyframes blinker {
        50% {
            opacity: 0;
        }
    }
</style>
</head>

<body>
    <marquee class="blink">This is an example of blinking text using
CSS within a marquee.</marquee>
</body>

</html>
```

Output:

© 2009 — 2023 W3schools® of Technology.