

## Component Mapping

```
// Creating a table eproduct in the database and filling it with sample
data
/*!40101 SET
@OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIE
NT */;
/*!40101 SET
@OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RE
SULTS */;
/*!40101 SET
@OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTI
ON */;
/*!40101 SET NAMES utf8 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS,
UNIQUE_CHECKS=0 */;
/*!40014 SET
@OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS,
FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE,
SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES,
SQL_NOTES=0 */;

--
-- Table structure for table `eproduct`
--

DROP TABLE IF EXISTS `eproduct`;
/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE `eproduct` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `name` varchar(100) DEFAULT NULL,
```

```

`price` decimal(10,2) DEFAULT NULL,
`date_added` timestamp NOT NULL DEFAULT
CURRENT_TIMESTAMP,
`parts_hdd` varchar(10) DEFAULT NULL,
`parts_cpu` varchar(10) DEFAULT NULL,
`parts_ram` varchar(10) DEFAULT NULL,
PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT
CHARSET=latin1;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `eproduct`
--

LOCK TABLES `eproduct` WRITE;
/*!40000 ALTER TABLE `eproduct` DISABLE KEYS */;
INSERT INTO `eproduct` VALUES (1,'HP Laptop
ABC',21900.00,'2019-06-04 07:18:57','2 Gb HDD','AMD Phenom','4
Gb'),(2,'Acer Laptop ABC',23300.00,'2019-06-04 07:19:07','500 Gb
HDD','Core-i7','4 Gb'),(3,'Lenovo Laptop ABC',33322.00,'2019-06-04
07:19:19','1 Tb HDD','Core-i7','8 Gb');
/*!40000 ALTER TABLE `eproduct` ENABLE KEYS */;
UNLOCK TABLES;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET
FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
/*!40101 SET
CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT
*/;
/*!40101 SET
CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESUL
TS */;
/*!40101 SET
COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION

```

```
*/;  
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;
```

```
-- Dump completed on 2019-06-07 10:05:19
```

```
//Creating a class EProduct
```

```
package com.ecommerce;
```

```
import java.math.BigDecimal;  
import java.util.Collection;  
import java.util.Date;  
import java.util.List;  
import java.util.Set;  
import java.util.Map;
```

```
public class EProduct {  
    private long ID;  
    private String name;  
    private BigDecimal price;  
    private Date dateAdded;  
    private ProductParts parts;  
  
    public EProduct() {  
  
    }  
  
    public long getID() {return this.ID; }  
    public String getName() { return this.name;}  
    public BigDecimal getPrice() { return this.price;}  
    public Date getDateAdded() { return this.dateAdded;}  
    public ProductParts getParts() { return this.parts;}  
  
    public void setID(long id) { this.ID = id;}
```

```
public void setName(String name) { this.name = name;}
public void setPrice(BigDecimal price) { this.price = price;}
public void setDateAdded(Date date) { this.dateAdded = date;}
public void setParts(ProductParts parts) { this.parts = parts;}
}
```

//Creating a class ProductParts  
package com.ecommerce;

```
public class ProductParts {

    private String hdd;
    private String cpu;
    private String ram;

    public String getHdd() { return this.hdd;}
    public String getCpu() { return this.cpu;}
    public String getRam() { return this.ram;}

    public void setHdd(String value) { this.hdd= value;}
    public void setCpu(String value) { this.cpu= value;}
    public void setRam(String value) { this.ram= value;}

}
```

//Creating a HibernateUtil class to initiate Hibernate in code  
package com.ecommerce;

```

import org.hibernate.SessionFactory;
import org.hibernate.boot.Metadata;
import org.hibernate.boot.MetadataSources;
import org.hibernate.boot.registry.StandardServiceRegistry;
import org.hibernate.boot.registry.StandardServiceRegistryBuilder;

public class HibernateUtil {

    private static final SessionFactory sessionFactory;

    static {
        try {
            StandardServiceRegistry standardRegistry = new
StandardServiceRegistryBuilder()
                .configure("hibernate.cfg.xml").build();
            Metadata metaData = new
MetadataSources(standardRegistry).getMetadataBuilder().build();
            sessionFactory =
metaData.getSessionFactoryBuilder().build();
        } catch (Throwable th) {
            throw new ExceptionInInitializerError(th);
        }
    }

    public static SessionFactory getSessionFactory() {
        return sessionFactory;
    }
}

```

//Creating a hibernate table configuration file EProduct.hbm.xml

```
<?xml version="1.0"?>
```

```

<!DOCTYPE hibernate-mapping PUBLIC
"-//Hibernate/Hibernate Mapping DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">
<hibernate-mapping package="com.ecommerce">
    <class name="EProduct" table="eproduct">
        <id name="ID" type="long" column="ID">
            <generator class="identity"/>
        </id>
        <property name="name" type="string" column="NAME"/>
        <property name="price" type="big_decimal" column="PRICE"/>
        <property name="dateAdded" type="timestamp"
column="DATE_ADDED"/>

        <component name="parts"
class="com.ecommerce.ProductParts">
            <property name="hdd" column="parts_hdd"
type="string" />
            <property name="cpu" column="parts_cpu"
type="string" />
            <property name="ram" column="parts_ram"
type="string" />
        </component>
    </class>
</hibernate-mapping>

```

//Configuring Hibernate with hibernate.cfg.xml

```

<?xml version='1.0' encoding='utf-8'?>
<!DOCTYPE hibernate-configuration PUBLIC
"-//Hibernate/Hibernate Configuration DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-configuration-3.0.dtd">
<hibernate-configuration>
    <session-factory>

```

```

    <!-- Database connection settings -->
    <property name="connection.driver_class">
com.mysql.jdbc.Driver</property>
    <property name="connection.url">
jdbc:mysql://localhost:3306/ecommerce</property>
    <property name="connection.username">root</property>
    <property name="connection.password">master</property>
    <mapping resource="com/ecommerce/EProduct.hbm.xml"/>
</session-factory>
</hibernate-configuration>

```

//Creating an HTML page index.html

```

<!DOCTYPE html>
<html>
<head>
<meta charset="UTF-8">
<title>Hibernate Component Mapping</title>
</head>
<body>
<a href="details">Product Details</a><br>

</body>
</html>

```

//Creating a ProductDetails servlet

```

import java.io.IOException;
import java.io.PrintWriter;

```

```
import javax.servlet.ServletConfig;
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.transaction.*;
import javax.xml.bind.*;
```

```
import java.io.Serializable;
import java.math.BigDecimal;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.Collection;
import java.util.List;
import java.util.Map;
import java.util.Set;
```

```
import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;
import org.hibernate.cfg.Configuration;
import com.ecommerce.EProduct;
import com.ecommerce.HibernateUtil;
import com.ecommerce.ProductParts;
```

```
/**
 * Servlet implementation class ProductDetails
 */
@WebServlet("/ProductDetails")
public class ProductDetails extends HttpServlet {
    private static final long serialVersionUID = 1L;
```

```
/**
```



```

* @see HttpServlet#HttpServlet()
*/
    public ProductDetails() {
        super();
        // TODO Auto-generated constructor stub
    }

    /**
     * @see HttpServlet#doGet(HttpServletRequest request,
    HttpServletResponse response)
     */
    protected void doGet(HttpServletRequest request,
    HttpServletResponse response) throws ServletException,
    IOException {
        // TODO Auto-generated method stub
        try {
            SessionFactory factory =
    HibernateUtil.getSessionFactory();

            Session session = factory.openSession();

            List<EProduct> list = session.createQuery("from
    EProduct").list();

            PrintWriter out = response.getWriter();
            out.println("<html><body>");

            out.println("<b>Component Mapping</b><br>");
            for(EProduct p: list) {
                out.println("ID: " + String.valueOf(p.getID()) + ",
    Name: " + p.getName() +
                                ", Price: " +
    String.valueOf(p.getPrice()) + ", Date Added: " +
    p.getDateAdded().toString());
                ProductParts parts = p.getParts();
                out.println("Parts =" + parts.getCpu() + ", " +

```

```

        parts.getHdd() + ", " + parts.getRam());
        out.println("<hr>");
    }

    session.close();

    out.println("</body></html>");

    } catch (Exception ex) {
        throw ex;
    }

}

/**
 * @see HttpServlet#doPost(HttpServletRequest request,
 *                               HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request,
                        HttpServletResponse response) throws ServletException,
                        IOException {
    // TODO Auto-generated method stub
    doGet(request, response);
}
}

```

```

//Configuring web.xml
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://xmlns.jcp.org/xml/ns/javaee"
xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee

```

[http://xmlns.jcp.org/xml/ns/javaee/web-app\\_4\\_0.xsd](http://xmlns.jcp.org/xml/ns/javaee/web-app_4_0.xsd)"

id="WebApp\_ID" version="4.0">

<display-name>HibernateComponentMapping</display-name>

<welcome-file-list>

<welcome-file>index.html</welcome-file>

<welcome-file>index.htm</welcome-file>

<welcome-file>index.jsp</welcome-file>

<welcome-file>default.html</welcome-file>

<welcome-file>default.htm</welcome-file>

<welcome-file>default.jsp</welcome-file>

</welcome-file-list>

<servlet>

<servlet-name>ProductDetails</servlet-name>

<servlet-class>ProductDetails</servlet-class>

</servlet>

<servlet-mapping>

<servlet-name>ProductDetails</servlet-name>

<url-pattern>/details</url-pattern>

</servlet-mapping>

</web-app>

