

Lecture 24: 1 July, 2021

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Data Mining and Machine Learning
April–July 2021

- Traditional IR
 - Books published after editing, review — trustworthy content

Information retrieval on the Internet

- Traditional IR

- Books published after editing, review — trustworthy content

- IR for Internet

- Internet documents are self-published, unverified
 - Economic incentive to boost rankings through fraudulent means
 - Ranking algorithms should try not to be fooled

Information retrieval on the Internet

- Traditional IR
 - Books published after editing, review — trustworthy content
- IR for Internet
 - Internet documents are self-published, unverified
 - Economic incentive to boost rankings through fraudulent means
 - Ranking algorithms should try not to be fooled
- Easy to add invisible content in HTML to misdirect search
 - Merging text and background colour, overlay text with images, unreadable font size

Information retrieval on the Internet

- Traditional IR
 - Books published after editing, review — trustworthy content
- IR for Internet
 - Internet documents are self-published, unverified
 - Economic incentive to boost rankings through fraudulent means
 - Ranking algorithms should try not to be fooled
- Easy to add invisible content in HTML to misdirect search
 - Merging text and background colour, overlay text with images, unreadable font size
- Self published documents may omit useful search terms
 - IBM webpage did not mention the word “computer”

Exploiting hypertext

- Hypertext links refer from one document to another
 - ` CMI webpage `
 - Target location : `https://www.cmi.ac.in`
 - Anchor text : `CMI webpage`

Exploiting hypertext

- Hypertext links refer from one document to another
 - ` CMI webpage `
 - Target location : `https://www.cmi.ac.in`
 - Anchor text : `CMI webpage`
- Use anchor text to index document at target location
 - Reliable indicator of what target document is about

Exploiting hypertext

- Hypertext links refer from one document to another
 - ` CMI webpage `
 - Target location : `https://www.cmi.ac.in`
 - Anchor text : `CMI webpage`
- Use anchor text to index document at target location
 - Reliable indicator of what target document is about
- Hyperlinks also connect internet documents as a directed graph
 - Reason about the World Wide Web (WWW) as a gigantic graph
 - Use techniques from **social network analysis**

Social network analysis — prestige

- Consider the film industry
 - When is an actor a star? When is a director famous?

Social network analysis — prestige

- Consider the film industry
 - When is an actor a star? When is a director famous?
 - Stars are sought out by famous directors
 - Famous directors get stars to work in their films

Social network analysis — prestige

- Consider the film industry
 - When is an actor a star? When is a director famous?
 - Stars are sought out by famous directors
 - Famous directors get stars to work in their films
 - Recursive definition

Social network analysis — prestige

- Consider the film industry
 - When is an actor a star? When is a director famous?
 - Stars are sought out by famous directors
 - Famous directors get stars to work in their films
 - Recursive definition
- Network (graph) of actors and directors, matrix M

$a \rightarrow d$

$$\begin{array}{c} \text{Directors} \\ j \\ \vdots \\ \text{Actors } i \left[\begin{array}{cc} \dots & 1 \end{array} \right] \end{array}$$

$M[i,j] = 1$ if Actor i works in a film directed by Director j

Social network analysis — prestige

- Each actor i has star value $S[i]$

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$
- Actors derive star value from the famous directors they work with

$$S[i] = \sum_j \underline{M[i,j]} \cdot \underline{F[j]}, \text{ or } \underline{S = M \cdot F}$$



Matrix mult

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$
- Actors derive star value from the famous directors they work with


$$S[i] = \sum_j M[\underline{i}, \underline{j}] \cdot \underline{F[j]}, \text{ or } S = M \cdot F$$

- Directors derive fame from the stars who work with them

$$F[j] = \sum_i M[\underline{i}, \underline{j}] \cdot \underline{S[i]}, \text{ or } F = \underline{M^T} \cdot S$$

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$
- Actors derive star value from the famous directors they work with

$$S[i] = \sum_j M[i,j] \cdot F[j], \text{ or } S = M \cdot F$$


- Directors derive fame from the stars who work with them

$$F[j] = \sum_i M[i,j] \cdot S[i], \text{ or } \underline{F} = M^T \cdot S$$

- Substituting F from second equation, $S = M \cdot M^T \cdot S$

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$
- Actors derive star value from the famous directors they work with

$$S[i] = \sum_j M[i,j] \cdot F[j], \text{ or } S = M \cdot F$$

- Directors derive fame from the stars who work with them

$$F[j] = \sum_i M[i,j] \cdot S[i], \text{ or } F = M^T \cdot S$$

- Substituting F from second equation, $S = M \cdot M^T \cdot S$
- Substituting S from first equation, $F = M^T \cdot M \cdot F$

Social network analysis — prestige

- Each actor i has star value $S[i]$
- Each director j has fame $F[j]$
- Actors derive star value from the famous directors they work with

$$S[i] = \sum_j M[i,j] \cdot F[j], \text{ or } S = M \cdot F$$

- Directors derive fame from the stars who work with them

$$F[j] = \sum_i M[i,j] \cdot S[i], \text{ or } F = M^T \cdot S$$

- Substituting F from second equation, $S = M \cdot M^T \cdot S$
- Substituting S from first equation, $F = M^T \cdot M \cdot F$
- Solve for S , F to compute star ratings, fame

Prestige for webpages

- Each document i has prestige $P[i]$

Prestige for webpages

- Each document i has prestige $P[i]$
- Prestigious (reliable) documents confer prestige on documents they link to
 - $P[i]$ is shared equally among all outgoing links

Prestige for webpages

- Each document i has prestige $P[i]$
- Prestigious (reliable) documents confer prestige on documents they link to
 - $P[i]$ is shared equally among all outgoing links
- A document derives prestige from documents that link to it
 - $P[i]$ is sum of prestige transferred by incoming links

Prestige for webpages

- Each document i has prestige $P[i]$
- Prestigious (reliable) documents confer prestige on documents they link to
 - $P[i]$ is shared equally among all outgoing links
- A document derives prestige from documents that link to it
 - $P[i]$ is sum of prestige transferred by incoming links
- Structure of the internet, adjacency matrix A

$$\begin{array}{c} \text{Webpages} \\ j \\ \vdots \\ \text{Webpages } i \left[\begin{array}{c} \dots \\ 1 \end{array} \right] \end{array}$$

$A[i, j] = 1$ if webpage i has a link to webpage j

Prestige for webpages ...

■ Suppose $A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$



Prestige for webpages ...

■ Suppose $A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$

■ Each document initially has prestige 1, $P = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$

Prestige for webpages ...

- Suppose $A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$ de $\langle a \ href = \underline{\underline{"d3"}} \rangle \dots \langle \rangle$

- Each document initially has prestige 1, $P = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$

- If a webpage points to n other pages, each of them gets 1/n of $P[i]$

Prestige for webpages ...

- Suppose $A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$

- Each document initially has prestige 1, $P = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$

- If a webpage points to n other pages, each of them gets $1/n$ of $P[i]$

- Prestige transfer matrix, $A^* = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$

Prestige for webpages ...

■ Suppose $A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$

■ Each document initially has prestige 1, $P = \begin{bmatrix} 1 \\ 1 \\ 1 \end{bmatrix}$

■ If a webpage points to n other pages, each of them gets $1/n$ of $P[i]$

■ Prestige transfer matrix, $A^* = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$

■ One step: $P^T A^* = \begin{bmatrix} 1 & 1 & 1 \end{bmatrix} \cdot \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 1.5 & 1 & 0.5 \end{bmatrix}$

Page rank

- Stable solution: $P^T \cdot A^* = P^T$

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i
 - Larry Page, co-founder of Google with Sergey Brin

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i
 - Larry Page, co-founder of Google with Sergey Brin
- How do we compute P^T ?

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i
 - Larry Page, co-founder of Google with Sergey Brin
- How do we compute P^T ?
- A^* is a stochastic matrix — each row sums to 1

$$\forall i \sum_j A^*[i,j] = 1$$

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i
 - Larry Page, co-founder of Google with Sergey Brin
- How do we compute P^T ?
- A^* is a stochastic matrix — each row sums to 1

$$\forall i \sum_j A^*[i,j] = 1$$

- Interpret $A^*[i,j]$ as probability of moving from document i to document j — random web surfer

Page rank

- Stable solution: $P^T \cdot A^* = P^T$
- $P[i]$ is Page rank of webpage i
 - Larry Page, co-founder of Google with Sergey Brin
- How do we compute P^T ?
- A^* is a stochastic matrix — each row sums to 1

$$\forall i \sum_j A^*[i,j] = 1$$

- Interpret $A^*[i,j]$ as probability of moving from document i to document j — random web surfer
- Use theory of Markov chains

Markov chains

- Finite set of states, with transition probabilities between states

Markov chains

- Finite set of states, with transition probabilities between states
- For us, states are documents
 - Henceforth, write A^* as A for convenience

Markov chains

- Finite set of states, with transition probabilities between states
- For us, states are documents
 - Henceforth, write A^* as A for convenience


$$A = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$$

Markov chains

- Finite set of states, with transition probabilities between states
- For us, states are documents
 - Henceforth, write A^* as A for convenience

$$A = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$$

Three
state
Markov
chain




Markov chains

- Finite set of states, with transition probabilities between states
- For us, states are documents
 - Henceforth, write A^* as A for convenience

$$A = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$$

Three
state
Markov
chain




- $P[j]$ is probability of being in document j

Markov chains

- Finite set of states, with transition probabilities between states
- For us, states are documents
 - Henceforth, write A^* as A for convenience

$$A = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix}$$

Three
state
Markov
chain



- $P[j]$ is probability of being in document j
- Start in document 1, so initially $P = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix}$


Markov chains ...

■ After one step: $P^T A = \begin{bmatrix} 1 & 0 & 0 \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix}$

Markov chains ...

■ After one step: $P^T A = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix}$

■ After second step: $\begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} \frac{3}{4} & \frac{1}{4} & 0 \end{bmatrix}$



Markov chains ...

- After one step: $P^{\top}A = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix}$
- After second step: $\begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} \frac{3}{4} & \frac{1}{4} & 0 \end{bmatrix}$
- After k steps, $P[j]$ is probability of being in state j

Markov chains ...

- After one step: $P^T A = \begin{bmatrix} 1 & \underline{0} & 0 \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix}$

- After second step: $\begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} \frac{3}{4} & \frac{1}{4} & \underline{0} \end{bmatrix}$

- After k steps, $P[j]$ is probability of being in state j

- Continuing our example,

$$\begin{bmatrix} \frac{3}{4} & \frac{1}{4} & 0 \end{bmatrix} \rightarrow \begin{bmatrix} \frac{1}{4} & \frac{3}{8} & \frac{3}{8} \end{bmatrix} \rightarrow \begin{bmatrix} \frac{9}{16} & \frac{5}{16} & \frac{1}{8} \end{bmatrix}$$

Markov chains ...

- After one step: $P^T A = \begin{bmatrix} 1 & 0 & 0 \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix}$

- After second step: $\begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \end{bmatrix} \begin{bmatrix} 0 & \frac{1}{2} & \frac{1}{2} \\ 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \end{bmatrix} = \begin{bmatrix} \frac{3}{4} & \frac{1}{4} & 0 \end{bmatrix}$

- After k steps, $P[j]$ is probability of being in state j

- Continuing our example,

$$\begin{bmatrix} \frac{3}{4} & \frac{1}{4} & 0 \end{bmatrix} \rightarrow \begin{bmatrix} \frac{1}{4} & \frac{3}{8} & \frac{3}{8} \end{bmatrix} \rightarrow \begin{bmatrix} \frac{9}{16} & \frac{5}{16} & \frac{1}{8} \end{bmatrix}$$

- Is it the case that $P[j] > 0$ for all j continuously, after some point?

Ergodicity

- Markov chain A is **ergodic** if there is some t_0 such that for every \underline{P} , for all $\underline{t} > t_0$, for every j , $(\underline{P}^T \underline{A}^t)[j] > 0$.
 - No matter where we start, after $t > t_0$ steps, every state has a nonzero probability of being visited in step t

$$\cancel{P} \left((P^T A) A \right) A$$

$$\downarrow$$
$$1 \text{ step} \Rightarrow P_1$$

$$P, A^{\cancel{T}} \rightarrow P_2$$

Ergodicity

- Markov chain A is **ergodic** if there is some t_0 such that for every P , for all $t > t_0$, for every j , $(P^\top A^t)[j] > 0$.
 - No matter where we start, after $t > t_0$ steps, every state has a nonzero probability of being visited in step t
- Properties of ergodic Markov chains
 - There is a stationary distribution π such that $\pi^\top A = \pi^\top$
 - π^\top is a **left eigenvector** of A

$$P^\top A = P^\top$$

Ergodicity

- Markov chain A is **ergodic** if there is some t_0 such that for every P , for all $t > t_0$, for every j , $(P^\top A^t)[j] > 0$.
 - No matter where we start, after $t > t_0$ steps, every state has a nonzero probability of being visited in step t
- Properties of ergodic Markov chains
 - There is a stationary distribution π such that $\pi^\top A = \pi^\top$
 - π^\top is a **left eigenvector** of A
 - For any starting distribution P , $\lim_{t \rightarrow \infty} P^\top A^t = \pi^\top$

- How can ergodicity fail?

- How can ergodicity fail?
 - Starting from i , we reach a set of states from which there is no path back to i

- How can ergodicity fail?
 - Starting from i , we reach a set of states from which there is no path back to i
 - We have a cycle $i \rightarrow j \rightarrow k \rightarrow i \rightarrow j \rightarrow k \dots$, so we can only visit some states periodically

Ergodicity ...

- How can ergodicity fail?
 - Starting from i , we reach a set of states from which there is no path back to i
 - We have a cycle $i \rightarrow j \rightarrow k \rightarrow i \rightarrow j \rightarrow k \dots$, so we can only visit some states periodically
- Sufficient conditions for ergodicity
 - **Irreducibility**: When viewed as a directed graph, A is strongly connected
 - For all states i, j , there is a path from i to j and a path from j to i

Ergodicity ...

- How can ergodicity fail?
 - Starting from i , we reach a set of states from which there is no path back to i
 - We have a cycle $i \rightarrow j \rightarrow k \rightarrow i \rightarrow j \rightarrow k \dots$, so we can only visit some states periodically
- Sufficient conditions for ergodicity
 - **Irreducibility**: When viewed as a directed graph, A is strongly connected
 - For all states i, j , there is a path from i to j and a path from j to i
 - **Aperiodicity**: For any pair of vertices i, j , the gcd of the lengths of all paths from i to j is 1
 - In particular, paths (loops) from i to i do not all have lengths that are multiples of some $k \geq 2$
 - Prevents bad cycles

Making the web graph ergodic

- No reason why web graph is irreducible and aperiodic
- Web graph has dead ends — terminal documents, no outgoing links

Making the web graph ergodic

- No reason why web graph is irreducible and aperiodic
- Web graph has dead ends — terminal documents, no outgoing links
- Solution: Add random jumps between documents — **teleportation**
- Teleportation matrix T : For all i, j , $T[i, j] = 1/N$, where N is the total number of documents
 - The random surfer ignores all the links in the current document and types a new URL

Making the web graph ergodic

- No reason why web graph is irreducible and aperiodic
- Web graph has dead ends — terminal documents, no outgoing links
- Solution: Add random jumps between documents — **teleportation**
- Teleportation matrix T : For all i, j , $T[i, j] = \underline{1/N}$, where N is the total number of documents
 - The random surfer ignores all the links in the current document and types a new URL
- Let α be the probability of teleportation: $M = \alpha T + (1 - \alpha) A$
 - Check that M is stochastic

Making the web graph ergodic

- No reason why web graph is irreducible and aperiodic
- Web graph has dead ends — terminal documents, no outgoing links
- Solution: Add random jumps between documents — **teleportation**
- Teleportation matrix T : For all i, j , $T[i, j] = 1/N$, where N is the total number of documents
 - The random surfer ignores all the links in the current document and types a new URL
- Let α be the probability of teleportation: $M = \alpha T + (1 - \alpha)A$
 - Check that M is stochastic
- By construction,
 - M is strongly connected — direct edge between each pair of documents
 - M is aperiodic — paths of any length exist between i and j
 - M has no dead ends

Page Rank

- In the modified web graph, stationary distribution is the Page rank, $\pi^T M = \pi^T$

Page Rank

- In the modified web graph, stationary distribution is the Page rank, $\pi^T M = \pi^T$
- Compute using $\lim_{t \rightarrow \infty} P^T M^t$

Page Rank

- In the modified web graph, stationary distribution is the Page rank, $\pi^T M = \pi^T$
- Compute using $\lim_{t \rightarrow \infty} P^T M^t$
- Use recursive doubling to accelerate computation of $\lim_{t \rightarrow \infty} P^T M^t$
 - Compute $M, M^2, (M^2)^2 = M^4, \dots, (M^{2^i})^2 = M^{4i}, \dots$
 - Set a threshold for progress to stop the process

$$x^y \quad x \cdot x \cdot \dots \cdot x \quad y \text{ times} \quad x \quad (x^2)^2 \quad (x^4)^2 \quad x^8$$

Page Rank

- In the modified web graph, stationary distribution is the Page rank, $\pi^T M = \pi^T$
- Compute using $\lim_{t \rightarrow \infty} P^T M^t$
- Use recursive doubling to accelerate computation of $\lim_{t \rightarrow \infty} P^T M^t$
 - Compute $M, M^2, (M^2)^2 = M^4, \dots, (M^{2^i})^2 = M^{4^i}, \dots$
 - Set a threshold for progress to stop the process
- Some limitations of Page rank
 - Universal property of a webpage, independent of a query
 - Define a topic-sensitive page rank

The Pianist

Page Rank

- In the modified web graph, stationary distribution is the Page rank, $\pi^T M = \pi^T$
- Compute using $\lim_{t \rightarrow \infty} P^T M^t$
- Use recursive doubling to accelerate computation of $\lim_{t \rightarrow \infty} P^T M^t$
 - Compute $M, M^2, (M^2)^2 = M^4, \dots, (M^{2^i})^2 = M^{4^i}, \dots$
 - Set a threshold for progress to stop the process
- Some limitations of Page rank
 - Universal property of a webpage, independent of a query
 - Define a topic-sensitive page rank
- Page rank was one the keys to the initial success of Google
 - Constant tweaks to ranking algorithm to keep ahead of **search engine optimizers (SEO)**