

Lecture 15: 27 May, 2021


Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Data Mining and Machine Learning
April–July 2021


Outliers and density

- An outlier is less dense than its nearest neighbours
- But difference in density may be local
- A distance metric to eliminate o_2 could make all of C_1 outliers
- C_1 has 400 points, C_2 has 100 points
- Larger distance would make all of C_2 outliers with respect to C_1



Outliers and density

- For clustering, we defined a radius Eps and looked for $MinPts$ neighbours within that ball
- Instead, fix $MinPts$ and find smallest ball with that many neighbours
- Compare $radius(p)$ with radius of its neighbours
- A is an outlier because its radius is much more than that of its neighbours




Outliers and density

- Local outlier factor $LOF(p)$


$$\frac{\text{Mean radius of } MinPts\text{-neighbours}(p)}{radius(p)}$$

- The smaller this ratio, the more likely that p is an outlier
- Comparison is local to neighbourhood, so this can deal with different densities across range of data



Semi-supervised learning

- Labelling training data is a bottleneck of supervised learning
- Handwritten digits 0,1,...,9
 - 1797 images
- Standard logistic regression model has 96.9% accuracy
- Suppose we take 50 random samples as training set
- Logistic regression gives 83.3%



Semi-supervised learning

- Instead of 50 random samples, 50 clusters using K means
- Use image nearest to each centroid as training set
 - 50 *representative images*
- Logistic regression accuracy jumps to 92.2%



Semi-supervised learning

- Propagate representative image label to entire cluster
- Logistic regression improves to 93.3%
- Propagate representative image label to only 20% items closest to centroid
- Logistic regression improves to 94%
- Only 50 actual labels used, about 5 per class!




Image segmentation

- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours



Image segmentation

- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change

10 colors



Image segmentation

- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8

8 colors



Image segmentation

- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes

6 colors



Image segmentation


- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes
- 4 colours

4 colors



Image segmentation

- An image is a matrix of pixels
- Each pixel has (R,G,B) values
- K means clustering on these values merges colours
- With 10 clusters, not much change
- Same with 8
- At 6 colours, ladybug red goes
- 4 colours
- Finally 2 colours, flower and rest



Summary

- Unsupervised learning is useful as a preprocessing step
- Semi supervised learning
 - Identify a small subset of items to label manually
 - Propagate labels via cluster
- Image segmentation
 - Highlight objects by colour

0 0 1 7 3
5 9 1 3 2
5 8 5 8 8
2 6 4 0 3
3 6 0 3 1

