

Neo4j

<https://neo4j.com/>

Introduction : Graph Database


- A database with an explicit graph structure
- with nodes, edges, and properties to represent and store data
- Each node knows its adjacent nodes
- Thus provides index-free adjacency
- Graph databases are schemaless
- ***Native / built-in*** support to represent relationships
- ACID-compliant transactional DB
- Accessible from Java API , the ***Cypher query language***

What is a Graph?

- An abstract representation of a set of objects where some pairs are connected by links.



Object (Vertex, Node)



Link (Edge, Arc, Relationship)

Graph Database

Data Model :

- Nodes and
- Relationships

Graph DB vs Relational DB


Graph

1. Graphs
2. Nodes
3. Properties & its Values
4. Relationships
5. Traversal


Relational

1. Tables
2. Rows
3. Columns & Data
4. Constraints
5. Joins


Relational Databases



Graph Databases



Graph Database






Mapping

- Each entity table is represented by a label on nodes
- Each row in a entity table is a node
- Columns on those tables become node properties.
- Join tables are transformed into relationships, columns on those tables become relationship properties


Node in Neo4j : Fundamental unit

contains properties with key-value pairs






Relationships in Neo4j

- Relationships between nodes are a key part of Neo4j.



Relationships in Neo4j




Properties

- Both nodes and relationships can have properties.
- Properties are key-value pairs where the key is a string.
- Property values can be either a primitive or an array of one primitive type.
- For example String, int and int[] values are valid for properties.


Supported data type in Neo4j

- **Number**, an abstract type, which has the subtypes **Integer** and **Float**
- **String**
- **Boolean**
- The spatial type **Point**
- Temporal types: **Date**, **Time**, **LocalTime**, **DateTime**, **LocalDateTime** and **Duration**

Example





Example



Paths in Neo4j – Traversing : Query

- A path is one or more nodes with connecting relationships, typically retrieved as a query or traversal result.



Powered by



mozilla

viadeo



Walmart

accenture
High performance. Delivered.



teachscape

LinkedIn

InfoJobs
EMPLOY



Google™

PayPal™



Supported platforms



REST://



When to use Graph Databases ?


- Complex data
- Densely--connected, semi--structured domains
 - Lots of join tables? Connectedness
 - Lots of sparse tables? Semi--structure
- Data Model Volatility
- Easy to evolve
- Join Complexity and Performance
- Millions of "joins" per second
- Consistent query times as dataset grows

Target applications of graphs database


- Recommendations
- Business intelligence
- Social computing
- Geospatial
- Systems management
- Web of things
- Genealogy
- Time series data
- Product catalogue
- Web analytics
- Scientific computing (especially bioinformatics)
- Indexing your *slow* RDBMS

28 And much more!

Neo4j Software Architecture



Neo4j Logical Architecture



Storage File Organization

- Neo4j stores graph data in a number of different store files.
- Each store file contains the data for a specific part of the graph e.g. **nodes, relationships, properties**

Store File Formats


Node (9 bytes)



Relationship (33 bytes)



Relationship Type (5 bytes)



Node store

- Size:9 bytes
 - **First byte**:in-use flag
 - **Next 4 bytes**:ID of first relationship
 - **Last 4 bytes**:ID of first property of node

Relationship store


- Size:33 bytes
 - **First byte**:In use flag
 - **Next 8 bytes**:IDs of the nodes at the start and end of the relationship
 - **4 bytes**:Pointer to the relationship type
 - **16 bytes**:pointers for the next and previous relationship records for each of the start and end nodes
 - **4 bytes**:next property id

Cypher Query Language (CQL)

- SQL has been the de facto language for RDBMS
- Cypher is a declarative language that serves the same purpose as SQL
- Uses ASCII-Art to represent patterns
- Nodes are surrounded with parentheses
- Use arbitrary variables to refer to nodes
Variable scope restricted to single statement
- Case Sensitive – standard naming convention
- <https://neo4j.com/docs/developer-manual/current/cypher/syntax/naming/>

Cypher Query : Syntax

- Relationships are specified using an arrow (- ->) between nodes
- Square bracket inside arrow for specification
 - Relationships - 1 type
 - Nodes - 0 or more labels
- Cypher allows patterns to be assigned to variables that increase modularity and reduce repetition



Cypher Query Clauses

- Minimum/simplest query consist of a **MATCH** clause followed by a **RETURN** clause.

```
MATCH (a:Person {name:'Jim'}) -[:KNOWS]->(b) -[:KNOWS]->(c), (a) -[:KNOWS]->(c)

RETURN b, c
```

- **WHERE** : Provides criteria for filtering pattern matching results.
- **CREATE** and **CREATE UNIQUE** : Create nodes and relationships.
- **MERGE** : Ensures that the supplied pattern exists in the graph, either by reusing existing nodes and relationships that match the supplied predicates, or by creating new nodes and relationships

Cypher Query Clauses ...

- **DELETE/REMOVE** : Removes nodes, relationships, and properties.
- **SET** : Sets property values and labels
- **ORDER BY** : Sorts results as part of a **RETURN**
- **SKIP LIMIT** : Skip results at the top and limit the number of results
- **FOREACH** : Performs an updating action for each element in a list.
- **UNION** : Merges results from two or more queries.
- **WITH** : Chains subsequent query parts and forwards results from one to the next. Similar to piping commands in Unix.
- For more detail <https://neo4j.com/docs/cypher-refcard/current/?ref=beginners-ebook>

Getting started

- Multiple ways to start
 - Neo4j Sandboxes (cloud containers)
 - VMs (VirtualBox - Windows & Mac)
 - VMs (Linux - VirtualBox or KVM)
 - **Desktop installation**
 - **Server – single instance**
 - **Clustering** – Enterprise

Neo4j Database Server Installation on Windows Machine

- Pre-requisite : JDK 8.0
- Visit the Neo4j official site using <https://neo4j.com/try-neo4j/>
- Download Neo4J Community Server Edition
- Download setup/run or **zip file/extract**
- Place the extracted files in a permanent home on your server, for example **D:\neo4j**. The top level directory is referred to as **NEO4J_HOME**.


Installation ...

- To run Neo4j as a console application, use:
<NEO4J_HOME>\bin\neo4j console
- To install Neo4j as a service use:
<NEO4J_HOME>\bin\neo4j install-service
- Start Neo4J browser : **<http://localhost:7474>**
- Connect using the username '**neo4j**' with default password '**neo4j**'. You'll then be prompted to change the password.
- **\$:play movie graph**
- **\$:play northwind graph**

Neo4j Data Browser

- Open using URL

<http://localhost:7474/browser/>



Remote Access to Data Browser

- Open the `neo4j.conf` file in an editor
- Add following entries in **HTTP Connector** section
- **dbms.connector.http.type=HTTP**
- **dbms.connector.http.enabled=true**
- **dbms.connector.http.address=0.0.0.0:7474**
- Instead of **0.0.0.0** , put here actual IP
- E.g. 10.10.7.101
- **dbms.connector.http.address=10.10.7.101:7474**

Application Developments

- Connecting through programming languages
- Neo4j officially supported drivers
 - Java
 - Javascript
 - **C#**
 - **Python**

Neo4j for C#.NET Developers

- PM> Install-Package **Neo4j.Driver-4.2.0**
- Neo4j Community Drivers
- **Neo4jClient** : A .NET client for Neo4j, which makes it easy to write Cypher queries in C# with IntelliSense
- GitHub Link :
<https://github.com/DotNet4Neo4j/neo4jclient>

Neo4j Python Driver

- Find out / download the latest version of the driver at <https://pypi.python.org/pypi/neo4j-driver>
- Or Install the latest version of the driver if you are online :

pip install neo4j