GE23131-Programming Using C-2025

Status	Finished
Started	Tuesday, 21 October 2025, 7:25 PM
Completed	Tuesday, 21 October 2025, 7:49 PM
Duration	23 mins 54 secs

Question **1**
Correct
Mark 10.00 out of 10.00
Flag question

Question 1

Write a program to print the sum of the first three terms separated by a space.

The second line will contain N.

Input Format:

The first line will contain the first three terms separated by a space.

The second line will contain N.

Output Format:

The integer value denoting the Nth term.

Example Input/Output 1:

Input:

1 2 3

5

Output:

81

Explanation:

The progression is 1, 2, 3 1+2+3=6 6+2+3=11 and so on.

The 5th term is 81.

Example Input/Output 2:

Input:

1 4 7

7

Output:

13

For example:

Input	Result
1 10 19 3	19
1 4 7 7	13

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int a,b,c;
    int n;
    scanf("%d %d %d",&a,&b,&c);
    scanf("%d",&n);
    int d = a + b + c;
    int e = b + c + (b + c) * (n-4);

    return 0;
}
```

Input	Expected	Get
1 10 19 3	19	19 ✓
1 4 7 7	13	13 ✓

Passed all tests! ✓

Question **2**
Correct
Mark 10.00 out of 10.00
Flag question

A floating point value F indicating the amount to repeat is passed as input. The program must print the corresponding value in pence.

Note: 1 **repeat** = 100 pence.

Input Format:

The first line contains F.

Output Format:

The first line contains the integer value denoting the pence.

Boundary Conditions:

0.00 <= F <= 999999.99

Example Input/Output 1:

Input:

12.30

Output:

1230

Example Input/Output 2:

Input:

0.00

Output:

0

Example Input/Output 3:

Input:

9.0

Output:

900

For example:

Input	Result
12.30 3	1230
0.00 5	0
9.0 3	900

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n;
    scanf("%d",&F);

    p=100;
    printf("%d",F*p);

    return 0;
}
```

Input	Expected	Get
12.30 3	1230	1230 ✓
0.00 5	0	0 ✓
9.0 3	900	900 ✓

Passed all tests! ✓

Question **3**
Correct
Mark 10.00 out of 10.00
Flag question

Jitin and Tim both owe a money great and they decide to meet the farm in and around the court which will meet Rem Rs.P per square feet. Jitin owns the square farm and Tim owns the farm and the width of the court. Find the difference between the length of the courts.

Input Format:

First line will contain the amount spent in Rs.P by Jitin and Tim separated by space.

Second line will contain the width in feet of the courts of Jitin and Tim separated by space.

Output Format:

The value in feet which is the difference between the length of the courts rounded off upto two decimal points.

Example Input/Output 1:

Input:

10000.00000

100 80

Output:

0.00

Explanation:

Area of Jitin's court = 10000.0 / 2000 sq.ft. Length = 2000.00 / 100

Area of Tim's court = 10000.0 / 1600 sq.ft. Length = 10000.00 / 80

Hence the difference = 200.00 - 0 which when rounded off to the nearest places is 0.00

Example Input/Output 2:

Input:

17788.40000

50 60

Output:

30.00

Explanation:

Area of Jitin's court = 17788.0 / 2500 sq.ft. Length = 2500.00 / 50

Area of Tim's court = 40000.0 / 3600 sq.ft. Length = 3600.00 / 100

Hence the difference = 2500.00 - 3600.00

Example Input/Output 3:

Input	Result
10000.00000 100 80	0.00
17788.40000 50 60	30.00

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,m,l,b,p,q,r,s;
    scanf("%d",&n);
    scanf("%d %d",&m,&l);
    scanf("%d %d",&p,&q);
    scanf("%d %d",&r,&s);
    n=l/m;
    p=r/p;
    q=s/q;
    if(p>n)
    {
        n=p-n;
    }
    if(q>n)
    {
        n=q-n;
    }
    printf("%d",n);
    return 0;
}
```

Input	Expected	Get
10000.00000 100 80	0.00	0.00 ✓
17788.40000 50 60	30.00	30.00 ✓

Passed all tests! ✓

Question **4**
Correct
Mark 10.00 out of 10.00
Flag question

In a zoo there are some birds and animals. All birds have two legs and all animals have four legs.

Given the head count and leg count of birds and animals taken together, the program must print the head count of birds and animals separated by a space as output.

Input Format:

First line will contain the integer value H representing the head count of both birds and animals taken together.

Second line will contain the integer value L representing the leg count of both birds and animals taken together.

Output Format:

First line will contain the integer values of the head count of birds and animals separated by a space.

Constraints:

0 < H < 2000

1 <= L <= 2000

Sample Input/Output:

Example 1:

Input:

27

84

Output:

12 15

Explanation:

There are 12 birds and 15 animals.

Example 2:

Input:

210

350

Output:

200 10

For example:

Input	Result
27 84	12 15
210 350	200 10

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,l;
    scanf("%d %d",&n,&l);
    int a,b;
    a=(4*n-l)/2;
    b=l/2-n;
    printf("%d %d",a,b);
    return 0;
}
```

Input	Expected	Get
27 84	12 15	12 15 ✓
210 350	200 10	200 10 ✓

Passed all tests! ✓

Question **5**
Correct
Mark 10.00 out of 10.00
Flag question

An integer value N is passed as the input. The program must reverse the sign of N and print -N as the output.

Input Format:

The first line contains N.

Output Format:

The first line contains -N.

Boundary Conditions:

-999999 <= N <= 999999

Example Input/Output 1:

Input:

125

Output:

-125

Example Input/Output 2:

Input:

-186

Output:

186

Example Input/Output 3:

Input:

0

Output:

0

For example:

Input	Result
125	-125
-186	186
0	0

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,m;
    scanf("%d",&n);
    m=-n;
    printf("%d",m);
    return 0;
}
```

Input	Expected	Get
125	-125	-125 ✓
-186	186	186 ✓
0	0	0 ✓

Passed all tests! ✓

Question **6**
Correct
Mark 10.00 out of 10.00
Flag question

The program must accept a number N and print the sum of tenth and unit digits.

Input Format:

The first line denotes the value of N.

Output Format:

The first line contains the sum of tenth and unit digits.

Boundary Conditions:

10 <= N <= 999999

Example Input/Output 1:

Input:

231

Output:

5

Example Input/Output 2:

Input:

186

Output:

9

Example Input/Output 3:

Input:

252

Output:

7

For example:

Input	Result
231	5
186	9
252	7

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,t,u,s;
    scanf("%d",&n);
    t=(n/10)%10;
    u=n%10;
    s=t+u;
    printf("%d",s);
    return 0;
}
```

Input	Expected	Get
231	5	5 ✓
186	9	9 ✓
252	7	7 ✓

Passed all tests! ✓