GE23131-Programming Using C-2025

Question **1**
Correct
Marks : 10.00
Flag question
Edit question

Status : Finished
Started : Tuesday, 21 October 2025, 10:10 PM
Completed : Wednesday, 22 October 2025, 12:43 AM
Duration : 1 hour, 29 minutes

Given a list of numbers where all other numbers are multiples of the smallest number, the program must find the count of the common factors of everything 1.

Input Format:

First line will contain the integer value of representing how many numbers are present in input.
Next N lines will have the numbers.

Output Format:

First line will contain the count of common factors 1.

Constraints:

N will be from 2 to 50.

Sample Input/Output:

Example 1:

Input:

```
3
2
4
6
```

Output:

```
2
```

Explanation:

The common factors are 1 and 2 as 2 is common factor of 2& 4 6.

Example 2:

Input:

```
4
2
3
5
7
```

Output:

```
1
```

Explanation:

The common factors are 1 and 3 as 3 is common factor of 3& 9 6.

For example:

Input	Result
3 2 4 6	2
4 2 3 5 7	1

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,smallest=0,count=0,i,j;
    scanf("%d",&n);
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
3 2 4 6	2	2
4 2 3 5 7	1	1

Passed all tests! ✓

Question **2**
Correct
Marks : 10.00
Flag question
Edit question

Given a list of numbers where all other numbers are multiple of the smallest number, the program must find the count of the common factors 0 excluding 1.

Input Format:

First line will contain the integer value of representing how many numbers are present in input.
Next N lines will have the numbers.

Output Format:

First line will contain the count of common factors 0.

Constraints:

N will be from 2 to 50.

Sample Input/Output:

Example 1:

Input:

```
3
2
4
6
```

Output:

```
2
```

Explanation:

The common factors excluding 1 are 2,6. Hence output is 2.

Example 2:

Input:

```
4
2
3
5
7
```

Output:

```
0
```

Explanation:

The common factors excluding 1 are 0. Hence output is 0.

For example:

Input	Result
3 2 4 6	2
4 2 3 5 7	0

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,smallest=0,count=0,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
3 2 4 6	2	2
4 2 3 5 7	0	0

Passed all tests! ✓

Question **3**
Correct
Marks : 10.00
Flag question
Edit question

Two whole numbers N1 and N2 are passed as input. The program must print the number of primes present between N1 and N2 (the range is inclusive of N1 and N2).

Input Format:

First line will contain the value of the first number N1.
Second line will contain the value of the second number N2.

Output Format:

First line will contain the count of prime numbers between N1 and N2.

Sample Input/Output:

Example 1:

Input:

```
11
2100
```

Output:

```
6
```

Explanation:

The prime numbers within the range 11 to 2100 are 11,13,17,19,23,29.

Example 2:

Input:

```
50
70
```

Output:

```
5
```

Explanation:

The prime numbers within the range 50 to 70 are 53, 59, 61, 67, 71. Hence output is 5.

For example:

Input	Result
11 2100	6
50 70	5

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,count=0,i,j,k,l,m,n1,n2;
    scanf("%d",&n1);
    scanf("%d",&n2);
    for(i=n1;i<=n2;i++)
    {
        int*arr=(int*)malloc(n);
        int*temp=(int*)malloc(n);
        int*check=(int*)malloc(n);
        int*count1=(int*)malloc(n);
        int*count2=(int*)malloc(n);
        int*common=(int*)malloc(n);
        int*uncommon=(int*)malloc(n);
        int*temp1=(int*)malloc(n);
        int*temp2=(int*)malloc(n);
        int*uncommon1=(int*)malloc(n);
        int*uncommon2=(int*)malloc(n);
        for(int i=0;i<n;i++)
        {
            scanf("%d",&arr[i]);
            temp[i]=arr[i];
            check[i]=0;
            count1[i]=0;
            count2[i]=0;
            common[i]=0;
            uncommon[i]=0;
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
        }
        smallest=arr[0];
        for(i=1;i<n;i++)
        {
            if(arr[i]<smallest)
            {
                smallest=arr[i];
            }
        }
        for(i=0;i<n;i++)
        {
            for(j=0;j<n;j++)
            {
                if(temp[j]==arr[i])
                {
                    count1[i]=count1[i]+1;
                    temp[j]=0;
                    if(count1[i]==1)
                    {
                        common[i]=arr[i];
                        count2[i]=count2[i]+1;
                    }
                    else
                    {
                        uncommon[i]=arr[i];
                        count2[i]=count2[i]+1;
                    }
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            if(count2[i]==1)
            {
                temp1[i]=common[i];
                temp2[i]=0;
                uncommon1[i]=0;
                uncommon2[i]=0;
                count2[i]=0;
                count1[i]=0;
                common[i]=0;
                uncommon[i]=0;
                check[i]=1;
                for(j=0;j<n;j++)
                {
                    temp[j]=arr[j];
                    if(temp[j]==temp1[i])
                    {
                        temp[j]=0;
                    }
                    else
                    {
                        temp[j]=temp[j];
                    }
                }
                i=0;
                j=0;
                continue;
            }
            else
            {
                temp1[i]=0;
                temp2[i]=0;
                uncommon1[i]=0;
                uncommon2[i]=0;
                count2[i]=0;
                count1[i]=0;
                common[i]=0;
                uncommon[i]=0;
                check[i]=1;
                for(j=0;j<n;j++)
                {
                    temp[j]=arr[j];
                    if(temp[j]==temp1[i])
                    {
                        temp[j]=0;
                    }
                    else
                    {
                        temp[j]=temp[j];
                    }
                }
                i=0;
                j=0;
                continue;
            }
        }
        printf("%d",count1[i]);
        return 0;
    }
```

Input	Expected	Get
11 2100	6	6
50 70	5	5

Passed all tests! ✓

Question **4**
Correct
Marks : 10.00
Flag question
Edit question

An integer value N is passed as the input. The program must print the first N terms in the Fibonacci sequence.

Input Format:

The first line denotes the value of N.

Output Format:

The first N terms in the Fibonacci sequence (with each term separated by a space)

Boundary Conditions:

1 <= N <= 30

Example Input/Output 1:

Input:

```
5
```

Output:

```
0 1 1 2 3
```

Example Input/Output 2:

Input:

```
10
```

Output:

```
0 1 1 2 3 5 8 13 21 34
```

For example:

Input	Result
5	0 1 1 2 3
10	0 1 1 2 3 5 8 13 21 34

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,i,j,k,l,num,num1,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
5	0 1 1 2 3	0 1 1 2 3
10	0 1 1 2 3 5 8 13 21 34	0 1 1 2 3 5 8 13 21 34

Passed all tests! ✓

Question **5**
Correct
Marks : 10.00
Flag question
Edit question

The sum control by a control sum is the first and second letters of N two orders numbers are passed as input. The program must print the average of first and second digits with precision upto two decimal places.

Input Format:

The first line denotes the value of N.
The second line contains the first and second letters seprated by a space.

Output Format:

The first line contains the average of first letters.
The second line contains the average of second letters.

Boundary Conditions:

5 <= N <= 20
The value of N will be from 0 to 2000.

Example Input/Output 1:

Input:

```
5
AB 200
AN 100
AM 250
```

Output:

```
100.00
250.00
```

For example:

Input	Result
5 AB 200 AN 100 AM 250	100.00 250.00
4 AB 100 AC 200 AD 300	100.00 200.00

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,i,j,k,l,num,num1,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
5 AB 200 AN 100 AM 250	100.00 250.00	100.00 250.00
4 AB 100 AC 200 AD 300	100.00 200.00	100.00 200.00

Passed all tests! ✓

Question **6**
Correct
Marks : 10.00
Flag question
Edit question

A positive N is passed as the input. The program must print the next immediate prime number.

Input Format:

The first line will contain N.

Output Format:

The first line will contain the integer value of next immediate prime number.

Boundary Conditions:

1 <= N <= 10000

Example Input/Output 1:

Input:

```
5
```

Output:

```
7
```

Example Input/Output 2:

Input:

```
7
```

Output:

```
11
```

For example:

Input	Result
5	7
7	11

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
5	7	7
7	11	11

Passed all tests! ✓

Question **7**
Correct
Marks : 10.00
Flag question
Edit question

The prime-sum sum of second two integers X and Y and print the odd integer between them.

Input Format:

The first line denotes the value of X.
The second line denotes the value of Y.

Output Format:

The first line contains the odd integer between X and Y separated by a space.

Boundary Conditions:

100000 <= X <= 999999
X <= Y <= 999999

Example Input/Output 1:

Input:

```
5
7
```

Output:

```
5 6 7
```

Example Input/Output 2:

Input:

```
10
12
```

Output:

```
10 11 12
```

For example:

Input	Result
5 7	5 6 7
10 12	10 11 12

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
5 7	5 6 7	5 6 7
10 12	10 11 12	10 11 12

Passed all tests! ✓

Question **8**
Correct
Marks : 10.00
Flag question
Edit question

An integer value N is passed as the input. The program must print YES if N is prime number. Else the program must print NO.

Input Format:

The first line denotes the value of N.

Output Format:

YES or NO based on if N is a prime number or not. (The OUTPUT is CASE SENSITIVE).

Boundary Conditions:

1 <= N <= 999999

Example Input/Output 1:

Input:

```
10
```

Output:

```
NO
```

Example Input/Output 2:

Input:

```
11
```

Output:

```
YES
```

For example:

Input	Result
10	NO
11	YES

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n,num,
    int*arr=(int*)malloc(n);
    int*temp=(int*)malloc(n);
    int*check=(int*)malloc(n);
    int*count1=(int*)malloc(n);
    int*count2=(int*)malloc(n);
    int*common=(int*)malloc(n);
    int*uncommon=(int*)malloc(n);
    int*temp1=(int*)malloc(n);
    int*temp2=(int*)malloc(n);
    int*uncommon1=(int*)malloc(n);
    int*uncommon2=(int*)malloc(n);
    for(int i=0;i<n;i++)
    {
        scanf("%d",&arr[i]);
        temp[i]=arr[i];
        check[i]=0;
        count1[i]=0;
        count2[i]=0;
        common[i]=0;
        uncommon[i]=0;
        temp1[i]=0;
        temp2[i]=0;
        uncommon1[i]=0;
        uncommon2[i]=0;
    }
    smallest=arr[0];
    for(i=1;i<n;i++)
    {
        if(arr[i]<smallest)
        {
            smallest=arr[i];
        }
    }
    for(i=0;i<n;i++)
    {
        for(j=0;j<n;j++)
        {
            if(temp[j]==arr[i])
            {
                count1[i]=count1[i]+1;
                temp[j]=0;
                if(count1[i]==1)
                {
                    common[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
                else
                {
                    uncommon[i]=arr[i];
                    count2[i]=count2[i]+1;
                }
            }
            else
            {
                temp[j]=temp[j];
            }
        }
        if(count2[i]==1)
        {
            temp1[i]=common[i];
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
        else
        {
            temp1[i]=0;
            temp2[i]=0;
            uncommon1[i]=0;
            uncommon2[i]=0;
            count2[i]=0;
            count1[i]=0;
            common[i]=0;
            uncommon[i]=0;
            check[i]=1;
            for(j=0;j<n;j++)
            {
                temp[j]=arr[j];
                if(temp[j]==temp1[i])
                {
                    temp[j]=0;
                }
                else
                {
                    temp[j]=temp[j];
                }
            }
            i=0;
            j=0;
            continue;
        }
    }
    printf("%d",count1[i]);
    return 0;
}
```

Input	Expected	Get
10	NO	NO
11	YES	YES

Passed all tests! ✓

```
    scanf("%d",&i);

    for(int j=2;j<=i/2;j++){
        if(i<2){
            continue;
        }
        if(i%j==0){
            prime=0;
            break;
            }
    }
    if(prime){
        printf("YES");
    }else{
        printf("NO");
    }

    return 0;
}
```

	Input	Expected	Got	
✓	19	YES	YES	✓
✓	189210	NO	NO	✓

Passed all tests! ✓

Question **9**

Correct

Flag question

The program must accept N integers and print the second largest value among the N integers.

Input Format:

The first line denotes the value of N.
Next N lines will contain the N integer values.

Output Format:

The first line contains the second largest integer.

Boundary Conditions:

2 <= N <= 100
The value of the integers will be from -999999 to 999999.

Example Input/Output 1:

Input:

3
100
2200
345

Output:

345

Example Input/Output 2:

Input:

6
-23
-256
-87
-90
-11019
-2

Output:

-23

For example:

Input	Result
3 100 2200 345	345
6 -23 -256 -87 -90 -11019 -2	-23

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    signed int n,x,first=-2000000,second=-2000000;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&x);
        if(x>first){
            second=first;
            first=x;
        }else if(x<first && x>second){
            second=x;
        }
    }
    printf("%d",second);
    return 0;
}
```

	Input	Expected	Got	
✓	3 100 2200 345	345	345	✓
✓	6 -23 -256 -87 -90 -11019 -2	-23	-23	✓

Passed all tests! ✓

Finish review