

CHANGE REQUEST

23.503 CR **1388** rev **8** Current version: **19.2.0**

For **HELP** on using this form: comprehensive instructions can be found at
<http://www.3gpp.org/Change-Requests>.

Proposed change affects: UICC apps ☐ ME ☒ Radio Access Network ☐ Core Network ☒

Title:	Traffic detection and QoS handling of multiplexed data flows										
Source to WG:	OPPO, China Mobile, [Xiaomi, Lenovo, Ericsson, Huawei, HiSilicon, Samsung, Nokia, NTT DOCOMO, vivo], [vivo]										
Source to TSG:	SA2										
Work item code:	XRM_Ph2	Date:	2025-02-05								
Category:	B Use <u>one</u> of the following categories: F (correction) A (mirror corresponding to a change in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Release:	Rel-19 Use <u>one</u> of the following releases: Rel-8 (Release 8) Rel-9 (Release 9) Rel-10 (Release 10) Rel-11 (Release 11) ... Rel-17 (Release 17) Rel-18 (Release 18) Rel-19 (Release 19) Rel-20 (Release 20)								
Reason for change:	According to the Conclusions for KI#4 in TR 23.700-70, traffic detection and QoS handling of multiplexed data flows shall be supported in TS 23.503.										
Summary of change:	1) Add new clause 6.1.3.27.x to support KI#4. 2) Add handling of the UE capability for support of (S)RTP Multiplexed Media Information in IP Packet Filters provided by SMF to PCF.										
Consequences if not approved:	Traffic detection and differentiated QoS is not supported for multiplexed media flows.										
Clauses affected:	6.1.3.27.x										
Other specs affected: (show related CRs)	<table><tr><td>Y</td><td>N</td></tr><tr><td>☒</td><td>☐</td></tr><tr><td>☒</td><td>☐</td></tr><tr><td>☒</td><td>☐</td></tr></table>	Y	N	☒	☐	☒	☐	☒	☐	Other core specifications	TS/TR ... CR ...
Y	N										
☒	☐										
☒	☐										
☒	☐										
		Test specifications	TS/TR ... CR ...								
		O&M Specifications	TS/TR ... CR ...								
Other comments:											
This CR's revision history:											

* * * * First change * * * *

6.1.3.27.x Traffic identification and differentiated QoS for multiplexed media flows

Traffic identification and differentiated QoS for multiplexed media flows is as defined in clause 5.37.11 of TS 23.501 [2] and enables differentiated QoS handling for (S)RTP media flows that are multiplexed on the same end-to-end transport layer connection.

When the UE indicates the support for (S)RTP Multiplexed Media Identification Information in IP Packet Filters to SMF at PDU Session establishment, the SMF provides this UE capability information to PCF.

In order to request differentiated QoS for multiplexed media flows from the PCF, the AF has to provide per media flow the (S)RTP Multiplexed Media Identification Information (see TS 23.501 [2] clause 5.7.6.2) in the Flow Description and the specific QoS requirements (described in clause 6.1.3.22).

The PCF determines the PCC Rules and QoS parameters for the **multiplexed (S)RTP** media flows as follows:

- When the AF request includes uplink direction and the UE capability information indicates support for (S)RTP Multiplexed Media Identification Information in IP Packet Filters, or the AF request is for the downlink direction only, the PCF generates a separate PCC rule for every media flow in the same way it is described in clause 6.1.3.22. Each PCC Rule includes the QoS parameters of the corresponding media flow and it's (S)RTP Multiplexed Media Identification Information in the IP Packet Filter set.
- When the AF request includes media flows with an uplink direction and the UE has not indicated support for (S)RTP Multiplexed Media Identification Information in IP Packet Filters, the PCF generates separate PCC rules for the downlink direction of the media flows as described by the previous bullet. For the uplink direction of the media flows, the PCF generates PCC rules based on operator configuration and **notifies** the AF that the differentiated QoS handling for multiplexed media flows cannot be fulfilled **for the uplink direction**. As an alternative, the PCF may reject the AF request indicating lack of UE support for (S)RTP Multiplexed Media Identification.

NOTE Y: It is assumed the PSA UPF supports the IP Packet Filter with (S)RTP Multiplexed Media Identification Information.

* * * * End of changes * * * *