

Prajwal Gupta

RA1911003010660

AI LAB-9

Aim- Implementation of UNCERTAIN METHODS – DEMPSTER SHAFER THEORY

* Problem formulation → To solve inference problem representing uncertain methods to obtain a belief function. Using the mass function, which has built-in combination rules obtain the Dempster rule of combination.

Initial state	Final state
$m_1: \{ 'a': 0.4, 'b': 0.2, 'ab': 0.1, 'ab': 0.3 \}$	$\{ 'ac': 0.157894,$
$m_2: \{ 'b': 0.5, 'c': 0.2, 'ac': 0.3, 'a': 0.0 \}$	$'c': 0.105263,$
	$'b': 0.5263157$
	$'ab': 0.0, 'abc': 0.0,$
	$'a': 0.21052631 \}$

* Problem solving: The combination is calculated from the two sets of masses m_1 and m_2 in the following way:

- $m_1(\emptyset) = 0$
- $m_{12}(A) = (m_1 \oplus m_2)(A) = \frac{1}{1-K} \sum_{B \cap C = A \neq \emptyset} m_1(B) m_2(C)$
- where, $K = \sum_{B \cap C = \emptyset} m_1(B) m_2(C)$

Combination of m_1 and m_2

$\{ 'b' \}: 0.5, \{ 'a' \}: 0.2499, \{ 'c' \}, \{ 'a' \}: 0.1499,$
 $\{ 'c' \}: 0.09999$

Algorithm-

Step 1: Start

Step 2: Each piece of evidence is represented by a separate belief function

Step 3: Combination rules are then used to successively fuse all these belief functions in order to obtain a belief function representing all available evidence.

Step 4: Specifically, the combination (called the joint mass) is calculated from the two sets of masses m_1 and m_2 in the following manner:

- $m_{1,2}(\emptyset) = 0$
- $m_{1,2}(A) = (m_1 \oplus m_2)(A) = (1/1-K) \sum_{B \cap C = A \neq \emptyset} m_1(B) m_2(C)$

where,

- $K = \sum_{B \cap C = \emptyset} m_1(B) m_2(C)$

K is a measure of the amount of conflict between the two mass sets.

Step 5: In python Mass-Function has the built-in combination rules.

Step 6: Stop

Code-

```
from numpy import *
```

```
# Do NOT use, just for illustration of the D-S combination rules implementation
```

```
def DempsterRule(m1, m2):
```

```
    ## extract the frame of discernment
```

```
    sets=set(m1.keys()).union(set(m2.keys()))
```

```
    result=dict.fromkeys(sets,0)
```

```
    ## Combination process
```

```
    for i in m1.keys():
```

```
        for j in m2.keys():
```

```
            if set(str(i)).intersection(set(str(j))) == set(str(i)):
```

```
                result[i]+=m1[i]*m2[j]
```

```
            elif set(str(i)).intersection(set(str(j))) == set(str(j)):
```

```
                result[j]+=m1[i]*m2[j]
```

```

## normalize the results

f= sum(list(result.values()))


for i in result.keys():
    result[i] /=f

return result

m1 = {'a':0.4, 'b':0.2, 'ab':0.1, 'abc':0.3}
m2 = {'b':0.5, 'c':0.2, 'ac':0.3, 'a':0.0}
print(DempsterRule(m1, m2))

```

Output-



```

input
{'ab': 0.0, 'b': 0.5263157894736842, 'abc': 0.0, 'c': 0.10526315789473682, 'ac': 0.15789473684210523, 'a': 0.21052631578947364}

```

Result-

Hence, the Implementation of Dempster Shafer Theory is done successfully.