

Enter password: *****

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 21

Server version: 8.0.45 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
mysql> CREATE DATABASE New;
```

Query OK, 1 row affected (0.01 sec)

```
mysql> USE New;
```

Database changed

```
mysql> CREATE TABLE Sample1(
```

```
    -> EID INT,
```

```
    -> Name VARCHAR(25),
```

```
    -> Dept VARCHAR(10),
```

```
    -> Age INT,
```

```
    -> Addr VARCHAR(15),
```

```
    -> Salary INT
```

```
    -> );
```

Query OK, 0 rows affected (0.02 sec)

```
mysql>
```

```
mysql> DESC Sample1;
```

```
+-----+-----+-----+-----+-----+
| Field | Type   | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| EID   | int    | YES  |     | NULL    |       |
| Name  | varchar(25) | YES  |     | NULL    |       |
| Dept  | varchar(10) | YES  |     | NULL    |       |
| Age   | int    | YES  |     | NULL    |       |
| Addr  | varchar(15) | YES  |     | NULL    |       |
| Salary | int    | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```

```
6 rows in set (0.00 sec)
```

```
mysql>
```

```
mysql> INSERT INTO Sample1 VALUES(1,'Anil','Acct',23,'Chennai',15000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Sample1 VALUES(2,'Sunil','Admin',40,'Goa',18000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Sample1 VALUES(3,'Vikas','Acct',35,'Bangalore',20000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Sample1 VALUES(4,'Roy','Acct',37,'Bangalore',20000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Sample1 VALUES(5,'Rock','Admin',35,'Mangalore',21000);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Sample1 VALUES(6,'Ganesh','Acct',30,'Cochin',22000);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Sample1 VALUES(6,'Sathesh','Admin',40,'Chennai',20000);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Sample1 VALUES(6,'Ganesh','Acct',30,'Cochin',22000);
```

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Sample1 VALUES(7,'Sathesh','Admin',40,'Chennai',23000);
```

Query OK, 1 row affected (0.00 sec)

```
mysql>
```

```
mysql> SELECT * FROM Sample1;
```

```
+-----+-----+-----+-----+-----+-----+
| EID | Name  | Dept | Age | Addr   | Salary |
+-----+-----+-----+-----+-----+-----+
| 1 | Anil  | Acct | 23 | Chennai | 15000 |
| 2 | Sunil | Admin | 40 | Goa     | 18000 |
| 3 | Vikas | Acct | 35 | Bangalore | 20000 |
| 4 | Roy   | Acct | 37 | Bangalore | 20000 |
| 5 | Rock  | Admin | 35 | Mangalore | 21000 |
| 6 | Ganesh | Acct | 30 | Cochin  | 22000 |
| 6 | Sathesh | Admin | 40 | Chennai | 20000 |
| 6 | Ganesh | Acct | 30 | Cochin  | 22000 |
| 7 | Sathesh | Admin | 40 | Chennai | 23000 |
```

```
+-----+-----+-----+-----+-----+-----+
```

9 rows in set (0.00 sec)

mysql>

mysql> DELETE FROM Sample1 WHERE EID=6;

Query OK, 3 rows affected (0.00 sec)

mysql>

mysql> SELECT * FROM Sample1;

```
+-----+-----+-----+-----+-----+-----+
```

```
| EID | Name  | Dept | Age | Addr  | Salary |
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| 1 | Anil  | Acct | 23 | Chennai | 15000 |
```

```
| 2 | Sunil | Admin | 40 | Goa    | 18000 |
```

```
| 3 | Vikas | Acct | 35 | Bangalore | 20000 |
```

```
| 4 | Roy   | Acct | 37 | Bangalore | 20000 |
```

```
| 5 | Rock  | Admin | 35 | Mangalore | 21000 |
```

```
| 7 | Sathesh | Admin | 40 | Chennai | 23000 |
```

```
+-----+-----+-----+-----+-----+-----+
```

6 rows in set (0.00 sec)

mysql>

mysql> INSERT INTO Sample1 VALUES(6,'Ganesh','Acct',30,'Cochin',22000);

Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO Sample1 VALUES(8,'James','Admin',38,'Cochin',32000);

Query OK, 1 row affected (0.00 sec)

```
mysql> INSERT INTO Sample1 VALUES(9,'Mark','Quality',58,'US',60000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Sample1 VALUES(10,'Monica','Quality',48,'US',50000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql>
```

```
mysql> SELECT * FROM Sample1;
```

```
+-----+-----+-----+-----+-----+-----+
| EID | Name  | Dept  | Age | Addr   | Salary |
+-----+-----+-----+-----+-----+-----+
| 1 | Anil  | Acct  | 23 | Chennai | 15000 |
| 2 | Sunil | Admin | 40 | Goa     | 18000 |
| 3 | Vikas | Acct  | 35 | Bangalore | 20000 |
| 4 | Roy   | Acct  | 37 | Bangalore | 20000 |
| 5 | Rock  | Admin | 35 | Mangalore | 21000 |
| 7 | Sathesh | Admin | 40 | Chennai | 23000 |
| 6 | Ganesh | Acct  | 30 | Cochin  | 22000 |
| 8 | James | Admin | 38 | Cochin  | 32000 |
| 9 | Mark  | Quality | 58 | US      | 60000 |
| 10 | Monica | Quality | 48 | US      | 50000 |
+-----+-----+-----+-----+-----+-----+
```

```
10 rows in set (0.00 sec)
```

```
mysql>
```