prajwalhonashetti143@gmail.com

Day 24:.

Task 1: Build Lifecycle

Demonstrate the use of Maven lifecycle phases (clean, compile, test, package, install, deploy) by executing them on a sample project and documenting what happens in each phase.

Phase 1: clean

This phase ensures that the project is in a clean state before building it.

mvn clean

What happens:

Deletes the target directory (where build artifacts are stored).

Cleans up any files created during the previous build.

Phase 2: compile

This phase compiles the source code of the project.

mvn compile

What happens:

Compiles all Java source files (src/main/java) in the project.

Outputs compiled classes to target/classes.

Phase 3: test

This phase runs tests against compiled source code using a suitable unit testing framework.

mvn test

What happens:

- Executes all test cases found in src/test/java.
- Reports on test results.
- By default, this uses JUnit and creates a report in target/surefire-reports.

Phase 4: package

This phase packages the compiled code into distributable format, such as JAR, WAR, or EAR.

mvn package

What happens:

- Takes the compiled code (target/classes), resources (src/main/resources), and tests (target/test-classes) and packages them into a JAR (by default).
- Outputs the packaged artifact (maven-demo-1.0-SNAPSHOT.jar) in the target directory.

Phase 5: install

This phase installs the package into the local repository, for use as a dependency in other projects locally.

mvn install

What happens:

- Copies the packaged artifact (maven-demo-1.0-SNAPSHOT.jar) into the local Maven repository (~/.m2/repository/com/example/mavenproject/maven-demo/1.0-SNAPSHOT/).
- Makes it available for other projects that declare it as a dependency in their pom.xml files.

Phase 6: deploy

This phase copies the final package to the remote repository for sharing with other developers and projects.

mvn deploy

What happens:

- Copies the packaged artifact to a remote repository (if configured) like Nexus or Artifactory.
- Typically used in a Continuous Integration/Continuous Deployment (CI/CD) environment to share artifacts across multiple projects.

Output:

1. clean Phase

[INFO] Scanning for projects...

[INFO]

| [INFO] com.example:sample-maven-project > |
|------------------------------------------------------------------------------------------|
| [INFO] Building sample-maven-project 1.0-SNAPSHOT |
| [INFO][jar] |
| [INFO] |
| [INFO] maven-clean-plugin:3.1.0:clean (default-clean) @ sample-maven-project |
| [INFO] Deleting /path/to/sample-maven-project/target |
| [INFO] |
| [INFO] BUILD SUCCESS |
| [INFO] |
| [INFO] Total time: 0.391 s |
| [INFO] Finished at: 2024-06-19T12:00:00Z |
| [INFO] |
| |
| 2. compile Phase |
| [INFO] Scanning for projects |
| [INFO] |
| [INFO]< com.example:sample-maven-project > |
| [INFO] Building sample-maven-project 1.0-SNAPSHOT |
| [INFO][jar] |
| [INFO] |
| [INFO] maven-resources-plugin:3.2.0:resources (default-resources) @ sample-maven-project |
| [INFO] Using 'UTF-8' encoding to copy filtered resources. |
| [INFO] Copying 0 resource |
| [INFO] Copying 0 resource |
| [INFO] |
| [INFO] maven-compiler-plugin:3.8.1:compile (default-compile) @ sample-maven-project |
| [INFO] Changes detected - recompiling the module! |
| [INFO] Compiling 1 source file to /path/to/sample-maven-project/target/classes |

| [INFO] |
|--------------------------------------------------------------------------------------------------|
| [INFO] BUILD SUCCESS |
| [INFO] |
| [INFO] Total time: 1.116 s |
| [INFO] Finished at: 2024-06-19T12:00:00Z |
| [INFO] |
| |
| 3. test Phase: output: |
| [INFO] Scanning for projects |
| [INFO] |
| [INFO]< com.example:sample-maven-project > |
| [INFO] Building sample-maven-project 1.0-SNAPSHOT |
| [INFO][jar] |
| [INFO] |
| [INFO] maven-resources-plugin:3.2.0:resources (default-resources) @ sample-maven-project |
| [INFO] Using 'UTF-8' encoding to copy filtered resources. |
| [INFO] Copying 0 resource |
| [INFO] Copying 0 resource |
| [INFO] |
| [INFO] maven-compiler-plugin:3.8.1:compile (default-compile) @ sample-maven-project |
| [INFO] Nothing to compile - all classes are up to date |
| [INFO] |
| [INFO] maven-resources-plugin:3.2.0:testResources (default-testResources) @ sample-maven-project |
| [INFO] Using 'UTF-8' encoding to copy filtered resources. |
| [INFO] skip non existing resourceDirectory /path/to/sample-maven-project/src/test/resources |
| [INFO] |

| [INFO] maven-compiler-plugin:3.8.1:testCompile (default-testCompile) @ sample-maven-project |
|---------------------------------------------------------------------------------------------|
| [INFO] No sources to compile |
| [INFO] |
| [INFO] maven-surefire-plugin:3.0.0-M5:test (default-test) @ sample-maven-project |
| [INFO] No tests to run. |
| [INFO] |
| [INFO] BUILD SUCCESS |
| [INFO] |
| [INFO] Total time: 1.265 s |
| [INFO] Finished at: 2024-06-19T12:00:00Z |
| [INFO] |
| |
| 4. package Phase: |
| Output: |
| [INFO] Scanning for projects |
| [INFO] |
| [INFO]< com.example:sample-maven-project > |
| [INFO] Building sample-maven-project 1.0-SNAPSHOT |
| [INFO][jar] |
| [INFO] |
| [INFO] maven-resources-plugin:3.2.0:resources (default-resources) @ sample-maven-project |
| [INFO] Using 'UTF-8' encoding to copy filtered resources. |
| [INFO] Copying 0 resource |
| [INFO] Copying 0 resource |
| [INFO] |
| [INFO] maven-compiler-plugin:3.8.1:compile (default-compile) @ sample-maven-project |
| [INFO] Nothing to compile - all classes are up to date |

| [INFO] |
|--------------------------------------------------------------------------------------------------|
| [INFO] maven-resources-plugin:3.2.0:testResources (default-testResources) @ sample-maven-project |
| [INFO] Using 'UTF-8' encoding to copy filtered resources. |
| [INFO] skip non existing resourceDirectory /path/to/sample-maven-project/src/test/resources |
| [INFO] |
| [INFO] maven-compiler-plugin:3.8.1:testCompile (default-testCompile) @ sample-maven-project |
| [INFO] No sources to compile |
| [INFO] |
| [INFO] maven-surefire-plugin:3.0.0-M5:test (default-test) @ sample-maven-project |
| [INFO] No tests to run. |
| [INFO] |
| [INFO] maven-jar-plugin:3.2.0:jar (default-jar) @ sample-maven-project |
| [INFO] Building jar: /path/to/sample-maven-project/target/sample-maven-project-1.0-SNAPSHOT.jar |
| [INFO] |
| [INFO] BUILD SUCCESS |
| [INFO] |
| [INFO] Total time: 1.232 s |
| [INFO] Finished at: 2024-06-19T12:00:00Z |
| [INFO] |
| |
| 5. install Phase: output: |
| [INFO] Scanning for projects |
| [INFO] |
| [INFO]< com.example:sample-maven-project > |
| [INFO] Building sample-maven-project 1.0-SNAPSHOT |
| [INFO][jar] |
| [INFO] |

```
[INFO] --- maven-resources-plugin:3.2.0:resources (default-resources) @ sample-maven-
project ---
[INFO] Using 'UTF-8' encoding to copy filtered resources.
[INFO] Copying 0 resource
[INFO] Copying 0 resource
[INFO]
[INFO] --- maven-compiler-plugin:3.8.1:compile (default-compile) @ sample-maven-project
[INFO] Nothing to compile - all classes are up to date
[INFO]
[INFO] --- maven-resources-plugin:3.2.0:testResources (default-testResources) @ sample-
maven-project ---
[INFO] Using 'UTF-8' encoding to copy filtered resources.
[INFO]
           skip
                    non
                            existing
                                         resourceDirectory
                                                               /path/to/sample-maven-
project/src/test/resources
[INFO]
[INFO] --- maven-compiler-plugin:3.8.1:testCompile (default-testCompile) @ sample-
maven-project ---
[INFO] No sources to compile
[INFO]
[INFO] --- maven-surefire-plugin:3.0.0-M5:test (default-test) @ sample-maven-project ---
[INFO] No tests to run.
[INFO]
[INFO] --- maven-jar-plugin:3.2.0:jar (default-jar) @ sample-maven-project ---
[INFO] Building jar: /path/to/sample-maven-project/target/sample-maven-project-1.0-
SNAPSHOT.jar
[INFO]
[INFO] --- maven-install-plugin:3.0.0-M1:install (default-install
```