

AMENDMENT NO. 1 MARCH 2007
TO
IS 15560 : 2005 POINT HOOKS WITH SHANKS UP TO 160 TONNE —
SPECIFICATION

(Foreword, second para, sixth line) — Delete the sentence 'This standard does not considered 0.063 tonne to 0.5 tonne capacity.'

(Page 1, clause 1.1.1, last line) — Substitute '0.063' for '0.63'.

(Page 4 Table 1) — Substitute the following table for the existing:

Table 1 Dimensional Characteristics of Shank Hooks

(Clause 6.1)

All dimensions in millimetres.

Lifting Capacity 'C _p ' in Tonnes for Grade				Throat Opening 2.9 d _n Min	Throat Opening 2.7 d _n Min	Seat Dia Min	Section			Shank Dia Max	
							Depth Max	Width Max	Height Max		
L	M	S	T	G	G ₁	D	H _m	L _m	L	E	B _s
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
0.063	0.08	0.125	0.16	18.00	17.50	18.00	15.50	10.00	53	14.00	28
0.125	0.16	0.25	0.32	21.20	20.50	20.00	20.00	12.11	70	17.00	34
0.25	0.32	0.50	0.63	25.00	24.00	22.00	25.70	16.00	84	20.00	41
0.50	0.63	1.00	1.25	30.00	29.00	25.00	30.70	18.00	102	22.4	47
0.63	0.80	1.25	1.60	20.60	19.20	27.00	32.00	20.60	122	25.00	49
0.80	1.00	1.60	2.00	23.20	21.60	30.40	36.50	23.20	130	26.50	54
1.00	1.25	2.00	2.50	26.10	24.30	34.20	40.00	26.10	139	28.00	57
1.25	1.60	2.50	3.20	29.00	27.00	38.00	43.00	29.00	149	30.00	60
1.60	2.00	3.20	4.00	31.90	29.70	41.80	47.50	31.90	158	31.50	64
2.00	2.50	4.00	5.00	34.80	32.40	45.60	51.60	34.80	170	33.50	68
2.50	3.20	5.00	6.30	40.60	37.80	53.20	60.20	40.60	188	37.50	72
3.20	4.00	6.30	8.00	46.40	43.20	60.80	68.80	46.40	209	42.50	76
4.00	5.00	8.00	10.00	52.20	48.60	68.40	77.40	52.20	235	47.50	80
5.00	6.30	10.00	12.50	58.00	54.00	76.00	86.00	58.00	263	53.00	90
6.30	8.00	12.50	16.00	65.00	59.40	83.60	94.60	63.80	296	60.00	101
8.00	10.00	16.00	20.00	72.20	67.50	95.00	107.50	72.50	335	67.00	113
10.00	12.50	20.00	25.00	81.20	75.60	106.4	120.40	81.20	375	75.00	127
12.50	16.00	25.00	32.00	92.80	86.40	121.6	137.60	92.80	402	85.00	143
16.00	20.00	32.00	40.00	104.40	97.20	136.8	154.80	104.40	469	95.00	160
20.00	25.00	40.00	50.00	127.0	117.0	169.0	157.0	101.0	485	110.0	180
25.00	32.00	50.00	63.00	142.0	131.5	189.0	176.0	113.0	520	120.0	202
32.00	40.00	63.00	80.00	155.0	143.5	207.0	193.0	124.0	569	130.0	225
40.00	50.00	80.00	100.0	168.0	156.0	224.0	208.0	134.0	616	140.0	252
50.00	63.00	100.0	125.0	187.0	173.0	247.0	229.0	148.0	680	150.0	285
63.00	80.00	125.0	160.0	200.0	185.0	250.0	280.0	224.0	906	170.0	320
80.00	100.0	160.0	-	224.0	207.0	280.0	315.0	250.0	1020	190.0	358
100.0	125.0	-	-	250.0	231.0	315.0	355.0	300.0	1115	212.0	402
125.0	160.0	-	-	280.0	259.0	355.0	400.0	315.0	1250	236.0	450
160.0	-	-	-	315.0	292.0	400.0	450.0	355.0	1485	260.0	505