

AMENDMENT NO. 1 JULY 2024
TO
IS 15627 : 2022 AUTOMOTIVE VEHICLES — PNEUMATIC TYRES FOR
TWO AND THREE-WHEELED MOTOR VEHICLES, QUADRICYCLES AND
E-RICKSHAW/E-CARTS — SPECIFICATION
(First Revision)

[Page 3, clause **3.28(b)**, line 3] — Substitute ‘one or more layer’ for ‘one layer’.

(Page 3, clause **3.28**) — Substitute ‘**3.28**’ for ‘**3.29**’.

[Page 4, clause **4.1.3.1(b)**, line 3] — Substitute ‘less than or equal to’ for ‘less than’.

(Page 5, clause **4.2.1**, line 6) — Substitute ‘Table 14’ for ‘Table 12’.

(Page 5, clause **4.3.1**, line 7) — Substitute ‘Table 15’ for ‘Table 13.’

(Page 5, clause **4.4**) — Substitute the following for the existing:

‘4.4 Tyre Strength Test (Plunger Test)

The sample shall conform to the requirements specified in Tables 16, 17 and 18 (as applicable) when tested as per the method given in Annex G.’

(Page 6, clause **4.5**, line 1) — Substitute ‘Table 19’ for ‘Table 18.’

[Page 6, clause **5.1(c)**, Note] — Substitute ‘Tables 20 and 21’ for ‘Tables 19 and 20.’

[Page 6, clause **5.1(q)**] — Substitute the following for the existing:

‘q) Cold inflation pressure in kPa.’

[Page 6, clause **5.1(u)**] — Substitute the following for the existing:

‘u) The inscription ‘M + S’ or ‘M.S’ or ‘M & S’ or ‘DP’ in the case of a snow tyre. Inscription ‘M + S’ or ‘M.S’ or ‘M & S’ indicates mud and snow, and DP indicates dual purpose.’

(Page 7, clause **5.2**) — Substitute the following for the existing:

‘5.2 Markings given in **5.1** shall be either permanently moulded into or permanently engraved/etched onto the tyres. The marking shall be clearly legible, indelible and raised above or sunk below the tyre surface. Engraving/etching shall be done during the manufacturing process of the tyre and not later than 24 h after the removal of the tyre from the mould.’

(Page 7, clause **6.1**, line 2) — Substitute ‘Table 22’ for ‘Table 21.’

(Page 7, clause **6.2.5.1**) — Substitute the following for the existing:

‘6.2.5.1 In case the changes cause the tyre to be outside the approved family/range of tyres, the verification shall be carried out for establishing compliance of the changed parameters to the requirements specified in this standard. If a tubeless tyre version is approved its tube version shall also deemed to be approved.’

(Page 7, clause **6.3**) — Insert the following after **6.3**

‘6.4 If the cold inflation pressure declared by the manufacturers varies for tyre sizes listed in Table 05 to 11, Table 12 to be referred for inflation pressure values corresponding to speed capability of vehicle.’

Price Groupe 2

Amendment No. 1 to IS 15627 : 2022

(Page 8, clause 7.3, line 3) — Substitute the ‘Table 23’ for ‘Table 22.’

[Page 10, Table 2, row (ii)] — Substitute ‘≤’ for ‘<’ and ‘≥’ for ‘>’.

(Page 11, clause C-1, line 2) — Substitute the ‘Table 5 to 11’ for ‘Table 5 to 10’.

(Page 11, clause C-3, line 1) — Substitute the ‘Table 5 to 11’ for ‘table’.

[Page 12, Table 5(a), col (14)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 12, Table 5(b), col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 13, Table 6(a), col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 13, Table 6(b), col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Maximum Cold I.P¹⁾’.

[Page 14, Table 7, col (14)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 15, Table 8, col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 16, Table 9, col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 18, Table 10, col (14)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

[Page 19, Table 11, col (13)] — Substitute the ‘Cold I.P¹⁾’ for ‘Max Cold I.P¹⁾’.

(Page 19) Insert the following table after Table 11 and renumber the subsequent tables:

‘Table 12 Basic Inflation Pressure (kPa) versus Speed at the Maximum Load of the Tyre

Sl. No	Speed Capability of the Vehicle (km/h)	Speed Symbol								
		P	Q	R	S	T	U	H	V	W
		Inflation Pressure (kPa)								
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
i)	≤ 150	230	230	230	230	230	230	230	230	230
ii)	160		240	240	240	240	240	240	240	240
iii)	170			250	250	250	250	250	250	250
iv)	180				260	260	260	260	260	260
v)	190					270	270	270	270	260
vi)	200						280	280	280	270
vii)	210							290	290	270
viii)	220								290	280
ix)	230								290	280
x)	240								290	290
xi)	250								*	290
xii)	260								*	290
xiii)	270								*	290
xiv)	280									*
xv)	290									*
xvi)	300									*

*if applicable, consult the tyre manufacturer.

NOTES

1) The inflation pressures mentioned in the load/inflation pressure limit Table 5 (a) to Table 11 are minimum values related to loads corresponding to speed 150 Km/h (speed symbol P) and below. They shall take into account not only the load but also the tyre construction, road holding, maximum speed, the location of the tyre, the operating conditions and the mechanical characteristics of the vehicle.

Amendment No. 1 to IS 15627 : 2022

- 2) In particular, for higher speeds, increases in pressure are essential for safety reasons. These increases are determined by using the values in Table 12. The actual pressure is to be adjusted for the design maximum load acting on the wheel.
- 3) Basic inflation pressure (kPa) versus speed at the maximum load of the tyre to be used for standard load tyres in the absence of declaration by tyre manufacturers.
- 4) In the case of reinforced tyres, the figures in above table increases by 50 kPa.'

(Page 19, clause **D-1**, line 4) — Substitute 'Table 13' for 'Table 12'.

[Page 20, clause **D-1**, Table 13, Sl No. (i)] — Substitute the following for the existing:

i)	Mopeds		
	Standard Rim Diameter Code ≤ 12	B	230
	Standard Rim Diameter Code ≥ 13	B	250
	Reinforced Rim Diameter Code ≥ 12	B	275

[Page 20, Table 13, Sl. No. (v)] — Substitute the following for the existing:

v)	E Rickshaw/E-carts		
	Standard For all rim diameter code	B	280

(Page 21, clause **E-1.2**, line 4) — Substitute 'Table 14' for 'Table 13'.

[Page 22, Table 14, Sl No. (v)] — Substitute the following for the existing:

v)	E Rickshaw/E-carts		
	Standard For all rim diameter code	B	280

(Page 23, clause **F-1**, line 7) — Substitute 'Table 15' for 'Table 13.'

(Page 23, clause **F-3.4**, line 2) — Substitute 'Table 15' for 'Table 14.'

(Page 25, clause **G-1**, line 3) — Substitute 'Tables 16, 17 or 18' for 'Tables 15, 16 or 17'.

(Page 25, clause **G-6.1**, line 3) — Substitute 'Tables 16, 17 and 18' for 'Tables 15, 16 and 17'.

(Page 25, clause **G-6.2**, line 3) — Substitute 'Tables 16, 17 and 18' for 'Tables 15, 16 and 17'.

(Page 25, clause **G-6.3**, lines 1 and 2) — Substitute 'Tables 16, 17 and 18' for 'Tables 15, 16 and 17'.

(Page 26, clause **H-4**, line 5) — Substitute 'Table 19' for 'Table 18.'

(Page 26, clause **H-1**) — Delete.

(Page 27, clause **J-1**) — Substitute the following for the existing:

'J-1 Example

$b \geq 4 \text{ mm}$	$\overline{b}$	100/80 R 18 M/C 53 S	TUBELESS	MAR 04
-----------------------	----------------	----------------------	----------	--------

(Page 27, Annex J) — Insert the following after clause **J-1.2(a)** and renumber the subsequent clauses:

'J-1.2 (b) M/C marking (optional), shall be in between rim diameter code and load index.'

Amendment No. 1 to IS 15627 : 2022

(Page 29, Annex K, 20) — Substitute the following for the existing:
'20 Inflation pressure (kPa),'.

(Page 29, Annex K, 19.1) — Substitute the following for the existing:
'20.1 Inflation pressure corresponding to maximum load carrying capacity,'.

(Page 29, Annex K, 19.2) — Substitute the following for the existing:
'20.2 Test and measurement pressures'.