

AMENDMENT NO. 2 FEBRUARY 2026
TO
IS 15633 : 2022 AUTOMOTIVE VEHICLES — PNEUMATIC TYRES FOR
PASSENGER CAR VEHICLE — DIAGONAL AND RADIAL PLY —
SPECIFICATION
(First Revision)

[Page 1, clause 1 (see also Amendment No. 1)] — Substitute the following for the existing:

‘1 SCOPE

This standard specifies the general, dimensional and performance requirements of new diagonal and radial ply pneumatic tyres designed primarily for vehicles in categories M1, N1, T1 and T2. It does not apply to tyres designed primarily for:

- a) The equipment of vintage cars; and
- b) Competitions (racings).

NOTES

1 For the purpose of this standard ‘tyres’ means ‘pneumatic tyres’; and

2 This standard defines requirements for tyres as a component. It does not limit their installation on any categories of vehicles.’

[Page 1, clause 3.1.1 (see also Amendment No. 1)] — Substitute the following for the existing:

‘3.1.1 Type of Pneumatic Tyres — It means a category of pneumatic tyres which do not differ in such essential respects as:

- a) Manufacturers name and brand name;
- b) Tyre-size designation;
- c) Category of use:
 - 1) Normal — Normal road use tyres;
 - 2) Special — Special-use tyre, for example, tyre for mixed use (both on and off the road) at restricted speed;
 - 3) Snow tyre;
 - 4) Temporary use spare tyre, and T type temporary use spare tyre;
- d) Structure [diagonal (bias-ply), bias-belted, radial, run flat];
- e) Speed category;
- f) Load-capacity index or maximum load and ply rating; and
- g) Nominal cross-section — Dimension when fitted to a specified rim.’

(Page 1, clause 3.3.4) — Substitute the following for the existing:

‘3.3.4 Reinforced or Extra Load and High Load Capacity Tyres

3.3.4.1 Reinforced/extra load tyres — A tyre designed to carry more load at a higher inflation pressure than the load carried by the corresponding standard tyre at the standard inflation pressure as specified in ISO 4000-1.

Price Group 4

Amendment No. 2 to IS 15633 : 2022

3.3.4.2 High load capacity (HL) tyres — High load capacity tyres are Extra load tyres/reinforced tyres that are designed to carry a higher load at the same inflation pressure corresponding to reinforced tyres/extra load tyres.’

[Page 5, clause **3.33.1** (see also Amendment No. 1)] — ‘Delete’

[Page 6, clause **3.38** (see also Amendment No. 1)] — Insert the following at the end:

‘3.39 T-type Temporary Use Spare Tyre — A type of temporary use spare tyre designed for use at inflation pressures higher than those established for standard and reinforced tyres.’

[Page 7, clause **4.2.1**, (see also Amendment No. 1)] — Substitute the following for the existing:

‘The sample shall conform to the requirements given in **4.2.5** and **4.2.6** when tested as per the method given in Annex C (Table 17) excluding **C3** and **C4**. Run flat and extended mobility tyres additionally shall conform to the requirement given in **4.2.7** and **4.2.8** respectively.’

(Page 7, clause **4.3.1**) — Substitute the following for the existing:

‘4.3.1 The sample shall conform to the requirements specified in **4.3.2** when tested as per the method given in Annex D (Table 18). Endurance test is not required for temporary use spare tyres and T-type temporary use spare tyres.’

[Page 8, clause **5.1(c) (5)** (see also Amendment No. 1)]— Substitute the following for the existing:

‘5) On run flat tyres the letter ‘RF’ placed in front of the rim diameter marking.’

[Page 8, clause **5.1(m)**] — Substitute the following for the existing:

- ‘m) REINFORCED/REINF/EXTRA LOAD/XL for reinforced and high load capacity tyres. Additionally, high load capacity tyres shall be marked with ‘HL’ in front of the nominal section width (the height of characters shall be as specified for tyre size designation).’

[Page 8, clause **5.1(n)**] — Substitute the following for the existing:

- ‘n) For temporary use spare tyre and T-type temporary use spare tyre additional marking of TEMPORARY USE ONLY (The height of uppercase characters shall be at least 12.7 mm high). For T-type temporary use spare tyre following additional markings are required:
- 1) INFLATE TO 420 kPa (60 psi). (The height of upper-case characters shall be at least 12.7 mm high; and
 - 2) T in front of the nominal section width. (The height of characters shall be as specified for tyres size designation).

NOTES

1 The above markings may be marked in the upper area of the tyre; and

2 Manufacturers may mark additional speed in km/h lower than max speed category symbol marked on the tyre as recommended by vehicle manufacturer. Vehicle usage speed (maximum 80 km/h or maximum 120 km/h) can be less than speed category symbols in case temporary use spare tyres and T type temporary use spare tyres.’

[Page 9, clause **6.2.5.2(f)**, (see also Amendment No. 1)] — Substitute the following for the existing:

- ‘f) Structure [diagonal or radial or bias belted or run flat];’.

(Page 9, Table 7) — Substitute the following for the existing:

Table 7 Type Test Schedule
(Clause 6.1)

Sl No.	Tests	Tyre 1	Tyre 2	Tyre 3	Tyre 4	Tyre 5	Tyre 6
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
i)	Tyre marking	✓	----	----	----	----	----
ii)	Tyre dimensions	✓	----	----	----	----	----
iii)	Tread wear indicators	✓	----	----	----	----	----
iv)	Tyre strength test	✓	----	----	----	----	----
v)	Endurance test	----	✓	----	----	----	----
vi)	Load/speed performance test	----	----	✓	----	----	----
vii)	Bead unseating resistance test for tubeless tyres	----	----	----	✓	----	----
viii)	Additional load speed performance test (if required) (see NOTE 1)	----	----	----	----	✓	----
ix)	Second additional load speed performance test (if required) (see NOTE 2)	----	----	----	----	----	✓
NOTES 1 If tyres identified by means of letter code ZR and suitable for speed more than 300 km/h, 5th tyre shall be required for the performing additional load speed test as per 4.2.2. 2 If tyres are identified as run flat or extended mobility, 6th tyre shall be required for the performing the flat tyre running mode as per procedure C-3 and C-4 respectively.							

(Page 10, Table 8) — Substitute the following for the existing:

Table 8 Conformity of Production Test
(Clause 7.2)

Sl No.	Tests	Tyre 1	Tyre 2	Tyre 3	Tyre 4	Tyre 5	Tyre 6
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
i)	Tyre marking	✓	----	----	----	----	----
ii)	Tyre dimensions	✓	----	----	----	----	----
iii)	Tread wear indicators	✓	----	----	----	----	----
iv)	Tyre strength test	✓	----	----	----	----	----
v)	Endurance test	----	✓	----	----	----	----
vi)	Load/speed performance test	----	----	✓	----	----	----
vii)	Bead unseating resistance test for tubeless tyres	----	----	----	✓	----	----

Amendment No. 2 to IS 15633 : 2022

Sl No.	Tests	Tyre 1	Tyre 2	Tyre 3	Tyre 4	Tyre 5	Tyre 6
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
viii)	Additional load speed performance test (if required) (<i>see</i> NOTE 1)	----	----	----	----	✓	----
ix)	Second additional load speed performance test (if required) (<i>see</i> NOTE 2)	----	----	----	----	----	✓
NOTES 1 If tyres identified by means of letter code ZR and suitable for speed more than 300 km/h, 5th tyre shall be required for the performing additional load speed test as per 4.2.2. 2 If tyres are identified as run flat or extended mobility, 6th tyre shall be required for the performing the flat tyre running mode as per procedure C-3 and C-4 respectively.							

Amendment No. 2 to IS 15633 : 2022

[Page 19, Table 14, 55 Series, SI No. (x) and (xi), (see also Amendment No. 1)] — Substitute the following for the existing:

SI No.	Tyre Size Designation	Rim Rec Alt	New Tyre-Inflated								
			Section Width, mm			Overall Diameter, mm			Load Index	Maximum Load kg	Cold I. P ¹⁾ (Corresponding to Maximum Load) kPa
			Design Width	Minimum Width	Maximum Width	Design Diameter	Minimum Diameter	Maximum Diameter			
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
x)	235/55R17	$7 \frac{1}{2} J$ 7J	$\frac{245}{240}$	$\frac{235}{230}$	$\frac{255}{250}$	690	682	698	Std. 99	775	250
									Reinf. 103	875	290
xi)	215/55R18	$\frac{7J}{6 \frac{1}{2} J}$	$\frac{226}{221}$	$\frac{217}{212}$	$\frac{235}{230}$	693	686	700	Std. 95	690	250
									Reinf. 99	775	290

(Page 22, Table 15, Title) — Substitute ‘**T Type Temporary use Spare Passenger Car Tyres (Diagonal Ply)**’ for ‘Temporary use Spare Passenger Car Tyres (Diagonal Ply)’.

(Page 22, Table 16, Title) — Substitute ‘**T Type Temporary use Spare Passenger Car Tyres (Radial Ply)**’ for ‘Temporary use Spare Passenger Car Tyres (Radial Ply)’.

(Page 22, Table 16) — Insert the following at the end:

‘NOTE — For temporary use spare tyres refer Table 9 to Table 14 for dimension, load, and inflation pressure details.’

Amendment No. 2 to IS 15633 : 2022

[Page 33, Annex J, (*see also Amendment No. 1*)] — Substitute the following for the existing:

‘ANNEX J

(*Clause 6.2.2*)

INFORMATION TO BE SUBMITTED FOR TYPE APPROVAL OF TYRES

1. Manufacturer’s name and address
2. Telephone No.
3. FAX. No.
4. E-mail address
5. Contact person
6. Tyre-size designation
7. Trade-name or mark
8. Category of use (normal/special/snow/ temporary use spare tyre /T type temporary use spare tyre)
9. Structure: [diagonal (bias-ply), bias-belted, radial, run flat]
10. Whether the tyre is an EMT
11. Fabric material: [Nylon (polyamide)/polyester/rayon, etc (one type).]
12. Speed category of the tyre
13. Load- index of the tyre/maximum load carrying capacity of the tyre (kg)
14. Whether the tyre is to be used with or without an inner tube
15. Whether the tyre is normal or reinforced or high load capacity
16. Ply-rating for code designated tyre
17. Overall section width (mm)
18. Overall diameter (mm)
19. Rim on which tyre can be mounted
20. Measuring rim and test rim
21. Inflation pressure (kPa)
 - 21.1 Inflation pressure corresponding to maximum load carrying capacity
 - 21.2 Test and measurement pressures
22. Factor X referred to in **3.31** in case of theoretical (imaginary) rim, if applicable
23. Maximum speed permitted by the tyre manufacturer and the load carrying capacity allowed for that maximum speed. Applicable only for tyres identified by means of letter code ‘V’ within the size designation and suitable for speeds over 240 km/h or for tyres identified by means of letter code ‘Z’ within the size designation and suitable for speeds over 270 km/h
24. Intended for use on (type of vehicle)
25. If tyre size is not listed in Table 9 to Table 16 and or tyre sizes with a different ply rating and/or load- inflation details other than those given in Table 9 to Table 16, reference to standards manuals of organizations like The European Tyre and Rim Technical Organization (ETRTO), Indian Tyre Technical Advisory Committee (ITTAC), The Japan Automobile Tyre Manufacturers’ Association (JATMA), The Tire and Rim Association, Inc. (T and RA-US);

Amendment No. 2 to IS 15633 : 2022

26. If reference to Standards Manuals of Organizations (illustrated in SI No. 25) is not available, applicant to submit either one of the documents:

26.1 A declaration from vehicle manufacturer (OEM) with Vehicle make, maximum speed, axle loads and size of rim used.

26.2 A self-declaration with vehicle make, maximum speed, axle loads and size of rim used

27. Type of tread pattern (lug or rib)

28. Drawing or photograph in triplicate identifying tyre tread pattern, side wall marking and relevant dimensions of inflated tyre mounted on the measuring rim

29. Declared maximum speed of vehicle, in km/h (if applicable) *

30. Maximum gross vehicle weight (GVW) of vehicle *, in kg

* (for N1 category vehicle only) maximum axle load capacity in kg – (front/rear) (strike off whichever is not applicable).’