

**AMENDMENT NO. 1 OCTOBER 2006
TO
IS 15679 : 2006 HOT TAPPING, STOPPLE
PLUGGING/LINE PLUGGING OF PRESSURIZED
NATURAL GAS PIPELINES —
CODE OF PRACTICE**

(Third cover, Forward, para 2) — Insert the following new para after para 2:

'In line with the practices followed in the industry in this field, units are given in FPS system also. For conversion of FPS units to corresponding SI units, the following conversion factors are applicable:

1"[inch] = 25 mm, for nominal sizes; otherwise 1"[inch] = 25.4 mm;
1N/m² = 1 Pa; 1 Bar = 100 kPa; 1 psi = 6.89 kPa and t°C = (t°F – 32) / 1.8

Each system shall be used independently of the other, without combining values in any way'

(Page 2, clause 2.14, line 8) – Insert '(8 mm)' after '1/4' and '(1 500 mm)' after '60"'.

(Page 2, clause 3.2.2, line 1 and wherever appears) – Substitute 'shall' for 'should'.

(Page 5, Table 2, Note) – Substitute '1" = 25 mm' for '1" = 0.254 mm'.

(Page 9, clause 7.6.1, line 4) – Substitute '(25 mm)' for '(2.54 mm)'.

(Page 9, clause 8.1, line 1) – Substitute 'shall' for 'must'.

(Page 11, clause 9.3, line 3) – Substitute '(10 mm)' for '(9.84")'.

(Page 13, clause 9.10, last line) – Insert '(300 mm)' after '12"'.

(PCD 3)