

AMENDMENT NO. 1 APRIL 2016
TO
IS 15696 : 2006 SUPPLIER'S DATA SHEET FOR
POWER BOILER

(Page 2, clause 2.1.2.14) — Insert the following new clauses after 2.1.2.14:

2.1.2.15	Steam water separator (s) (<i>applicable for supercritical units</i>)	
a)	Number	:
b)	Material Specification and composition	:
c)	Design metal temperature, °C	:
d)	Design pressure, kg/cm ² (a)	:
e)	Design standard	:
f)	Design thickness for straight portion, mm	:
g)	Design thickness for dished ends, mm	:
h)	Overall length of separator, mm	:
j)	Outside diameter of separator, mm	:
k)	Maximum permissible temperature differential between any two parts of the separator :, °C:	:
1)	During normal operation	:
2)	During accelerated starting	:
m)	Water capacity at MCR conditions between normal and lowest water level permitted	:

Amendment No. 1 to IS 15696 : 2006

2.1.2.16	Separator drain recirculation pumps (<i>applicable for supercritical units</i>)	
a)	Manufacturer	:
b)	Type	:
c)	No. of pumps provided	:
d)	No. of pumps in operation during start up	:
e)	Capacity of each pump, m ³ /h	:
f)	Total dynamic head, m(wc)	:
g)	Net positive suction head required (NPSHR), m(wc)	:
h)	Efficiency, percent	:
j)	Speed, rpm	:
k)	Materials of construction	:
m)	Maximum operating temperature, °C	:
n)	Casing	:
p)	Impeller	:
q)	Shaft	:
r)	Bearings	:
s)	Type of drive, Motor/Turbo/Other	:
t)	Motor housing, Internal / External	:
u)	Motor rating / Speed, kW / rpm	:
v)	Type of lubrication	:

(Page 13, clause **2.1.18.6**, Sl No. 1) — Substitute ‘Drum/Separator’ for ‘Drum’.

(Page 13, clause **2.2.19.2**) — Substitute ‘Drum/Separator’ for ‘Drum’.