

AMENDMENT NO. 1 JUNE 2025
TO
IS 15709 : 2018 AUTOMOTIVE VEHICLES — RETREADED PNEUMATIC TYRES
FOR PASSENGER CAR — SPECIFICATION
(First Revision)

(Foreword, para 3) — Substitute the following for existing:

‘The following Indian Standards may be referred for valve, valve accessories, terminology of automotive vehicles, Selection and inspection of re-treadable tyre casing, and Retreading of tyres by the pre-cured process:

<i>IS No.</i>	<i>Title</i>
IS 9081 : 2024	Automotive vehicles — Valves and valve accessories for pneumatic tyres — Specification
IS 10939 : 2023	Designation system for tyre tube valves for automotive vehicles
IS 14272 : 2011	Automotive vehicles — Types — Terminology
IS 15524 : 2018	Automotive vehicles — Retreading of tyres by the pre — Cured process
IS 15731 : 2018	Automotive tyres — Selection and inspection of retreadable tyre casing’.

[Page 1, clause 1b)] — Substitute the following for the existing:

‘b) Re-treaded tyres with a speed capability below 120 km/h or above 300 km/h (limit of below 120 km/h is not applicable for bias-ply tyres).’

(Page 1, clause 2) — Substitute the following for the existing:

2 REFERENCES

The standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard are encouraged to investigate the possibility of applying the most recent editions of these standards:

<i>IS No.</i>	<i>Title</i>
IS 10694 (Part 2) : 2009	Automotive vehicles — Rims — General requirements: Part 2 Passenger car <i>(second revision)</i>
IS 15633 : 2022	Automotive vehicles — pneumatic tyres for passenger car vehicles — Diagonal and radial ply — Specification <i>(first revision)</i>

[Page 2, clause 3.21(a), line 4] — Substitute ‘Tables 9 to 14 of IS 15633.’ for ‘Tables 7 to 12 of IS 15633.’

[Page 3, clause 3.21(b), line 4] — Substitute ‘Tables 9 to 14 of IS 15633.’ for ‘Tables 7 to 12 of IS 15633.’

[Page 7, clause 4.5.11(c)] — Substitute the following for the existing:

‘c) The tread wear indicators shall provide a means of indicating, with a tolerance of $^{+0.60}_{-0.00}$ mm when the tread grooves are no longer more than 1.6 mm deep; and’.

(TED 07)

Price Group 1
Publication, BIS, New Delhi