

AMENDMENT NO. 3 FEBRUARY 2026
TO
IS 15804 : 2008 AUTOMOTIVE VEHICLES — WINDSCREEN WIPING AND
WASHING SYSTEM FOR M1 CATEGORY OF VEHICLES — REQUIREMENTS

(*Second cover page, foreword*) — Substitute the following for the existing:

“Automotive Electrical Equipment and Instruments Sectional Committee, TED 11

FOREWORD

This Indian Standard was adopted by the Bureau of Indian Standards, after the draft finalized by the Automotive Electrical Equipment and Instruments Sectional Committee had been approved by the Transport Engineering Division Council.

Windscreen wiping and washing systems are meant to ensure good visibility under adverse weather conditions.

In the formulation of this standard, considerable assistance has been derived from the following:

AIS-019/2001 Automotive vehicles — Windscreen wiping and washing system for M1 category of vehicles
EU Regulation No. 1008/2010 and EU Regulation No. 535/2021

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 2022 ‘Rules for rounding off numerical values (*second revision*)’. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.”

(*Page 1, clause 3.3*) — Substitute the following for the existing:

‘**3.3 Primary Reference Marks** — These are holes, surfaces, marks and identification signs on the vehicle body or chassis. The type of reference mark used and the position of each mark relative to X, Y and Z co-ordinates of the three-dimensional reference grid and to a design ground plane shall be specified by the vehicle manufacturer. These marks may be the control points used for body assembly purposes.’

(*Page 2, clause 3.19*) — Insert the following at the end:

‘**3.20 Intermittent Operation of the Wiper System** — Means an automatic non-continuous mode of operation of the wiper system, where after each full cycle there is a period during which the wipers are stationary in one specific designated halting position.

3.21 Fully Primed System — Means a system which has been activated normally for a period of time and where fluid has been transferred through the pump, tubing and has exited the nozzle(s).

3.22 Vehicle Master Control Switch — Means the device by which the vehicle's on-board electronics system is brought from being switched off, as is the case when a vehicle is parked without the driver being present, to normal operation mode.’

Price Group 1

Amendment No. 3 to IS 15804 : 2008

(Page 2, clause 4.1.1) — Substitute the following for the existing:

‘4.1.1 Every vehicle shall be equipped with a windscreen wiper system which is able to function when the vehicle master control switch has been activated, without any action by the driver other than switching the operating control, needed for starting and stopping the windscreen wiper system, to the on position.

The windscreen wiper system shall consist of one or more wiper arms which shall have wiper blades that are easily replaceable.’

(Page 2, clause 4.1.6) — Substitute the following for the existing:

‘4.1.6 Where the windscreen wiper system is stopped as a result of switching the operating control to the off position, the wiper arm(s) and blade(s) shall return to their position of rest.’

(Page 2, clause 4.1.9.1) — Insert the following at the end:

‘4.1.9.2 During the test, the wiper blade(s) shall remain in contact with the windscreen and complete lift-off shall not be permitted. The wiper blade(s) shall stay in full contact with the windscreen in the area as established in 4.1.2.1 for each complete cycle and any partial lift-off during upwards as well as downwards stroke shall not be permitted.’

(Page 3, clause 4.2.1) — Substitute the following for the existing:

‘4.2.1 Every vehicle shall be fitted with a windscreen- washer system which is able to function when the vehicle master control switch has been activated, which is capable of withstanding the loads produced when the nozzles are plugged, and the system is actuated in accordance with the procedure set out in 5.2.1 and 5.2.2.’

(Page 3, clause 4.2.5) — Insert the following at the end:

‘4.2.6 The windscreen washer system shall have the ability to spray fluid onto the target area of the windscreen, without any trace of leakage, disconnection of any tubing and malfunctioning of any nozzle, at normal conditions when subjected to ambient temperatures between – 10 °C and 80 °C. In addition, when the nozzles are blocked, the system shall also show no signs of leakage and disconnection of any tubing.

4.2.7 The windscreen washer system shall be capable of being manually activated by means of the washer control. In addition, activation and deactivation of the system may also be coordinated and combined with any other vehicle system.’

(Page 3, clause 5.1.3.2) — Substitute the following for the existing:

‘5.1.3.2 The engine, if fitted, shall run at a speed not exceeding 30 percent of the speed corresponding to its maximum power output. However, where this is proven not to be practicable due to specific engine control strategies, for instance in the case of electric hybrid vehicles, a realistic scenario taking into account the engine speeds, periodical absence or complete absence of a running engine during normal driving conditions, shall be determined. Where the windscreen wiper system can meet the requirements without a running engine, the engine does not have to run.’

(Page 3, clause 5.1.4) — Substitute the following for the existing:

‘5.1.4 Compressed air operated or vacuum operated windscreen-wiper systems shall be able to function continuously at the prescribed sweep frequencies whatever the engine speed or engine load or minimum and maximum battery charge levels specified by the manufacturer for normal operation.’