

**AMENDMENT NO. 2 DECEMBER 2008
TO
IS 12592 : 2002 PRECAST CONCRETE MANHOLE
COVER AND FRAME — SPECIFICATION**

(First Revision)

(Page 2, clause 6) — Substitute the following for the existing:

‘DESIGN

The reinforced concrete manhole cover and frame shall be designed in accordance with the provisions of IS 456. If required by the purchaser, the manufacturer shall furnish the specification and drawing (principle given in IS 456 may be followed).

NOTE — If desired by the purchaser the reinforcement details may be verified against the drawings furnished by the manufacturer by breaking a cover/frame.’

[Page 3, Table 1 (see also Amendment No. 1)] — Substitute the following for the existing values of dimension ‘F’ in col 8 for the corresponding Grade Designation LD-2.5 under col 1 and Clear Opening in Frame, A under col 3:

Grade Designation (1)	Clear Opening in Frame, A (3)	F Nominal (8)
LD-2.5	450 × 600	558 × 708
LD-2.5	400 × 400 450 × 450	508 × 508 558 × 558
LD-2.5	370 450 500 560	478 558 608 668

[Page 4, clause 7.4.2, para 2, second sentence (see also Amendment No. 1)] — Substitute the following for the existing:

Amend No. 2 to IS 12592 : 2002

‘Exposed surface of mild steel sheet shall be given suitable treatment either with hot dip galvanizing or anti-corrosive paint or coating, as specified by the purchaser.’

(Page 4, clause 8, para 1, second sentence) — Substitute the following for the existing:

‘The lifting device shall be protected from corrosion by hot dip galvanizing or anti-corrosive paint or coating as specified by the purchaser or shall be made of naturally corrosion resistant metal rods.’

[Page 4, clause 9.3, first sentence (see also Amendment No. 1)] — Substitute ‘covers’ for ‘units’.

(CED 20)

Reprography Unit, BIS, New Delhi, India