

**AMENDMENT NO. 1 FEBRUARY 2009
TO
IS 2720 (PART 28) : 1974 METHODS OF
TEST FOR SOILS**

**PART 28 DETERMINATION OF DRY DENSITY OF SOILS,
IN-PLACE, BY THE SAND REPLACEMENT METHOD**

(First Revision)

(Page 20, Annex B, clause B-2.4) — Substitute the following for the existing clause:

‘The wet gravel shall be placed in an oven and the oven-dry weight (W'_g) and water content (w_g) shall be determined.’

(Page 20, Annex B, clause B-3.1) — Substitute the following for the existing under SI No. (d) to (j):

- | | |
|---|--------------------------------------|
| d) Wet density of minus 4.75 mm soil | $= \frac{(b)}{(c)}$ |
| e) Dry weight of minus 4.75 mm soil | $= \frac{(b)}{1 + w_s/100}$ |
| f) Dry density of minus 4.75 mm soil | $= \frac{(d)}{1 + w_s/100}$ |
| g) Dry weight of total material (soil + gravel) | $= W'_g + (e)$ |
| h) Water content (w_T) of total material, percent | $= \frac{W_w - (g)}{(g)} \times 100$ |
| j) Percentage of gravel in the material on a dry weight basis | $= \frac{W'_g}{(g)} \times 100$ |

(CED 43)