

AMENDMENT NO. 1 AUGUST 1982
TO
IS : 2720 (Part II)-1973 METHODS OF TEST
FOR SOILS
PART II DETERMINATION OF WATER CONTENT
(Second Revision)

Alterations

(*Page 4, clause 4.1*):

a) *Informal table, first column* — Substitute the following for the existing matter:

‘ 425 μ m IS Sieve
2-mm IS Sieve
4.75-mm IS Sieve
9.50-mm IS Sieve
19-mm IS Sieve
37.5-mm IS Sieve ’

b) *Note 1* — Substitute the following for the existing note:

‘ NOTE 1 — For sizes of sieves, see IS: 460 (Part I)-1978† ’.

(*Page 4, foot-note with ‘ † ’ mark*) — Substitute the following for the existing foot-note:

‘ †Specification for test sieves: Part I Wire cloth test sieves (*second revision*). ’

(*Page 8, clause 16.1*):

a) *Informal table, first column* — Substitute the following for the existing matter:

‘ 2-mm IS Sieve
19-mm IS Sieve ’

b) *Note 1* — Substitute the following for the existing note:

‘ NOTE 1 — For sizes of sieves, see IS : 460 (Part I)-1978* ’.

(*Page 8, foot-note with ‘ * ’ mark*) — Substitute the following for the existing foot-note:

‘ *Specification for test sieves: Part I Wire cloth test sieves (*second revision*). ’

(Page 14, clause 28.3, Note) — Substitute the following for the existing note:

' Norm — If the sample is bulky, reverse the above placement, that is, put the sample in the chamber and the absorbent in the cup. In the case of clayey soils and pastes, place the 3 smaller and one bigger steel balls in the body along with the absorbent. '

(Page 15, clause 28.4, Note) — Substitute the following for the existing note:

' Norm — When steel balls are used, place the three smaller and one bigger balls in the body along with the absorbent and the sample in the cup and seal up the unit as usual. Hold the rapid moisture meter vertical with the cup downwards and allow the absorbent with the balls to fall into the cup. Shake the unit up and down vigorously in this position for about 15 seconds. Now invert the unit and allow the material to fall into the body. Now holding the unit horizontal rotate it for 10 seconds so that the balls rolled round the inside circumference of the body. Rest for 20 seconds. Repeat the above cycle until the gauge reading is constant (usually this takes 4 to 8 min). Note the reading as usual. '

(BDC 23)