

AMENDMENT NO. 6 JUNE 2026
TO
IS 2796 : 2017 MOTOR GASOLINE — SPECIFICATION
(Sixth Revision)

[Page 1, clause 1.1, (see also Amendment No. (5)] — Substitute the existing:

‘1.1 This standard prescribes the requirements and methods of sampling and test methods for two octane grades each of Motor Gasoline (earlier also known as Motor Spirit) and up to 10 percent ethanol blended motor gasoline (E10) under each of BS IV and BS VI categories suitable for use as a fuel in the automobile spark-ignition internal combustion engines of vehicles complying with BS IV and BS VI emission norms respectively. This standard also covers lower RON motor gasoline (earlier also known as motor spirit) meant only as a blending component for blending of ethanol blended fuel.’

[Page 4, Table 1, Sl No. (vi), col (2)] — Substitute ‘Motor octane number (MON)¹³, Min.’ for ‘Motor octane number (MON), Min.’.

[Page 4, Table 1, Sl No. (x), col (2), (see also Amendment No. (2)] — Substitute ‘Reid vapour pressure (RVP)¹³ at 37.8°C, kPa, Max’ for ‘Reid vapour pressure (RVP) at 37.8 °C, kPa, Max’.

[Page 4, Table 1, Sl No. (xi), col (2)] — Substitute ‘Vapour lock index (VLI)¹³, Max’ for ‘Vapour lock index (VLI), Max’.

(Page 5, Note 13 (see also Amendment No. (5)] — Substitute the existing:

¹³BS VI Motor Gasoline intended for ethanol blending (E20, E22, E25, E30 and E85) shall comply with all the specifications mentioned in col (4) of Table 1, except RON, MON, RVP and VLI. These parameters may vary from the specified value. However, the final EBMG fuels viz., E20, E22, E25, E30 and E85 shall confirm to the mentioned, applicable limits of RON, MON, RVP and VLI in the respective Indian Standard. The Parameters of RON, MON, RVP and VLI for E 20 to E30 and RVP and VLI for E85 shall form part of the Certificate of Analysis (CoA) for respective fuel which shall be tested and confirmed either at refinery or at manufacturing location which conducts the test with lower specification BSVI gasoline and respective Ethanol percentage. If any of the above parameters meet the base IS 2796 specification those parameters need not be retested.’
