

**AMENDMENT NO. 3 JANUARY 2022**  
**TO**  
**IS 2796 : 2017 MOTOR GASOLINE — SPECIFICATION**  
**( *Sixth Revision* )**

*(Page 2, clause 4.1, para 1, line 4)* — Delete ‘(99.5 percent, v/v)’

*(Page 2, clause 4.1, para 2, line 2)* — Substitute ‘ $10 \pm 1.0$  percent (v/v)’  
for ‘ $9.75 \pm 0.25$  percent (v/v)’

*(Page 2, clause 4.1, para 2, line 3)* — Delete ‘(99.5 percent, v/v)’

*(Page 5, Table 1, Note 8, line 4)* — Substitute ‘9.0 to 11.0’ for ‘9.5 to 10.0’

*(Page 13, Annex C, clause C-10)* — Substitute the following for the existing:

**C-10 PRECISION AND BIAS**

**C-10.1** In the absence of calibration plot the value observed in aqueous phase can be calculated to the nearest percentage volume as per the under mentioned precision levels.

**C-10.2** Based on the field test data, it was observed that a maximum of 9.0-10.0 ml (average) of ethanol content is extracted in to the aqueous phase as against 10.0 ml ethanol added in ethanol doped motor gasoline.

**C-10.3** The standard deviation of the test results at 5 percent ethanol content by volume is  $\pm 0.3$  percent and for 10 percent ethanol content by volume is  $\pm 0.50$  percent.

**C-10.4** Considering the precision of the graduated glass cylinder, the maximum possible measurement can be treated as 10.0 percent by volume with standard deviation of  $\pm 1.0$  percent. Thus the repeatability under the method is as under:

| <i>Percentage</i> | <i>Repeatability / Reproducibility</i> |
|-------------------|----------------------------------------|
| 5 percent (v/v)   | 0.5 ml (Approximately)                 |
| 10 percent (v/v)  | 1.0 ml (Approximately)                 |