

AMENDMENT NO. 1 JANUARY 1999
TO
IS 2969 : 1974 METHOD FOR DETERMINATION OF
OIL CONTENT OF JUTE YARN AND FABRICS
(First Revision)

FOREWORD

(This amendment has been issued to accommodate the use of *n*-hexane as an extracting reagent.)

(*Page 3, clause 2.1*) — Substitute the following for the existing:

'2.1 A known amount of the sample is extracted with trichloroethylene or light petroleum or *n*-hexane in Soxhlet apparatus. The solvent is removed by distillation and the extract is weighed. The mass of the extract is expressed as a percentage of the oven dry mass of the extracted specimen or conditioned mass of test specimen before extraction.'

(*Page 5, clause 7.2.2*) — Insert 7.2.3 as under:

'7.2.3 *n*-hexane'

(*Page 5, clause 8.1.1*) — Substitute the following for the existing:

'8.1.1 Take a test specimen, weigh it to the nearest milligram and place it in the thimble of the Soxhlet apparatus. Take about 100 ml of trichloroethylene or light petroleum or *n*-hexane in the extraction flask previously cleaned, dried and weighed correct to 1 mg. Extract the test specimen for 1.5 to 2 hours with a minimum of 10 siphonings per hour. Disconnect the apparatus.'

(*Page 5, clause 8.1.2*) — Substitute the following for the existing:

'8.1.2 Recover the excess of the solvent by heating the flask in a water-bath, maintained at 90 to 95°C if the solvent is trichloroethylene, 60 to 65°C if the solvent is light petroleum and 70 to 75°C if the solvent is *n*-hexane, and simultaneously allowing a stream of air to pass through the flask by means of a tube terminating just below its neck. Remove all traces of moisture by heating the flask at 105 ± 3°C for 30 min. Weigh the flask and determine the mass of the extract (M_e) correct to 1 mg.'

Amend No. 1 to IS 2969 : 1974

(*Page 5, clause 8.2.1*) — Substitute the following for the existing:

'**8.2.1** Take a test specimen, weigh it to the nearest milligram and place it in the thimble of the Soxhlet apparatus. Take about 150 ml of trichloroethylene or light petroleum or *n*-hexane in the extraction flask previously cleaned, dried and weighed correct to 1 mg. Extract the test specimen for 1.5 to 2 hours with a minimum of 6 siphonings per hour. Disconnect the apparatus.'

(TX 05)