

**AMENDMENT NO. 1 MARCH 1997
TO
IS 13136 : 1991 ARMS AND AMMUNITION — RIFLE —
AIR RIFLE SPRING OPERATED — SPECIFICATION**

(Page 8, Fig. 4) — Insert the following in Fig. 4:

Marking	Dimensions ϕA
4.5	0 4.424 - 0.003
5.5	0 5.424 - 0.003

Tolerance — ± 0.5 mm on whole number and ± 0.1 mm on decimals unless otherwise specified.

Material — Steel conforming to IS 3748 : 1990.

Hardness — 700 HV Min.

(Page 8, Fig. 5) — Insert the following in Fig. 5:

Marking	Dimensions ϕA	Rifle For
L0.44	0 4.444 - 0.003	4.5 mm (.171)
H4.48	0 4.484 - 0.003	
1.5.44	0 5.444 - 0.003	5.5 mm (.22)
H5.48	0 5.484 - 0.003	

Tolerance — ± 0.5 mm on whole numbers and ± 0.1 mm on decimals unless otherwise specified.

Material — Steel conforming to IS 3748 : 1990.

Hardness — 700 HV Min.

Amend No. 1 to IS 13136 : 1991

(Page 8, Fig. 6) — Insert the following in Fig. 6:

Rifling	ϕA	B	ϕC
Accept 4.5 mm (.177)	0 4.437 - 0.003	0.605 ± 0.002	4.612 ± 0.003
5.5 mm (.22)	0 5.437 - 0.003	0.605 ± 0.002	5.612 ± 0.003
Rifling NOT GO (Depth) 4.5 mm (.177)	0 4.437 - 0.003	0 0.55 - 0.05	4.68 ± 0.003
	0 4.457 - 0.003	0 0.55 - 0.05	4.68 ± 0.003
	0 4.477 - 0.003	0 0.55 - 0.05	4.68 ± 0.003
5.5 mm (.22)	0 5.437 - 0.003	0 0.55 - 0.05	5.68 ± 0.003
	0 5.457 - 0.003	0 0.55 - 0.05	5.68± 0.003
	0 5.477 - 0.003	0 0.55 - 0.05	5.68 ± 0.003
Rifling NOT GO (width) 4.5 mm (.177)	0 4.44 - 0.003	0.62 ± 0.002	0 4.60 - 0.005
5.5 mm (.22)	0 5.44 - 0.003	0.62 ± 0.002	0 5.60 - 0.005

Tolerance — ± 0.5 mm on whole numbers and ±0.1 mm on decimals unless otherwise specified.

Material — Steel conforming to IS 3748 : 1990 .

Hardness — 700 *HVMin*.

(Page 15, Annex C) — Insert 'IS 3748 : 1990 Tool and die steels (*second revision*)' suitably after 'IS 3601 : 1984'.

(LM 08)