

AMENDMENT NO. 1 MARCH 1999
TO
IS 13187 : 1991 ROAD TANKERS FOR LIGHT
PETROLEUM PRODUCTS — SPECIFICATION

(Page 7, clause 7.3) — Insert the following new clause after 7.3:

7.4 An appropriate spark arrestor may be provided at suitable place to avoid fire at outlet end of exhaust pipe of the vehicle.'

(Page 7, clause 9) — Substitute the following for the existing text:

'9 TESTING

9.1 Hydraulic Pressure Test — Each compartment of the tanker shall be subjected to hydrostatic pressure test of 0.316 kgf/cm² at the top and maintained for a period of not less than 1 h. The compartment shall not show any signs of leakage or drop of pressure during the test. The tank shall be cleaned and dried by blowing dry air after testing to prevent corrosion.

9.2 Other components like valves, fittings, accessories and joints shall be tested in accordance with the relevant codes of construction.

9.3 The testing shall be done by a competent person and a suitable record shall be kept.'

(Page 7, clause 10) — Substitute the following for the existing text:

"10 MARKING

10.1 Each tanker used for transportation of petroleum shall, whether loaded or empty, be conspicuously marked with Pictorial Markings, as relevant in accordance with IS 1260 (Part 1) : 1973 'Pictorial markings for handling and labelling of goods: Part 1 Dangerous goods'.

10.2 The common name of the flammable liquid being transported, for example, 'MOTOR SPIRIT, KEROSENE', etc of appropriate size shall also be marked along with the Pictorial Markings."

(HMD 17)