

AMENDMENT NO. 1 DECEMBER 2025
TO
IS 13363 : 2017 AUTOMOTIVE VEHICLES — AIR BRAKE SYSTEMS —
PERFORMANCE REQUIREMENTS FOR DRAIN VALVES
(First Revision)

(Page 1, clause 4.1) — Substitute the following for the existing:

‘4.1 Working Conditions

Working medium:	Air
Normal working pressure:	800/1 000 kPa (8/10 bar)
Maximum working pressure:	1 250 kPa (12.5 bar)
Thermal range of operation:	
Normal:	10 °C to 50 °C
Extreme:	– 40 °C to 80 °C’.

(Page 1, clause 5.4) — Substitute the following for the existing:

‘5.4 Test requirement shall be as agreed to between the manufacturer and the purchaser. In the absence of any such agreement the endurance test as given below shall be carried out on the specimen.

Endurance test — The unit shall be subjected to an endurance test of 2 000 cycles under the following conditions:

- a) Volume for reservoir for which is screwed 5 litre;
- b) Air pressure applied 1 200 kPa (12 bar); and
- c) Frequency 12 cycles/h’.

(Page 2, clause 5.8) — Substitute the following for the existing:

‘5.8 Over Pressure Test

The unit shall be subjected to air pressure of 1 900 kPa (19 bar) for 10 s. The valve shall then pass the tests as per **5.2** and **5.3.**’

(Page 2, clause 5.9) — Substitute the following for the existing:

‘5.9 Water Spray Test

Test requirement shall be as agreed to between the manufacturer and the purchaser. In the absence of any such agreement the test specified in **5.9.1** shall be carried out on the specimen.

5.9.1 The components shall be subjected to a driving rain test as per IS 9000 (Part 16). The component shall reveal no defects after the test.’

Price Group 1

Amendment No. 1 to IS 13363 : 2017

(Page 2, clause 5.10) — Substitute the following for the existing:

‘5.10 Vibration Test

The unit shall be subjected to a vibration acceleration level of 5 g at 60 Hz, for 8 h in actual installation orientation or as mutually agreed to between the supplier and the purchaser. At the end of the test, the unit shall not have any structural damage. Further, the unit shall meet test as per **5.2** and **5.3.**’

(TED 04)

Publication, BIS, New Delhi