

**AMENDMENT NO. 2 JANUARY 1996
TO
IS 13457 : 1992 PESTICIDE — DELTAMETHRIN WP —
SPECIFICATION**

(*Page 1, clause 2*) — Substitute '1070 : 1992 Reagent grade water (*third revision*)' for '1070 : 1977 Water for general laboratory use (*second revision*)'.

(*Page 1, clauses 3.1.1 and 3.1.2*) — Substitute 'deltamethrin technical' for 'deltamethrin, technical'.

(*Page 1, clause 3.3.1*) — Substitute the following for the existing:

'3.3.1 Deltamethrin content shall be declared. When tested by the method prescribed in Appendix A of IS 12005 : 1987, the observed deltamethrin content, percent (m/m) of any of the samples shall not differ from the declared nominal value by more than the tolerance limits indicated below (*see also clause 6*):

<i>Nominal Value, Percent</i>	<i>Tolerance Limit, Percent</i>
Up to 9	$\begin{cases} + 10 \\ - 5 \end{cases}$
Above 9 and below 50	± 5
50 and above	$\begin{cases} + 5 \\ - 3 \end{cases}$

(*Page 1, clause 4*) — Substitute the following for the existing:

'4 PACKING

The material shall be packed in HM-HDPE or mild steel containers provided with LDPE liners of thickness not less than 0.062 mm. It shall also conform to the general requirements given in IS 8190 (Part 2) : 1988.'

(*Page 1, clause 5*) — Add the following at the end:

'5.1 BIS Certification Marking

The product may be marked with Standard Mark.

Amend No. 2 to IS 13457 : 1992

5.1.1 The use of the Standard Mark is governed by the provisions of Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.'

[*Page 2, Table 1 (see also Amendment No. 1)*] — Substitute the following for the existing:

Sl No.	Characteristic	Requirement	Method of Test, Ref to	
			Appendix of IS 12005 : 1987	Cl No. of of IS 6940 : 1982
(1)	2)	(3)	(4)	(5)
i)	Deltamethrin content, percent by mass	Nominal value as declared on the container (see 3.3.1)	A	—
ii)	Sieving (material passing through 45-micron IS Sieve), percent by mass, <i>Min</i> [see IS 460 (Part 1) : 1985]	99.0	—	11.1
iii)	Suspensibility, percent by mass, <i>Min</i>	75.0	—	11.2
iv)	Acidity (as H ₂ SO ₄) or alkalinity (as NaOH), percent by mass, <i>Max</i>	0.5	—	11.3
v)	Wettability in seconds, <i>Max</i>	120	—	11.4

(*Page 2, clause 7.3*) — Substitute '1070 : 1992' for '1070 : 1977'.

(FAD 1)

Reprography Unit, BIS, New Delhi, India