

**AMENDMENT NO. 3 MARCH 2002
TO
IS 2512 : 1978 SPECIFICATION FOR MINERS' CAP-
LAMP BATTERIES (LEAD-ACID TYPE)**

(First Revision)

(Page 4, clause 1.1, last line) — Substitute the following for the existing:
'nominal capacity of 9 Ah/12 Ah for use with miners' cap-lamps'.

(Page 9, clause 6.8.4) — Add the following at the end:

'For batteries suitable for bulb ratings above 0.8 A, up to and including 1.0 A, the discharge test conducted according to 6.8.3 shall have a capacity not less than 12 Ah or give a duration not less than 12 hours at a discharge current of 1.0A.'

(Page 10, clause 6.9.5, line 3, after 0.8 A) — Add the following:

'for 9 Ah battery and 1.0 A for 12 Ah battery'.

(Page 10, clause 6.9.7, line 2, after 0.8 A) — Add the following:

'for 9 Ah battery and 1.0 A for 12 Ah battery'.

(Page 10, clause 6.9.8, line 2) — Add the following at the end:

'for batteries suitable for a bulb rating of 4 V, 1.0 A, the discharge current under 6.9.2(a), 6.9.5 and 6.9.7 shall be at 1.0 A in lieu of 0.8 A.'

(Page 10, clause 6.10.4) — Add the following at the end:

'NOTE — For cap-lamp batteries used with 4 V, 1.0 A bulb, the continuous discharge (under 6.10.4) should be at 1.0 A in lieu of 0.8 A.'

(ETD 11)