

AMENDMENT NO. 1 FEBRUARY 2026
TO
IS 4508 : 2024 OPEN ENDED SLUGGING WRENCHES (SPANNERS) —
SPECIFICATION
(Second Revision)

(Page 1, clause 4) — Substitute the following for the existing:

‘4 MATERIAL

The material shall be suitable alloyed or unalloyed steel, meeting the requirements laid down in 5. Some of the suitable steel grades are listed in Table 2.’

(Page 4, Table 2) — Substitute the following for the existing:

‘Table 2 Chemical Composition of Steel Grades

(Clause 4)

Sl No.	Grade	C	Si	Mn	S	P	Cr	V
					(Max)	(Max)	(Min)	(Min)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	Chrome vanadium	0.28 <i>Min</i>	0.40 <i>Max</i>	0.40 <i>Min</i>	0.040	0.040	0.30	0.07
ii)	40Cr	0.37 <i>Min</i>	0.17 to 0.37	0.50 to 0.80	0.040	0.040	0.80	—
iii)	35C8	0.30 to 0.40	0.15 to 0.35	0.60 to 0.90	0.040	0.040	—	—
iv)	45C8	0.40 to 0.50	0.15 to 0.35	0.60 to 0.90	0.040	0.040	—	—

NOTE — Composition limit is in weight percent maximum, unless shown otherwise.