

AMENDMENT NO. 1 JANUARY 2026
TO
IS 4509 : 2024 RING SLUGGING WRENCHES (SPANNERS)— SPECIFICATION
(Second Revision)

(Page 1, clause 4) — Substitute the following for the existing:

‘The material shall be suitable alloyed or unalloyed steel, meeting the requirements laid down in 5. Some of the suitable steel grades are listed in Table 2.’

(Page 4, Table 2) — Substitute the following for the existing:

Sl No.	Grade	C	Si	Mn	S (Max)	P (Max)	Cr (Min)	V (Min)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
i)	Chrome vanadium	0.28 <i>Min</i>	0.40 <i>Max</i>	0.40 <i>Min</i>	0.040	0.040	0.30	0.07
ii)	40Cr	0.37 <i>Min</i>	0.17 to 0.37	0.50 to 0.80	0.040	0.040	0.80	Nil
iii)	35C8	0.30 to 0.40	0.15 to 0.35	0.60 to 0.90	0.040	0.040	Nil	Nil
iv)	45C8	0.40 to 0.50	0.15 to 0.35	0.60 to 0.90	0.040	0.040	Nil	Nil

NOTE — Composition limit in weight percent maximum, unless shown as a range or a minimum.