

AMENDMENT NO. 1 SEPTEMBER 2026
TO
IS 4651 (PART 3) : 2020 PLANNING AND DESIGN OF PORTS AND HARBOURS —
CODE OF PRACTICE
PART 3 LOADING
(Second Revision)

(Page 5, clause 6.2.2.1) — Insert the following at the end:

‘6.2.2.2 The fender reaction shall be obtained for ultimate berthing energy of 2E (that is, 2 times calculated berthing energy).’

(Page 5, clause 6.3.2, line 7) — Substitute ‘Mooring loads are to be calculated only for wind speed of about 30 m/s for mooring analysis, for liquid and gas vessels, corresponding to 10 min average, and not for the storm wind as detailed in IS 875 (Part 3). For container vessels, mooring loads are to be calculated for wind speed of 15 m/s, subject to the condition that these vessels are de-moored from the berth beyond wind speed of 15 m/s. The wind speed is calculated as wind speed corresponding to 10 min average.’ *for* ‘Mooring loads are to be calculated only for wind speed of about 30 m/s for mooring analysis and not for the storm wind as detailed in IS 875 (Part 3).’

(Page 8, clause 6.7.5.1(a), line 4) — Substitute ‘100’ *for* ‘1 000’.

(Page 10, clause 6.7.7, last para) — Substitute the following for the existing:

‘The recommended return period is 100 years for wave force estimation and to fix the top level. For important structures like nuclear power plants and defence jetty, the return period of 1 000 years is recommended to fix top level of the jetty.’