

AMENDMENT NO. 1 JANUARY 1981
TO
IS:473S-1968 SPECIFICATION FOR ARM SHAFT CAMS FOR
SEWING MACHINES FOR HOUSEHOLD PURPOSES

Alterations

(Page 4, clause 2.1, line 2) - Substitute 'grade 15' for 'grade 20'.

(Page 4, clauses 4.1 and 4.2) – Substitute the following for the existing clauses:

'4.1 The diameter variation on the cam shall not be more than 0.01 mm from its specified value at any point on the cam.

4.2 The error in parallelism of cam face with respect to the bore axis shall not exceed 0.1 mm per 100 mm,

4.3 The error in squareness of shoulder face with respect to the cam surface shall not exceed 0.3 mm per 100 mm.'

(Page 4, clause 6.1, line 2) - Substitute 'trade-mark, if required' for 'trade-mark'.

(Page 6, clause 7.1) – Substitute the following for the existing clause:

*7.1 Each arm shaft cam shall be given a suitable anti-rust coating or wrapped in vapour phase inhibitor paper (commonly known as VPI paper). The wrapped arm shaft cam shall be securely packed in accordance with the best prevalent trade practice. Each package shall bear manufacturer's name, trade-mark and description of contents.'

(Page 6, clause 7.1.1, line 1) - Substitute 'packages' for 'cartons'.

(EDO 34)