

AMENDMENT NO. 1 JULY 2025
TO
IS 17634 : 2022 STORAGE UNITS — SPECIFICATION

(Page 2, clause 3.16) — Insert the following at the end:

‘3.17 Overturn — Condition where an unrestricted storage unit does not return to its upright normal position.

3.18 Unit — Complete furniture intended to be tested. Example, bookcases, wardrobes, cabinets, wall-mounted or exterior-mounted elements, free-standing and mobile pedestals, lateral and vertical files.’

(Page 2, clause 5) — Substitute the following for the existing:

5 DIMENSIONS

‘The dimensions shall be as agreed to between the manufacturer and the purchaser or as declared by the manufacturer as per furniture design requirements.’

(Page 2, clause 6, title) — Substitute the following for the existing:

‘RAW MATERIALS REQUIREMENTS’

[Page 2, clause 6.1(a)] — Delete.

(Page 2, clause 6.1, last para) — Delete.

(Page 2, clause 6.2, para 1) — Substitute the following for the existing:

‘For fabric and/or leather (synthetic and natural) surfaces, the raw material samples shall be tested for the following tests (as applicable) and shall conform the minimum performance requirements specified in IS 17637.’

(Page 2, clause 6.2, last para) — Delete.

(Page 2, clause 6.2) — Insert the following at the end:

‘6.3 If the raw material has already been tested for the applicable requirements mentioned in 6.1 and 6.2, then no re-testing shall be carried out with the final product.’

(Page 3, clause 7.2.1.2, para 4) — Substitute the following for the existing:

‘Carry out the inspection and assessment according to 8.4. Also, the maximum deflection of visual and non-visual shelves shall be as followed:

- a) For visual shelves – 5 mm/m; and
- b) For non-visual shelves – 7 mm/m.

NOTE — Visual shelves are the shelves that are visible even in closed storage unit or in storage unit without doors. All other shelves are to be considered as non-visual shelves.’

(Page 4, clause 7.2.3.2, last para) — Substitute the following for the existing:

‘Carry out the inspection and assessment according to 8.4. Also, the maximum deflection of visual and non-visual cloth rails shall be as followed:

- a) For visual cloth rail – 10 mm/m; and
- b) For non-visual cloth rail – 15 mm/m.

NOTE — Visual cloth rails are the cloth rails that are visible even in closed storage unit or in storage unit without doors. All other cloth rails are to be considered as non-visual cloth rails.’

Amendment No. 1 to IS 17634 : 2022

(Page 21, clause **7.5.1**, para 1) — Insert the following at the end:

‘Units intended to be attached to the building structure shall only be tested according to **7.5.9**.’

(Page 21, clause **7.5.1**, last para) — Insert the following at the end:

‘The potential energy shall be determined by multiplying the total mass (kg) of the unit, gravity (m/s^2) and the height (m) above the floor to the centre of gravity. The total mass is the mass of the unit loaded according to Table 9.’

(Page 33, clause **9.1**) — Insert the following at the end:

- ‘e) Performance category that is domestic, institutional light and institutional heavy; and
- f) Units intended to be attached to the building structure, if applicable.’

(Page 34, clause **A-4**, para 1) — Substitute the following for the existing:

‘All the applicable tests need not to be carried out on the same sample and may be performed on a series of units at the manufacturer's discretion, unless specified within a given test(s) of this standard. The number of samples for testing may vary depending on the decision regarding the sequence of testing.’