

AMENDMENT NO. 1 JUNE 2024
TO
IS 17681 : 2022 BOTTLED WATER DISPENSERS — SPECIFICATION

[Page 1, clause 1.2 (c)] — Substitute the following for the existing:

‘c) Floor standing water dispenser.’

(Page 1, clause 1.3) — Substitute the following for the existing:

‘The product covered in this standard can have following combinations for dispensing cold water, hot water, and water at room temperature:

- a) Cold only;
- b) Hot only;
- c) Room temperature only;
- d) Hot and room temperature;
- e) Cold and room temperature;
- f) Cold and hot;
- g) Cold, hot, and room temperature;
- h) Water dispenser with an in-built refrigerator cabinet; and
- j) Water dispenser with storage compartment with cabinet or without cabinet.

NOTE — The above list is indicative only. Product may have other combinations also.’

(Page 2, fig. 3, Title) — Substitute the following for the existing:

‘FLOOR STANDING —WITH/WITHOUT REFRIGERATION CABINET.’

(Page 3, clause 3.11) — Substitute the following for the existing:

‘**3.11 Stable Operating Conditions** — Condition in which the appliance mean temperatures and energy consumption comply with the relevant stability requirements as defined in this standard (see 8.6).’

(Page 3, clause 4.4, first para, line 13) — Substitute ‘product’ for ‘frame’.

(Page 4, clause 5.2, first sentence) — Substitute the following for the existing:

‘The operation of the compressor shall be controlled with the help of thermostat (electronic or electromechanical) to maintain the water temperature within the limits of application.’

(Page 4, clause 8.2) — Substitute the following for the existing:

‘8.2 Electrical Power Supply

The tests shall be conducted at the rated voltage as indicated on the nameplate.

When a voltage range is indicated on the nameplate, the rated (test) voltage shall be the mean of the upper and lower limits of the range.

All the tests specified in this standard shall be carried out at the rated frequency. For a water dispenser where the rated frequency is not specified, the tests shall be carried out at 50 Hz.’

Price Group 2

Amendment No. 1 to IS 17681 : 2022

(Page 4, clause 8.5, second sentence) — Substitute the following for the existing:

‘Units shall be switched ON after all the internal parts have achieved the ambient temperature of the test after a minimum soaking period of 2 h with water inside the tank.’

(Page 4, clause 8.6) — Substitute the following for the existing:

‘8.6 Stable Operating Conditions

The water dispenser shall be kept running till equilibrium conditions are achieved. The dispenser shall be kept under this condition for minimum 30 min and water temperature shall be recorded at an interval of 5 min to establish this. The average temperature recorded shall be within $\pm 2^\circ\text{C}$ during this period.’

(Page 5, Table 1, Title) — Substitute the following for the existing:

‘Table 1 Cooling Capacity Test — Table Top, Floor Standing without Refrigeration Cabinet

(Clause 10.1.1, 10.4, 10.5, and 10.6)’

(Page 5, clause 10.1.1.1 (b), Note) — Substitute the following for the existing:

‘NOTE — During the water withdrawal if the compressor trips then wait till compressor gets restarted. The compressor off time shall not be considered in the test time.’

(Page 6, Table 2, Title) — Substitute the following for the existing:

‘Table 2 Cooling Capacity Test — Floor Standing with Refrigeration Cabinet

(Clause 10.1.2, 10.4, 10.5, and 10.6)’

(Page 6, clause 10.2) — Substitute the following for the existing:

‘10.2 Maximum Operating Condition Test (Environmental)

10.2.1 Climate Class — Tropical (T) for T class rated product

10.2.1.1 Temperature

- a) Ambient temperature 43°C ; and
- b) Water temperature 35°C .

10.2.1.2 Method of test

- a) After stabilizing as mentioned in 8.6, the dispenser shall be operated up to 1 h at a full capacity of the loaded bottle in the main tank and beverage/water filled in metal cans/ PET bottles in cabinet in case of refrigeration cabinet model (Beverage/water filled in 6 to 8 metal cans/water PET bottles of 500 ml each shall be used);
- b) Cold and plain water shall be withdrawn at regular intervals of 10 min at rated cooling capacity and the temperature shall be recorded; and
- c) Simultaneously, the air temperature in the cabinet shall be recorded by the suitable temperature measuring device (see 9.1.1).

10.2.1.3 Outlet cold water temperature

The cold water temperature shall be less than or equal to 23°C at rated outlet flow.

The refrigeration cabinet air temperature shall be minimum 5°C less than ambient temperature.

Amendment No. 1 to IS 17681 : 2022

10.2.2 Climate Class — Normal (N) for N class rated product

10.2.2.1 Temperature

- a) Ambient temperature 32 °C; and
- b) Water temperature 28 °C.

10.2.2.2 Method of test

- a) After stabilizing as mentioned in 8.6, the dispenser shall be operated up to 1 h at a full capacity of the loaded bottle in the main tank and beverage/water filled in metal cans/PET bottles in cabinet in case of refrigeration cabinet model (Beverage/water filled in 6 to 8 metal cans/water PET bottles of 500 ml each shall be used);
- b) Cold and plain water shall be withdrawn at regular intervals of 10 min at rated cooling capacity and the temperature shall be recorded; and
- c) Simultaneously, the air temperature in the cabinet shall be recorded by the suitable temperature measuring device (see 9.1.1).

10.2.2.3 Outlet cold water temperature

The cold water temperature shall be less than or equal to 23 °C at rated outlet flow.

The refrigeration cabinet air temperature shall be minimum 5 °C less than ambient temperature.’

(Page 6, clause 10.3.1) — Substitute the following for the existing:

‘10.3.1 At High Voltage

After stabilization as per rated climate class, the bottled water dispenser shall be operated at high voltage that is, 110 percent of rated voltage for 2 h. The thermostat shall be disabled during the test. The compressor shall not trip during the test.’

(Page 7, clause 10.3.2) — Substitute the following for the existing:

‘10.3.2 At Low Voltage

After stabilization as per rated climate class, the bottled water dispenser shall be operated at low voltage that is, 90 percent of rated voltage for 2 h. The thermostat shall be disabled during the test. The compressor shall not trip during the test.’

(Page 7, clause 10.4.1 (a), line 3) — Substitute ‘or’ for ‘and’.

(Page 7, clause 10.7) — Substitute the following for the existing:

‘10.7 Door Opening and Closing Test

The bottled water dispenser with refrigeration cabinet shall be subjected to 3 000 cycles of the door opening and closing of a minimum 5 cycles per min. Each cycle shall comprise of 1 opening and 1 closing. After this test, the dispenser shall qualify the door seal test (see 10.8) and there shall be no failure of the hinges.’

Amendment No. 1 to IS 17681 : 2022

(Page 8, Table 3) — Substitute the following table for the existing table:

‘Table 3 Pull Down Test

(Clause 10.9)

Sl No.	Condition	Ambient temperature °C	Inlet Water Temperature °C	Pull Down °C
(1)	(2)	(3)	(4)	(5)
i)	Tropical (T)	43 ± 1	35 ± 1	Outlet cold water temperature: < 23
ii)	Normal (N)	32 ± 1	28 ± 1	Outlet cold water temperature: < 18’

(Page 8, clause **10.9.2**) — Substitute the following for the existing:

‘10.9.2 Requirements

The measured water temperature shall be as per Table 3 within 60 min that is, maximum pull down time shall be 60 min.’

(MED 03)

Publication, BIS, New Delhi