

AMENDMENT NO. 3 DECEMBER 2025
TO
IS 17790 : 2022 INSULATED FLASK FOR DOMESTIC USE — SPECIFICATION

[Page 1, clause 4.2.3 (see also amendment No. 2)] — Substitute the following for the existing:

‘Cold retention Type 1 as per Table 2 A’

[Page 1, clause 4.2.3 (see also amendment No. 2)] — Insert the following clause at the end:

‘4.2.4 Cold retention Type 2 as per Table 2 B’

(Page 3, clause 7.4) — Substitute the following for the existing:

7.4 Test for Cold Retention Capability

The temperature of water cooled to 5 °C and kept in flask, measured in accordance with the method prescribed in Annex B.

7.4.1 Thermal Insulated Flask Type 1

When measured after 6 h, temperature shall not be greater than as given in Table 2 A.

7.4.2 Thermal Insulated Flask Type 2

When measured at intervals of 1 h, 3 h, and 6 h respectively, temperature shall not be greater than as given in Table 2 B.’

(Page 3, Table 2) — Renumber the existing Table 2 as Table 2 A and modify its title as follows:

‘Table 2 A Cold Retention Capability — Type 1

(Clauses 4.2.3 and 7.4.1)’.
(Page 3, Table 2 A) — Insert the following new Table 2 B after Table 2 A:

‘Table 2 B Cold Retention Capability — Type 2

(Clauses 4.2.4 and 7.4.2)

Sl No.	Capacity of the Flask (in ml)	Temperature Attained (in °C) for Narrow Mouth			Temperature Attained (in °C) for Wide Mouth		
		After 1 h	After 3 h	After 6 h	After 1 h	After 3 h	After 6 h
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)
i)	0 to 200	13	17	22	13	17	22
ii)	201 to 400	13	17	22	13	17	22
iii)	401 to 600	12	16	21	12	16	21
iv)	601 to 800	12	16	20	12	16	20
v)	801 to 1 200	11	15	18	11	15	20
vi)	>1 200	11	15	18	11	15	20

Price Group 2

Amendment No. 3 to IS 17790 : 2022

[Page 8, clause **9.1** (see also amendment No. 2)] — Insert the following note at the end:

‘NOTE — Non-peelable sticker can be used for marking all the above details except the brand name and ISI marking. The sticker shall comply with the requirements given in Annex G.’

[Page 9, clause **B-1** (see also amendment No. 1)] — Substitute the following for the existing:

‘The cold retention capacity of an insulated flask is determined by filling cold water at 5 °C in it, as prescribed in **B-2** and measuring the temperature of water after 6 h (Type 1) and at the intervals of 1 h, 3 h and 6 h (Type 2), respectively. While carrying out the test, maintain the atmospheric conditions at 27 °C ± 2 °C and 65 percent ± 5 percent RH. The samples shall be pre-conditioned at 5 °C ± 1 °C for a minimum period of 2 h before starting the test.’

[Page 9, clause **B-2.1** (see also amendment No. 1)] — Substitute the following for the existing:

‘**B-2.1** Rinse the flask with water at 5 °C ± 1 °C, drain out water. Quickly fill flask up to the neck with the ice cold water. Allow the temperature to increase slowly to 5 °C. Close the flask with stopper and cup and note the time. Note the temperature of water in the flask at the end of 6 h (Type 1) and at the end of 1 h, 3 h and 6 h (Type 2), respectively.’

[Page 9, clause **B-2.2** (see also amendment No. 1)] — Substitute the following for the existing:

‘**B-2.2** The flask shall be taken as having passed the test, if the temperatures measured at the end of 6 h (Type 1) and 1 h, 3 h and 6 h (Type 2), are not greater than those specified in **7.4**.’

[Page 9, Annex F (see also amendment No. 2)] — Insert the following Annex G at the end:

ANNEX G						
(Clause 9.1)						
STICKER TEST METHOD WITH ACCEPTANCE CRITERIA						
Sl No.	Test	Test Duration	Sticker Test Method	Tools	Requirement	Acceptance Criteria
(1)	(2)	(3)	(4)	(5)	(6)	(7)
i)	Visual appearance	NA	Visual inspection under light	Inspection table/ White light	Free from scratches/dirt/misprint	Visually sticker shall be found ok
ii)	Material type	NA	As per supplier certificate	None	-	As decided by the product manufacturer
iii)	Dimensions (L X W)	NA	Measurement of sticker	Scale	As per approved drawing	Shall meet the dimensions declared as per drawing
iv)	Sticker thickness check	NA	3 different points	Micrometer	As per approved drawing	Shall meet the thickness declared as per drawing
v)	Manual peel test	30 s	Try peeling from edge using finger nail for 30 s	Finger nail	Sticker shall tear or get destructed. It shall not peel off cleanly-fully	Sticker shall tear or destruct. It should not peel off cleanly-fully

Amendment No. 3 to IS 17790 : 2022

Sl No.	Test	Test Duration	Sticker Test Method	Tools	Requirement	Acceptance Criteria
(1)	(2)	(3)	(4)	(5)	(6)	(7)
vi)	Blade lift test	30 s	Insert a thin blade under any one corner of sticker and attempt to lift-peel the sticker	Blade/ paper cutter	Sticker shall not lift & leave any residue	Sticker shall not lift and tear
vii)	Kerosene test (chemical / solvent resistant test)	30 s	Apply chemical/solvent (Kerosene oil) on the sticker, rub and then try to lift the sticker	Cotton	No Bubbling and print remain intact	Sticker found OK and Print remains readable
viii)	Tape lift test (High adhesion tape 0.4 gauge)	10 min	Apply high standard adhesion tape 0.4 gauge on sticker & peel back 180 degrees	Manually	Sticker should not peel off	Sticker should not peel off
ix)	Tape lift test (Paper Tape low adhesion)	Few seconds	Apply paper tape with low adhesion on sticker & peel back 180 degrees	Manually	No pull lifting and bubbling	No changes shall be observed in the sticker
x)	Water soak + Peel test	30 min	Soak applied sticker in water for 30 min and attempt to peel	Water bath	No delamination of sticker and no edge lifting	No delamination of sticker and edge lifting shall occur
xi)	Soil test	24 h	Apply mix soil (Fine / Dry partial soil) on sticker and keep under observation for 24 hours	Manually	Sticker must tear or get destructed Should not peel off cleanly-fully	Sticker must tear or get destructed Should not peel off cleanly-fully
xii)	Detergent test	24 h	Apply soapy solution on sticker and keep under observation for 24 h	Detergent and Cotton	No delamination and bubbling	No delamination and bubbling shall occur.
xiii)	Hot water temperature test	24 h	Apply sticker on hot water bottle of 95° and keep under observation	Thermometer	No delamination and edge lifting	After 24 h, no visual defect shall be observed.
xiv)	Cold water temperature test	24 h	Apply sticker on cold water bottle at 5 degree and keep under observation	Deep Freezer	No delamination and bubbling	No delamination and bubbling shall occur.
xv)	Scrubber test	20 s	Rub with scrubber on sticker along with detergent for 20 s	Scrubber	No delamination and bubbling	No delamination and bubbling shall occur.
NOTE — 15 tests have been given out of which the sticker shall comply with tests given at Sl No. (i), (ii), (viii), (x), (xii), (xiii), and (xiv).						

(MED 33)

Publication, BIS, New Delhi