

AMENDMENT NO. 1 JULY 2023

TO

IS 17790 : 2022 INSULATED FLASK FOR DOMESTIC USE — SPECIFICATION

(Page 2, clause 5.3) — Substitute the following for the existing:

‘Welding if done, shall be free from welding defects, when tested as per IS 3658 on welded joint. The welding electrode shall conform to grade 308 L (07Cr18Ni9) as per IS 5856. The weld shall be finished properly, so that when a fingure is passed on the joint, it shall be smooth.’

(Page 2, clause 7.1.1) — Substitute the following for the existing:

‘The materials used to manufacture the inner containers shall be stainless steel of grade 304 as per IS 5522 or 316/316L as per IS 6911.’

(Page 2, clause 7.1.2.1, first sentence) — Substitute the following for the existing:

‘The material used for the outer container shall be of stainless steel as per N2 grade of IS 15997 or 304 grade of IS 5522.’

(Page 2, clause 7.1.4.2, line 3) — Insert the following at the end:

‘The shore hardness of O-ring, and washer shall be in the range 45 to 55 IRHD/Shore A when tested as per ISO 48-2/ISO 48-4. The O-ring, washer and stopper shall be free of Bisphenol A (BPA) when tested as per IS 14625.’

(Page 2, clause 7.1.5) — Substitute the following for the existing:

‘The auxiliary closure(s) (if provided), also intended for use as drinking cup(s), shall be non-toxic, food grade material and shall not deform under normal conditions of use (*see* IS 9845). The materials shall not contain BPA when tested as per IS 14625.’

(Page 2, clause 7.2.1) — Substitute the following for the existing:

‘The nominal capacities may be declared one amongst upto 150 ml to 2 500 ml. Any other nominal capacities may be as agreed to between the purchaser and the manufacturer, subject to meeting the requirements of this standard. The tolerance on the nominal capacity shall be + 5 percent. No negative tolerance is permitted.’

(Page 2, clause 7.3, line 5) — Insert the following sentence at the end:

‘Separate bottle shall be used for conducting this test.’

(Page 3, clause 7.4, line 4) — Insert the following sentence at the end:

‘Separate bottle shall be used for conducting this test.’

[Page 3, Table 1, col (2), Sl No. (i)] — Substitute ‘≤ 150 - 250’ for ‘150 - 250’.

[Page 3, Table 2, col (2), Sl No. (i)] — Substitute ‘≤ 150 - 250’ for ‘150 - 250’.

(Page 6, clause 7.10, line 1) — Substitute the following for the existing:

‘The dry empty flask/bottle without stopper or plug or lever shall be weighed (weigh balance accuracy up to 10 mg).’

(Page 6, clause 7.17.1, line 2) — Substitute the word ‘mouth’ for ‘month’.

Price Group 1

Amendment No. 1 to IS 17790 : 2022

(Page 6, clause 7.17) — Insert the following new clause:

‘7.18 Endurance Test for O-Ring, Washer and Stopper

The flask after the test at 7.3 shall be subjected to this test.

7.18.1 Inspect the O-ring, washer and stopper for any defects with naked eyes or corrected vision. There shall be no defects.

7.18.2 Open and close the flask 2 500 times.

7.18.3 Inspect the O-ring, washer and stopper for any defects with naked eyes or corrected vision. There shall be no defects.

7.18.4 The flask shall pass the tests as per 7.3, 7.4 and 7.9.’

(Page 9, clause A-2, Notes) — Substitute the following for the existing:

- ‘1 In no case shall the inner container be disturbed or opened except for measuring the temperature as stated above.
2 For an inner container having the inner stopper to be fixed by screw fastening, the inner stopper shall be fastened by 1 N-m (100 N-cm).’

(Page 9, clause B-1) — Substitute the following for the existing:

‘The cold retention capacity of a flask is determined by filling cold water at 5 °C in it, as prescribed in B-2 and measuring the temperature of water after 6 h. While carrying out the test, maintain the atmospheric conditions at 27 °C ± 2 °C and 65 percent ± 5 percent RH. The samples shall be pre-conditioned at 5 °C ± 1 °C for a minimum period of 2 h before starting the test.’

(Page 9, clause B-2, Notes) — Substitute the following for the existing:

- ‘1 In no case shall the inner container be disturbed or opened except for measuring the temperature as stated above.
2 For an inner container having the inner stopper to be fixed by screw fastening, the inner stopper shall be fastened by 1 N-m (100 N-cm).’