

AMENDMENT NO. 1 FEBRUARY 2024
TO
IS 17870 : 2022 COMMERCIAL PRESSURE COOKER — SPECIFICATION

(Page 1, clause 3.6) — Substitute ‘shall’ for ‘may’ in the existing line 5.

(Page 2, clause 5.10) — Substitute the following for existing:

‘5.10 Resettable Safety Devise — Gasket release system, (gasket shall be as per IS 7466) or similar to **5.5** or a spring-loaded device. All of the above devices shall operate between 1.25 to 2.5 times the nominal operating pressure.’

(Page 4, clause 8.8) — Substitute the following for existing:

‘8.8 Test for SS Cookers —The stainless steel cookers, which have composite cooker base/bottom shall comply with the requirements given in IS 15960.’

(Page 4, clause 8.12) — Substitute the following for existing:

‘8.12 Test for Lid Stand

This is to enable the transfer of the cooker from the stove. The same stand or a separate stand may be used to keep the lid when not in use (normally the lids are kept upside down) so that the pressure gauge and vent tube does not get damaged. The stand shall be supplied with a commercial pressure cooker as per the agreement between the manufacturer and the purchaser.’

(Page 4, clause 8.12.1) — Substitute the following for existing:

‘Keep the lid on the stand. The pressure gauge or vent tube shall not get damaged. The lid shall not have scratches.’

(Page 5, clause 10.5) — Add the following at the end:

‘z) Avoid interchanging the safety components between brands and different sizes of the same brand. Safety instructions may be put on the packaging or component. The gaskets as well the PRD may have markings to help the consumers to identify the correct combination.’

(MED 33)

Price Group 1

Publication, BIS, New Delhi