

AMENDMENT NO.1 MARCH 2024

TO

**IS 18010 (PART 5/SEC 1) : 2020 UNIFIED DIGITAL INFRASTRUCTURE UNIFIED
LAST MILE COMMUNICATION PROTOCOLS STACK
PART 5 NETWORK ACCESS LAYER (IEEE 802.15.4)
SECTION 1 SPECIFICATION**

[Foreword, Paragraph 6] — Substitute ‘868 MHz’ for ‘867 MHz’.

[Foreword, Paragraph 6] — Insert the following new paragraphs after para 6 of foreword.

This standard is aligned with the enhanced spectrum mentioned in the Gazette notification G.S.R. 853(E) dated 20 Dec 2021 issued by ‘wireless planning and coordination wing’, ministry of communications [use of low power equipment in the frequency band 865-868 MHz for *Short Range Devices (exemption from licence) Rules, 2021*].

This standard includes the ‘test API requirements’ that will be necessary for developing compliance specifications.

[Page 3, clause 0 Introduction, Paragraph 6] — Substitute ‘868 MHz’ for ‘867 MHz’.

[Page 1, clause 1.2] — Substitute ‘868 MHz’ for ‘867 MHz’.

[Page 2, clause 4] — Insert the following after SI No. y) z) ‘DUT Device Under Test’.

[Page 3, clause 5.3.2, Table 3] — Substitute ‘868’ for ‘867’ in the first column.

[Page 3, clause 5.3.2, Table 3] — Substitute ‘29’ for ‘19’.

[Page 3, clause 5.3.2, Table 3, col (iv)] — Substitute ‘15’ for ‘10’.

[Page 7, clause 8.3] — Insert the following new clause after 8.3’.

‘8.4 Test Mode Requirement

LMCP device shall support below test mode requirements as specified below:

Support disabling data whitening Support transmission of 5 packets with no inter packet gap or alternatively, a continuous signal of PN9 sequence which has equivalent form may also be used. Support generating test packets per IS 18010-5-2 (*under prepration*).’