

IS QC 300200 : 2000
IEC QC 300200 (1982)

AMENDMENT NO. 1

Page 6

Sub-clause 2.2.5

Replace the existing text by the following:

2.2.5 Reverse voltage

2.2.5.1 Rated reverse voltage

The value of reverse voltage which a polar capacitor can withstand continuously at any temperature between the lower category temperature and the rated temperature (to be specified in the detail specification).

2.2.5.2 Test reverse voltage

The value of the voltage used for the purpose of carrying out the reverse voltage test.

Page 8

Table I

Add the following tests:

IS QC 300200 : 2000
IEC QC 300200 (1982)

— Group 1A

Add the following test after Resistance to soldering heat:

4.17 Component solvent resistance

— Group 1B

Add the following test after Solderability:

4.18 Solvent resistance of the marking

Page 9

Table II

Add the following test in Group 1A, after Resistance to soldering heat:

4.17 Component solvent resistance (if applicable)	Solvent: ... Solvent temperature: ... Method 2 Recovery time: ...	See detail specification
---	--	--------------------------

Add the following test in Group 1B, after Solderability:

4.18 Solvent resistance of the marking (if applicable)	Solvent: ... Solvent temperature: ... Method 1 Rubbing material: ... Recovery time: ...	Legible marking
--	---	-----------------

Page 13

Table II

Group 4B, Sub-clause 4.14, replace under “Conditions of test” in two places upper category temperature by rated temperature.

Note. — As a consequence the same change applies to the conditions of test specified in the Sub-group C4B for the reverse voltage test in the related Blank Detail Specifications, IEC Publications 384-15-1, 384-15-2 and 384-15-3.

Page 26

Sub-clause 4.14

Replace the existing text by the following:

4.14 Reverse voltage (if required by the detail specification)

4.14.1 Initial measurement

Initial measurements shall be made as prescribed by Sub-clause 4.3.1.

IS QC 300200 : 2000
IEC QC 300200 (1982)

4.14.2 The capacitors shall be subjected to the test as follows:

a) *Sub-family 1* (non-solid electrolyte capacitors with foil electrode).

Test temperature: rated temperature.

Test reverse voltage: 3 V d.c. (unless otherwise specified in the detail specification)
applied to each capacitor through a resistor of $1\,000 \pm 100\ \Omega$.

Test duration: 125 h in the reverse polarity direction with the test
reverse voltage followed by 125 h in the forward polarity
direction with the rated voltage.

b) *Sub-family 2* (non-solid electrolyte capacitors with porous anode).

If applicable, the same conditions as specified for Sub-family 1 apply.

c) *Sub-family 3* (solid electrolyte capacitors with porous anode).

Test temperature: rated temperature.

Test reverse voltage: $0.1 \times$ rated voltage, but with max. 3 V d.c. (unless otherwise
specified in the detail specification).

The voltage applied to each capacitor shall be from a voltage
source with a minimum impedance of $0.1\ \Omega/\text{V}$ with a maximum
of $3\ \Omega$. (The voltage shall be applied gradually as described in
Sub-clause 4.12.2 a).

Test duration: 125 h in the reverse polarity direction with test reverse voltage
followed by 125 h in the forward polarity direction with the rated
voltage.

4.14.3 *Final measurements and requirements*

After recovery the capacitors shall be visually examined and measured and shall meet the
requirements given in Table II.

Page 27

Add the following sub-clauses:

4.17 *Component solvent resistance*

Sub-clause 4.31 of IEC Publication 384-1.

4.18 *Solvent resistance of the marking*

Sub-clause 4.32 of IEC Publication 384-1.